

CHANTRE, G. et ROZENBERG, P. (1997). «Can drill resistance profiles (Resistograph) lead to within-profile and within-ring density parameters in Douglas fir wood»? In *Timber management toward wood quality and end-product values. CTIA/IUFRO Int. Wood Quality Workshop*, pp. 41-47.

EMERSON, R., POLLOCK, D., KAINZ, J., FRIDLEY, K., MCLEAN, D. et ROSS, R. (1999). *Nondestructive evaluation techniques for timber bridges. NDT.net* 4, 1-5.

GANTZ, C. (2002). «Evaluating the efficiency of the resistograph to estimate genetic parameters for wood density in two softwood and two hardwood species». Master of Science, North Carolina State University.

GRUBER, F. (2001). Comparing results to identify defects in wood of Norway spruce (*Picea abies* L. Karst.) using the drill devices Resistograph 1410, Teredo and Impulshammer-sound system IML. II. Drill diagrams on red-rot wood and discussion. *All. Forst Jagd Zeit.* 172, 1-7.

HELMS, D. et NIEMZ, P. (1993). «New application of the drill resistance method for quality evaluation of wood and wood products». In *Ninth International Symposium on Nondestructive Testing of Wood*. pp. 95-102.

MATTHECK, C. et BETGHE, K. (1993). VTA - «Visual Tree defect Assessment». In *9th Int. Meet. Non-Destructive Testing*. Madison, USA.

MOORE, W. (1998). Outillage pour la détection des défauts internes des arbres. *P.H.M. Revue horticole* 392, 38-41.

RINN, F., SCHWEINGRUBER, H. et SCHAR, E. (1996). Resistograph and X-Ray density charts of wood comparative evaluation on drill resistance profiles and X-Ray density charts of different wood species. *Holzforschung* 50, 303-311.

SHIGO, A. (1991). *Modern arboriculture : a systems approach to the care of trees and their associates*. Durham, 425 p.

TOUSSAINT, A., KERVYN, V., DELCROIX, B. BAUDOIN, J-P. (2002). Analyse de l'impact physiologique et économique de l'élagage des arbres d'alignement en port libre. *Biotechnol. Agron. Soc. Environ.* 6, 99-107.

WINSTORFER, P., XU, W. et WIMMER, R. (1995). Application of a drill resistance technique for density profile measurement in wood composite panels. *For. Prod. J.* 45, 90-94.