

Click on vibe (or vibe.bat) to launch the program!

Then select

File -> Open video file for COLOR processing -> and choose sequence (or sequence.avi)

Please note that the program intentionally stops after about 5 minutes and 10.000 processed frames.

If you want to save your results or modify the parameters, it is possible to run the program with the appropriated arguments.

----- vibe-gray.exe -----

Usage:

C:\mypath\vibe-gray.exe --input [-i] <input-file.avi> [--output [-o] <output-file.avi>] [options]

Options:

--display-result-only [-ro] : display (and save) vibe segmentation exclusively  
--nb-samples [-n] <value> : number of samples per pixel model (default: 20)  
--matching-threshold [-t] <value> : threshold used to compare pixel samples to current pixel values  
(default: 20)  
--matching-number [-s] <value> : number of close samples needed to classify a current pixel value as  
background (default: 2)  
--subsampling-factor [-f] <value> : amount of random temporal subsampling (default: 16)

Examples:

If you wish to read from myvideo.avi, specify some parameters, display both images, and ouput a sequence of jpeg files:

\$> C:\mypath\vibe-gray.exe -i myvideo.avi -n 10 -s 3 --subsampling-factor 32 -o result-%010d.jpg

If you wish to read from an axis netcam, just display (and save) the segmented image, and output as an .avi file:

\$> C:\mypath\vibe-gray.exe -i http://192.168.1.12/mjpg/video.mjpg --display-result-only -o result.avi

If you wish to read from a sequence of jpeg images, output to an mpeg file, and display both images:

\$> C:\mypath\vibe-gray.exe -i image-%10d.jpg -o result.mpg

----- vibe-rgb.exe -----

Usage:

C:\mypath\vibe-rgb.exe --input [-i] <input-file.avi> [--output [-o] <output-file.avi>] [options]

Options:

--display-result-only [-ro] : display (and save) vibe segmentation exclusively

```
--nb-samples [-n] <value>      : number of samples per pixel model (default: 20)
--matching-threshold [-t] <value>    : threshold used to compare pixel samples to current pixel values
(default: 20)
--matching-number [-s] <value>     : number of close samples needed to classify a current pixel value as
background (default: 2)
--subsampling-factor [-f] <value>   : amount of random temporal subsampling (default: 16)
```

Examples:

If you wish to read from myvideo.avi, specify some parameters, display both images, and ouput a sequence of jpeg files:

```
$> C:\mypath\vibe-rgb.exe -i myvideo.avi -n 10 -s 3 --subsampling-factor 32 -o result-%010d.jpg
```

If you wish to read from an axis netcam, just display (and save) the segmented image, and output as an .avi file:

```
$> C:\mypath\vibe-rgb.exe -i http://192.168.1.12/mjpg/video.mjpg --display-result-only -o result.avi
```

If you wish to read from a sequence of jpeg images, output to an mpeg file, and display both images:

```
$> C:\mypath\vibe-rgb.exe -i image-%10d.jpg -o result.mpg
```

---