

GEOTHERMAL USE OF OLD FLOODED MINES: FROM A RISKY TRIAL-AND-ERROR APPROACH TOWARDS CHALLENGING PREDICTIVE SIMULATIONS

Alain Dassargues, O. Vopat, Ph. Orban, S. Brouyère

Hydrogeology & Environmental Geology, Urban & Environmental Engineering research unit, ULiège, Belgium

Contact Information: Alain Dassargues, Urban & Environmental Engineering, ULiège, Belgium, Email:

Alain.Dassargues@ULiege.be

In urban areas, flooded abandoned mines could be used for shallow geothermal purposes. Such aquifer thermal energy storage (ATES) systems, using heat-pumps and an open loop with a groundwater pumping and re-injection doublet, are highly challenging and uncertain with risks undermining the ultimate feasibility. The true geometry of the interconnected network made of old open galleries and shafts can be highly complex and partially unknown/forgotten. Indeed, high-velocity water flow is expected in this network, while low-velocity groundwater flow occurs in less permeable fractured and porous rock massif. For the latter, hydraulic conductivity values have been significantly increased by mining exploitation. Logically, hot water is pumped in the deep parts of the open network, and cold water can be re-injected in the shallower parts (i.e. in shallower galleries or fractured rocks). A seasonal inversion could be planned for building cooling during the hot season.

So far, those who have successfully moved to such a heat production have adopted a risky strategy that can be qualified as a trial-and-error procedure. Indeed, after some time, a cold water breakthrough is observed as mixing with the pumped deep hot waters. In fact, this strategy needs to continually adapt the project by integrating several pumping/injection wells, seasonal variations, and even a further integration of other renewable energy sources in a local smart grid. This ends up with very significant investments that are rarely planned at the beginning of the project.

Another approach could be to involve more accurate hydrogeological characterization of the old mined zones for detailed simulations of the groundwater flow and the associated temperature evolution in pumping zones. The challenge is huge because characterization and numerical issues are to be solved. Added to the often unknown complexity/heterogeneity of the galleries network conjugated to those of the mined geological formations, variable density water flow and coupled heat transport must be taken into account using a dedicated software allowing to simulate a combination of high-velocity 'pipe-like' water flows (in the galleries) and porous/fractured groundwater flow (in the rock matrix). An example of a simplified but realistic situation is given showing numerical results with the differentiated temperatures as a consequence of heat/cold propagation in the galleries, shafts and the fractured rocks. This kind of numerical simulations allow to anticipate the temperature changes affecting the future (short-, mid-, and long-term) efficiency of the geothermal system as well as possible environmental impacts.

Real cases in relation with future projects, should ideally be simulated using such detailed approach, but numerical simulation with true data will surely not be an easy way. However, it is only on the basis of accurate predictions (i.e., about long term efficiency and possible expected impacts) that the financial risk could be assessed for decisions.

References

- Brouyère, S., Orban, P., Wildemeersch, S., Couturier, J., Gardin, N. and Dassargues, A., 2009, The Hybrid Finite Element Mixing Cell Method: A New Flexible Method for Modelling Mine Groundwater Problems, *Mine Water & the Environment* 28(2): 102-114
- Dassargues A., 2018. Hydrogeology: groundwater science and engineering, 472p. Taylor & Francis CRC press, Boca Raton.

- Eppelbaum, L., Kutasov, I. and A. Pilchin. 2014. Applied Geothermics, Series: Lecture Notes in Earth System Sciences. Berlin Heidelberg :Springer-Verlag.
- Florea, L. J., Hart, D., Tinjum, J. and C. Choi. 2017. Potential impacts to groundwater from ground-coupled geothermal heat pumps in district scale. *Groundwater* 55(1): 8-9.
- Fox, D. B., Koch, D.L. and J. W. Tester. 2016. An analytical thermohydraulic model for discretely fractured geothermal reservoirs, *Water Resources Research* 52 : 6792–6817.
- Graf T. and C.T. Simmons. 2009. Variable-density groundwater flow and solute transport in fractured rock: Applicability of the Tang et al. [1981] analytical solution. *Water Resources Research* 45 :W02425.
- Hamm, V. and B. Bazargan Sabet. 2010. Modelling of fluid flow and heat transfer to assess the geothermal potential of a flooded coal mine in Lorraine, France. *Geothermics* (39) :177-186.
- Hermans, T., Wildemeersch, S., Jamin, P., Orban, P., Brouyère, S., Dassargues, A. and F. Nguyen. 2015. Quantitative temperature monitoring of a heat tracing experiment using cross-borehole ERT, *Geothermics* 53 : 14-26.
- Huysmans, M. and A. Dassargues. 2005. Review of the use of Peclet numbers to determine the relative importance of advection and diffusion in low permeability environments. *Hydrogeology Journal* 13(5-6) : 895-904.
- Kabuth, A., Dahmke, A., Beyer, C., Bilke, L., Dethlefsen, F., Dietrich, P., Duttmann, R., Ebert, M., Feeser, V., Görke, U.-J., Köber, R. Rabbel, W., Schanz, T., Schäfer, D., Würdemann, H. and S. Bauer. 2017. Energy storage in the geological subsurface: dimensioning, risk analysis and spatial planning: the ANGUS+ project. *Environmental Earth Science* 76: 23.
- Klepikova, M., Wildemeersch, S., Jamin, P., Orban, Ph., Hermans, T., Nguyen, F., Brouyere, S. and A. Dassargues. 2016. Heat tracer test in an alluvial aquifer: field experiment and inverse modelling, *Journal of Hydrology*, 540 :812-823.
- Love, A. J., Simmons, C.T. and D. A. Nield. 2007. Double-diffusive convection in groundwater wells, *Water Resources Research* 43(8) : W08428.
- Ma, R. and Ch. Zheng. 2010. Effects of density and viscosity in modeling heat as a groundwater tracer. *Ground Water* 48(3) : 380–389.
- Stauffer, F., Bayer, P., Blum, Ph., Molino-Giraldo, N. and W. Kinzelbach. 2014. Thermal use of shallow groundwater. Boca Raton: CRC Press, Taylor & Francis Group.
- Vopat, O., 2017, Modélisation des caractéristiques hydrogéologiques liées à une exploitation géothermique d’anciennes mines, Master Thesis, ULiège.
- Wildemeersch, S., Brouyère, S., Orban, P., Couturier, J., Dingelstadt, C., Veschkens, M. and Dassargues, A., 2010, Application of the Hybrid Finite Element Mixing Cell method to an abandoned coalfield in Belgium, *Journal of Hydrology* 392 (3-4): 188-200.
- Wildemeersch, S., Jamin, P., Orban, P., Hermans, T., Klepikova, M., Nguyen, F., Brouyère, S. and A. Dassargues. 2014. Coupling heat and chemical tracer experiments for estimating heat transfer parameters in shallow alluvial aquifers. *Journal of Contaminant Hydrology* 169(0): 90–99.