LCA of a fuel cell using gold for the bipolar plates

Saïcha Gerbinet¹, A.-P. Romano², Giuseppe Caldarella¹,

Nathalie Job¹, Sylvie Groslambert¹, Angélique Léonard¹

Saicha.gerbinet@uliege.be

¹Department of Chemical Engineering


Université de Liège

http://chemeng.uliege.be

²Materia Nova Research Center










2 solutions






Solution 2:



Fuel cells





HYLIFE



- Optimize lifetime and efficiency of materials for fuel cell
- Environmental impact

























Bipolar plates









System boundaries





Results






ReCiPe MidPoint (H)

Results






ReCiPe MidPoint (H)

Deposit?






ReCiPe MidPoint (H)

Gold in the whole bipolar plate?





ReCiPe MidPoint (H)

Reduce the impact of gold?



▶ 2 solutions!



Solution 1:


Reduce the impact of gold?



- ▶ 2 solutions!
 - Optimize the bath use
 - Use recycled gold

Number of plates per bath?





ReCiPe MidPoint (H)


Recycled gold



- Difficulty to find reliable information
 - Bibliographic studies
 - ► Use of: « Gold treatment of precious metal from electronics scrap, in anode slime, precious metal extraction | Alloc Def, U »


Recycled gold






In the fuel cell?





In the fuel cell?






ReCiPe MidPoint (H)

In the fuel cell?






ReCiPe MidPoint (H)

Gold?






ReCiPe MidPoint (H)

Conclusion





Conclusion/perspectives



- Large contribution of gold
 - Does the performance improvement justify the use of precious metal?
- Recycling?
 - Lack of data
 - Not always an improvement of environmental impact
 - Availability?
 - Design to allow recycling?