GC and GC×GC based approaches for the molecular characterization of complex matrices related to alternative energy sources

Pierre Giusti ^{1,2,3*}, Laura Freije-Carrelo^{1,2,4}, Javier García-Bellido⁴, Eliane Lazzari ^{1,2,5,7}, Marco Piparo ^{1,2}, Gaetan Burnens^{1,2}, Jean-françois Focant⁵, Giorgia Purcaro⁷, Mariella Moldovan⁴, Suzuki Takamasa⁸, Ryo Takechi⁸, Takaaki Hiraoka⁹, Haruhiko Miyagawa⁸, Brice Bouyssiere^{2,3}, Jorge Ruiz-Encinar⁴.

¹TotalEnergies OneTech R&D, TRTG, BP 27, 76700 Harfleur, France.

²International Joint Laboratory-iC2MC: Complex Matrices Molecular Characterization, BP27, 76700 Harfleur, France. ³Université de Pau et des Pays de l'Adour, E2S UPPA, CNRS, IPREM, Institut des Sciences Analytiques et de Physico-chimie pour l'Environnement et les Matériaux, UMR5254, Hélioparc, 64053 Pau, France.

⁴Department of Physical and Analytical Chemistry University of Oviedo, Av. Julián Clavería, 3300, Oviedo, Spain.
 ⁵Organic and Biological Analytical Chemistry Group, MolSys Research Unit, University of Liège, Liège, Belgium.
 ⁶ GEPEA, UMR 6144, Energy Systems and Environment Department, IMT Atlantique, 04 rue Alfred Kastler, CS 20722, 44307, Nantes Cedex 3, France.

⁷Gembloux Agro-Bio Tech, University of Liège, Gembloux, Belgium.
⁸GCTA Business Unit, Analytical & Measuring Instruments Division, Shimadzu Corporation
⁹European Innovation Center, Shimadzu Europa GmbH

* email: pierre.giusti@totalenergies.com

Abstract

The continuing global energy demand makes biomass feedstock one of the promising resources to cope with more sustainable and greener energy challenges and reduce the dependency on fossil-based energy sources. Animal fats as well as vegetable oils, and tomorrow biomass-pyrolysis oils, represent interesting new sources to produce biofuels. In the same way, the conversation of the large amount of plastic residue by mechanical or chemical techniques, such as pyrolysis, can also reach the needs for circular economy. Regarding the composition, besides triacylglycerols, biomasses feedstocks contain a wide range of other contaminants which can affect the technical properties of the raw fat feedstock. For example, higher acid content can cause severe corrosion in the fuel supply system of engines, impacting the catalytic transesterification process, while the possible condensation of aldehydes and ketones could lead to the formation of gums [1-3]. Coming back to plastic pyrolysis oil, even though their chemical composition shows similarities with fossil-based hydrocarbons fluids/cuts, e.g. PIONA related compounds, some N- and S- or O-containing compounds can be found and could be related to adverse qualities of the final product. In both feedstock cases, an exhaustive characterization by GC and GC×GC hyphenated with mass spectrometry of these compounds was made and is fundamental for performing the most appropriate pretreatment. In addition to these targeted impurities, molecule family type speciation was performed as it is key for the molecular modeling of biofuel properties. Despite this powerful GC×GC-MS based approaches, there is still a lack in the detection mode for the detailed and quantitative characterization of oxygenated compounds, especially when biomasses biofuel is the objective. For this reason, a new GC detector able to provide compound-independent quantification of C, H, N and S in complex samples was developed in the past years thanks to a collaboration between the universities of Oviedo (Spain) and Pau (France) and TotalEnergies [4]. A commercial GC-MS was modified by using a combustion interface between the GC and the final MS analysis in order to detect every organic compound present as volatile species formed during their combustion (CO2, H2O, NOx, SOx). It this therefore possible to achieve a speciesindependent generic and simultaneous quantification of C, H, N and S. Importantly, GC-combustion-MS can be used as well for the detection of oxygen if enriched 180-oxygen is used for the combustion (WO2017/114654 patent)

Keywords:

New feedstocks; GC-combustion-MS; Molecular characterization; Oxygen compounds detection. References

[1] M.S. Talmadge, R.M. Baldwin, M.J. Biddy, R.L. McCormick, G.T. Beckham, G.A. Ferguson, S. Czernik, K.A. Magrini-Bair, T.D.

Foust, P.D. Metelski, C. Hetrick, M.R. Nimlos. Green Chem. 16 (2014) 407-453.

[2] D. Castello, M.S. Haider, L.A. Rosendahl. Renew. Energy 141 (2019) 420-430.

[3] M. Beccaria, A.L.M. Siqueira, A. Maniquet, P. Giusti, M. Piparo, P.H. Stefanuto, J.F. Focant. J. Separ. Sci. 44 (2021) 115–134

[3] L. Freije-Carrelo, J. Garci-Bellido, L.A. Sobrado, M. Moldovan, B. Bouyssiere, P. Giusti, J.R. Encinar. Chem. Comm. 19 (2020), 2905-2908.