

First coherent structure in elasto-inertial turbulence

Y. Dubief^{1,*}, J. Page², R. R. Kerswell³, V. E. Terrapon⁴, and V. Steinberg⁵

¹ *Department of Mechanical Engineering, University of Vermont, Burlington, VT, USA*

² *School of Mathematics, University of Edinburgh, UK*

³ *Department of Applied Mathematics and Theoretical Physics, University of Cambridge, Cambridge, UK*

⁴ *Aerospace and Mechanical Engineering Department, University of Liege, Belgium*

⁵ *Department of Physics of Complex Systems, Weizmann Institute of Science, Rehovot, Israel*

(Dated: June 29, 2022)

Two dimensional channel flow simulations of FENE-P fluid in the elasto-inertial turbulence regime reveal distinct regimes ranging from chaos to a steady travelling wave which takes the form of an arrowhead structure. This coherent structure provides new insights into the polymer/flow interactions driving EIT. A set of controlled numerical experiments and the study of transfer between elastic and turbulent kinetic energies highlight the role of small- and large-scale dynamics in the self-sustaining cycle of chaos in EIT flows.

INTRODUCTION

Elasto-inertial turbulence (EIT) [1, 2] is a chaotic state occurring in weakly inertial to strongly inertial channel and pipe flows with polymer additives. Given an appropriate initial perturbation, local fluctuations of velocity gradient stretch polymers, which exert a local stress feedback on the flow, thereby sustaining a level and an organization of velocity gradient fluctuations. The exact mechanism of interaction between flow instabilities and polymer instabilities remains poorly understood. EIT belongs to the category “active scalar turbulence” where a molecule (*e.g.* polymers), an organism (*e.g.* bacteria, microswimmers) or a field (*e.g.* magnetic field) is two-way coupled with the flow and this coupling has a direct influence on, or may drive, turbulence. The present study is concerned with a sub-category of active turbulence, that of additive-driven chaos. The dynamics is a self-sustaining cycle where the chaotic dynamics of the scalar induces flow perturbations that in turns sustain the scalar’s chaotic dynamics. Such cycles are observed in active turbulence induced by bacteria or microswimmers [3] or nematic fluids [4], at very low Reynolds number. Also in inertialess flows, and relevant to the present study, polymer additives create elastic turbulence [5, 6] in flows with curved streamlines.

EIT, elastic turbulence, active nematic turbulence or active turbulence induced by bacteria promote mixing in flows either dominated by diffusion or where Newtonian instabilities cannot survive in the absence of the active scalar. This chaos has practical applications, such as heat transfer enhancement [7, 8] or promoting emulsification [9] for elastic turbulence. From a theoretical perspective, these flows are fundamentally different from classical turbulence, specifically with respect to energy transfers between large and small scales. In the case of EIT, a numerical experiment consisting of increasing the molecular diffusivity of the polymer model demonstrated that the small-scale dynamics of polymers is critical to sustaining chaos [10]. Our ability to harness and control the mixing

power of such an active scalar ultimately requires the understanding of how polymer and flow scales interact, and of how the flow transfers energy to the active scalar and *vice versa*. These energy transfers, in turbulent systems where they are identified, are directly linked to coherent structures. For instance, the self-sustaining dynamics of wall-bounded turbulence relies on quasi-streamwise vortices which interact with streaks, elongated regions of high- and low-momentum fluid, to create vertical energy transfer to and from the very near wall regions [11, 12].

The notion of coherent structures is ubiquitous in the theory of turbulence, even though its definition remains empirical. A coherent structure is typically defined as a region of the flow whose dynamics (a) has a significant energetic impact and (b) whose dynamics remain correlated for sufficiently large time scales, at least larger than the smallest time scale of turbulence, defined by Kolmogorov’s theory [13] in classical turbulence. So far, the study of EIT has revealed structures in the form of thin, elongated sheets where polymers are much more stretched than anywhere else in the flow [1]. Attached to these sheets are trains of spanwise, cylindrical regions of positive and negative $Q := -\frac{1}{2}\partial_j u_i \partial_i u_j$, the second invariant of the velocity gradient tensor ($\partial_j u_i$ is the j -derivative of the velocity component i) [14, 15]. Q is the basis for a common vortex identification method in classical turbulence [16], as it is the difference between the local norm of the rotation rate and the strain rate. It is also related to local minima of pressure through the Laplacian of pressure $2Q = \partial_i \partial_i p$. However, in EIT flows, the regions of positive Q , where the local rotation rate is larger than the local strain rate, are only strong enough to produce oscillations in the local streamlines rather than vortices [14].

The connection between the trains of positive and negative Q -structures and the thin sheets of highly stretched polymers was discussed [15] on the basis of the elliptic equation for pressure,

$$\partial_i \partial_i p = 2Q + \frac{1-\beta}{Re} \partial_i \partial_j T_{ij}, \quad (1)$$

where p is the pressure, and T_{ij} and $(1 - \beta)/Re$ are the polymer stress tensor and viscosity parameters related to the polymer solution, both of which will be defined later. This equation is the result of applying the divergence operator to the momentum transport equation. Equation (1) is also believed to be a key equation of elastic turbulence [17] as it connects polymer dynamics, pressure and the nonlinear inertial effect (Q is the divergence of the advection term in the Navier-Stokes equation). Note that this last term is small compared to the other terms in the regimes of low Reynolds number considered for this study, even at $Re = \mathcal{O}(1000)$.

Due to the elliptic nature of Eq. (1), it can be anticipated that small scale perturbations in polymer stress, amplified by the second spatial derivative, have an instantaneous, local and global effect on the pressure. Local variations of pressure would in turn translate into velocity perturbations and creation of local strain, which drives polymer stretching. Recently, it has also been argued that structures connected to Newtonian Tollmien-Schlichting instability waves may play a role in EIT [18]. There is numerical evidence that weakly chaotic states, which arise in a sequence of bifurcations from the Newtonian travelling waves, can be continued into regions of the parameter space where EIT has also been observed. However, this work has been restricted to very dilute solutions with weak polymer activity and it is currently unclear whether the polymer sheets are the cause or the effect of the relevant instabilities in EIT.

The present study reports the discovery of a first coherent structure in EIT which can dominate the dynamics of the flow. Under certain conditions, the flow becomes steady and symmetrical about the mid-plane of the channel with the coherent structure being the only, but significant, departure from a laminar flow. Based on the structure of the associated polymer stress, this structure looks like an arrowhead which points in the direction of the flow and propagates at a constant speed downstream. Under certain conditions, the ‘arrowhead’ may become a robust attractor with complete elimination of chaos. At the macroscopic level, the presence of the resulting travelling wave shows in a steady drag increase.

The very existence of the structure is particularly exciting for a turbulence that does not follow the classical properties of Newtonian turbulence. Power spectra show steeper decay of energy [2] than the $-5/3$ decay of the classical cascade of energy [13]. The numerical experiments of Sid *et al.* [10] showed that EIT can only be sustained if the small scale dynamics of polymer stress is accurately captured in simulation, strongly suggesting an inverse energy cascade from polymer to flow perturbations. Due to its chaotic nature, analyses of EIT have been necessarily statistical in the absence of any simpler manifestation of the phenomenon. In statistics, it is often difficult to conclusively isolate the fine details of complex dynamics. The arrowhead – the first coherent structure

to be isolated from EIT – provides a far simpler investigative framework thanks to its steadiness in an appropriately travelling frame. The goals of the present study are to introduce the existence of the arrowhead structure and to identify and compare the energy transfer between polymers and flow for it and for the otherwise chaotic structures of EIT.

METHODS

The simulations discussed here solve the FENE-P (finitely extensible nonlinear elastic-Peterlin) viscoelastic model in 2D using the algorithm [19] used to discover EIT [1, 2, 14, 15, 20]. The computational domain is a channel with periodic boundary conditions over a length of $2\pi n_x h$ ($n_x = 1$ for most simulations discussed here) in the streamwise direction $x = x_1$ and walls at $z = x_2 = \pm h = \pm 1$. Note that graphs of wall-normal profiles of statistical quantities are shown as function of the distance from the wall,

$$\xi = h - z. \quad (2)$$

The flow is divergence free, $\partial_i u_i = 0$, where u_i is the velocity vector. The momentum transport equation is

$$D_t u_i = -\partial_i p + \frac{\beta}{Re} \partial_j \partial_j u_i + \frac{1 - \beta}{Re} \partial_j T_{ij} + f(t) \delta_{1i}, \quad (3)$$

non-dimensionalised by the bulk velocity U_b , the half-height of the channel h and the zero-shear rate viscosity of the polymer solution ν_0 , so the Reynolds number is defined as $Re := U_b h / \nu_0$. The material derivative is defined as $D_t := \partial_t + u_k \partial_k$. The parameter β is the ratio of solvent viscosity ν_s to ν_0 . The force term $f(t)$ drives the flow by enforcing constant mass flow, which is applied in the x direction as indicated by the Kronecker tensor δ_{ij} . The polymer stress tensor T_{ij} is obtained from the conformation tensor $C_{ij} = \langle q_i q_j \rangle$, which represents the local phase average of the product of the end-to-end vector q_i of each polymer molecule. Its transport equation is

$$D_t C_{ij} = C_{ik} \partial_k u_j + \partial_k u_i C_{kj} - T_{ij} + \frac{1}{ReSc} \partial_k \partial_k C_{ij} \quad (4)$$

with

$$T_{ij} = \frac{1}{Wi} \left(\frac{C_{ij}}{1 - C_{kk}/L^2} - \delta_{ij} \right). \quad (5)$$

The first two terms on the RHS of Eq. (4) represent the stretching caused by the flow and the third term (Eq. 5) is the entropic term or spring term that tends to bring stretched polymers back to their least energetic configuration of being coiled. Three parameters define the FENE-P model: L the maximum extensibility of polymers, Wi the ratio of polymers’ relaxation time scale λ_p to the flow time scale λ_f , and β the ratio of the solvent




FIG. 1. Characteristic snapshots of the four distinct regimes: CR, chaotic regime (a,b), CAR chaotic arrowhead regime (c,d), IAR, intermittent arrowhead regime (e,f) and SAR, steady arrowhead regime (g,h), identified in the $L_x = 2\pi$ -computational domain. The left column shows contours of first normal stress difference on a log-scale colormap, the right column provides the corresponding pressure contours on a linear scale. In Figs. (a,b), the green dots identify the location of low and high pressure regions in the lower-half of the channel.

viscosity to the zero shear rate viscosity of the solution. Throughout this article, the flow time scales used to normalize the relaxation time scale is the integral time scale of the flow h/U_b . Global artificial diffusion is employed to regularize the hyperbolic Eq. (4) [21] with a high Schmidt number Sc of 1000 for all production runs, consistent with our earlier paper [22].

Production runs use $512n_x \times 513$ grids and grid convergence is verified on $1024n_x \times 1025$ for at least one simulation for each regime identified here. Similarly, one simulation per regime is carried out with lower Schmidt numbers to confirm that the regime is not an artefact of energy build up at small scales. The grid is stretched in the wall-normal direction and the height of the first cell




FIG. 2. Temporal signals of drag increase DI for examples of the four different regimes highlighted in Fig. 1. Colors correspond to simulations introduced in Fig. 1.

is critical to resolution of wall polymer stress in chaotic regimes. For the Reynolds number considered, the appropriate wall resolution is found to be $\Delta z_{min}/h = 10^{-4}$, which is about two orders of magnitude smaller than Kolmogorov scale. The time step is $10^{-3}h/U_b$ for most simulations and as low as $10^{-4}h/U_b$ for simulations with large L and Wi for numerical stability reasons.

Lastly the impact of the Schmidt number is assessed for at least one simulation per regime of EIT. As the Schmidt number increases, the number of points where C_{ij} loses its positiveness increases. Careful investigation of the number of nodes, and their location, where $\det(C_{ij}) < 0$ reveals that they are in regions of low-polymer extensibility, attached to regions of high extensibility. Using the SAR simulation ($L = 100, Wi = 100, \beta = 0.9$) as an example, the number of points where $\det(C_{ij}) < 0$ is 1% for 512^2 , $Sc = 1000$ and drops to less than 0.1% for 512^2 , $Sc = 50$. The loss of positiveness results in small negative values of one of the diagonal components, of the order of or smaller than 10^{-2} . Increasing the resolution and decreasing the time step resolves the loss of positiveness but at great computational costs. Grid convergence analysis and spectral analysis however shows that the loss of positiveness, even for 1% of the nodes, does not affect the dynamics. More information on the effects of the Schmidt number can be found in Appendix.

Supporting materials for the grid convergence study are provided in the Appendix.

VISUAL IDENTIFICATION OF THE DIFFERENT STRUCTURES

The identification of the different regimes begins in a domain of fixed length, $L_x = 2\pi$ (the influence of the domain's length will be discussed later). At $Re = 1000$, the investigation of flows with $L = 50, 100, 200, 500$, $0 \leq Wi \leq 250$ and $\beta = 0.9$, as well as $\beta = 0.97$ and 0.5 (neither shown here) reveals four distinct regimes based on the spatial and temporal structure of polymer stress

and pressure. The polymer stress is represented by the first normal stress difference defined as

$$N_1 := \tilde{T}_1 - \tilde{T}_2, \quad (6)$$

where \tilde{T}_i are the eigenvalues of T_{ij} . The choice of N_1 is motivated by its role in extensional viscosity $\nu_E \propto N_1/\dot{\epsilon}$, where $\dot{\epsilon}$ is the elongational rate [23]. Note that the structures captured by contours of N_1 are similar to structures of the elastic energy

$$e_p := -\frac{1}{2} \frac{1-\beta}{ReWi} L^2 \ln(1 - C_{kk}/L^2). \quad (7)$$

Figure 1 shows snapshots of contours of N_1 and p that are representative of the different regimes observed in the ($n_x = 1$)-domain across our parameter space.

The first regime, labelled the chaotic regime (CR), is the original state in which EIT was discovered [1, 2, 14, 20] and observed in subsequent studies [10, 18]. CR consists of thin sheets of large polymer stress emanating from the near-wall region and stretching toward the centerline at a shallow angle (Fig. 1a). The pressure signature (Fig. 1b) is reminiscent of that corresponding to Tollmien-Schlichting (TS) waves, a series of alternating low and high pressure regions, whose vertical extent does not exceed the channel half-height. This comparison is in agreement with the instability discussed by Shekar *et al.* [18].

In Figs. 1(a,b), regions of low- and high-pressure in the lower half of the channel are identified by green dots to search for a correlation between the dynamics of p and N_1 . When the undulations of a sheet of large N_1 are locally convex (concave) with respect to their distance from the wall, the local pressure is high (low). The same observation can be made for the top half of the channel. Undulations of high N_1 or polymer stress sheets are a signature of chaos in EIT.

Figures 1(c,d) reveal the emergence of a peculiar structure: the arrowhead structure. In this second regime, labelled the chaotic arrowhead regime (CAR), two sheets of large N_1 , one from the upper half, the other from the lower half, join at the centerline. The near-wall structure of sheets is similar to that of CR. The pressure field (Fig. 1d) appears to be dominated by the arrowhead with a low-pressure region ahead of the junction and a high-pressure region in the wake of the junction. This regime remains very chaotic, however the arrowhead remains a robust structure, observable throughout the whole duration of the simulation $4000h/U_b$.

The third regime, labelled the intermittent arrowhead regime (IAR), undergoes extended periods of quasi-steadiness, and short periods of chaos. Figures 1(e,f) depict an instant of intense chaos, whereas periods of quasi-steadiness are similar to the fourth regime discussed below (Figs. 1g,h). The striking difference between CAR and IAR is the higher definition of the arrowhead struc-

ture and the presence of a bullet-shaped high pressure region, in the wake of the junction. High- and low-pressure regions near the wall follow the same correlation with the local undulations of N_1 -sheets as observed in CR.

The fourth regime, labelled the steady arrowhead regime (SAR), is the the main discovery of this article. The structure, shaped like an arrowhead, exhibits perfect symmetry across the centerline as depicted in Figs. 1(g,h). The pressure distribution (Fig. 1b) shows a bullet-shaped high-pressure region located in the inside of the arrowhead, and shock-like feature perpendicular with the flow located at short distance downstream of the nose. Away from the shock, both upstream and in the wake of the arrowhead's junction, isobars are perpendicular with the flow, as one would expect for a laminar flow. The convection speed was measured with two approaches. The first is traditional space-time correlations. The second uses an optimization method (standard steepest gradient) to minimize the cost function $\min_{U_c} \|N_1(x, y, n\Delta T_s) - N_1(x + U_c\Delta T_s, y, (n+1)\Delta T_s)\|_\infty$ where $\Delta T_s = h/U_b$ is the sampling frequency of full flow and polymer fields and U_c is the solution of the optimization process, the convection speed.

The supplemental material [24] shows 4 sample movies of the 4 cases displayed in Fig. 1. The movie corresponding to SAR shows the same flow twice. The upper image is $N_1(x, y, t)$ and the lower is $N_1(x + U_c(t - t_0), y, t)$, where t_0 is the time of the first frame. The authors recognize that the transitions between regimes merit careful attention as their study is likely to hold critical clues to mechanisms creating chaos in EIT flows. Such a study however deserves its own publication.

REGIMES AND DRAG INCREASE

From Fig. 1, the distinction between CAR and IAR is not obvious. These regimes find their names in the temporal signal of drag increase (DI), defined as the percentage increase relative to the laminar drag for the same viscoelastic conditions. In a constant mass flow simulation, the drag is proportional to the pressure gradient necessary to impose the prescribed mass flow. As depicted in Fig. 2, the temporal evolution of the CR of Figs. 1(a,b) is highly disordered or chaotic. The simulation corresponding to the CAR is also chaotic. The intermittent regime (IAR) is quasi periodic, with large fluctuations of DI . The large peaks of DI corresponds to the type of chaotic state displayed in Fig. 1(e), the valleys to a quasi-steady arrowhead structure. Finally the signal for SAR is flat as it should be for a travelling wave.

The average of the temporal signal of DI is performed on several thousands of characteristic time scale h/U_b ranging from 4000 for CR to 10,000 for one of our SAR simulations (6,000 for the others). Technically, the long




FIG. 3. (a) Drag increase for different L and Wi , $\beta = 0.9$, $Re = 1000$ and a domain length of $L_x = 2\pi$. \bullet , $L = 50$; \blacksquare , $L = 100$; \blacktriangle , $L = 200$; \blacktriangledown , $L = 500$. Symbols are color-coded by states as defined in Fig. 1 and grey defines the laminar regime. (b) Flow regimes in the Wi - L phase space. $Re_b = 1000$ and $\beta = 0.9$.




FIG. 4. (a) Profiles of mean streamwise velocity as a function of the distance from the wall $\xi = 1 - z$. (b) Profiles of mean trace of the configuration tensor normalized by the polymer maximum extensibility as a function of ξ . Colors correspond to simulations introduced in Fig. 1.

integration time is not necessary for statistical convergence, but it confirms the steadiness of the solution. The more chaotic the regime is, the faster statistical convergence is achieved. Figure 3(a) maps the drag increase as a function of the Weissenberg number Wi and the polymer maximum extensibility L for the $L_x = 2\pi$ -domain. Experiments in channel flows [25] report a non-monotonic

behavior of DI as a function of the (non-dimensional) relaxation time Wi , where DI increases from $Wi = 0$ to a maximum followed by a gradual return to zero (laminar flow) at high Wi . Laminarization was also observed in pipe flows [26]. Figure 3(a) suggests a similar behavior for $L = 100$ and 200 . Yet we cannot conclusively establish that the dynamics of our simulations leading to the DI evolution is the same as experiments. As it will be shown below, the length of the domain plays a significant role in the type of regime that may exist at a given combination (Wi, L) . For $L = 50$, the existence of a maximum of DI could not be established because low- L and high- Wi flows require much lower time steps for stability reasons. Attempts to simulate $L = 50$, $\beta = 0.9$, and $Wi > 200$ proved to be too computationally expensive and too unstable for the present algorithm. This has shown to be reliable and robust for large L , Wi and β , however the present study explores flows where C_{ii} intermittently reaches values very close to L^2 , which can produce numerical instabilities. A new algorithm is in development to address this issue.

Figure 3(b) provides a rough outline of the different regimes in the Wi - L phase space for $Re = 1000$, $\beta = 0.9$ and a domain length of $L_x = 2\pi$. CR is confined to $L = 50$ with the exception of $L = 100$, $Wi = 20$. For $L = 100$, increasing Wi yields an evolution from CR to CAR to SAR to laminar, whereas $L = 200$ undergoes an evolution from laminar to IAR to SAR to laminar. For $L = 500$, simulations at $Wi = 30, 100$ reached SAR.

Fig. 3b suggests that SAR can be reached by increasing L at constant Wi or increasing Wi at constant L . The mechanisms behind this observation remain unclear and beyond the scope of the present article. Nonetheless, speculation, or guidance for future research, may be found in the physics that each parameter governs. In the FENE-P model, L controls the maximum elongational viscosity ratio [27],

$$\lim_{\dot{\epsilon} \rightarrow \infty} \frac{\nu_E}{3\nu_0} = L^2(1 - \beta) \quad (8)$$

where $\dot{\epsilon}$ is the extensional rate. As it will be discussed in Section “Influence of Domain Length, Reynolds Number and β ”, increasing β , *i.e.*, reducing $(1 - \beta)$, requires augmenting L^2 to reach SAR. This supports the speculation that elongational viscosity plays a key role in the emergence of SAR. The Weissenberg number controls time scales of the polymer dynamics. From Fig. 3b it seems that small Wi numbers promote chaos, whereas large Wi numbers helps with steadiness. Ultimately, the roles of L , Wi , and β in the emergence of chaos and its destruction remain an open question, because the mechanism of chaos is poorly understood at the time of publication of this article.

Mean velocity profiles (Fig. 4a) evolve from a nearly parabolic velocity profiles at CR and CAR to more of a plug flow-like profile at IAR and SAR, with a velocity




FIG. 5. Profiles of the mean Kolmogorov scale (Eq. 14) as a function of the distance from the wall $\xi = 1 - z$. Colors correspond to simulations introduced in Fig. 1.




FIG. 6. Profiles of the mean energy transfer term Π_e (a), and, in (b), the mean fluctuating energy transfer term Π'_e (solid lines) and dissipation rate of TKE $\bar{\epsilon}$ (dashed lines) as a function of the distance from the wall $\xi = 1 - z$. Colors correspond to simulations introduced in Fig. 1.

plateau extending over $\xi \gtrsim 0.5$. These profiles correspond to the flows depicted in Fig. 1. Figure 4(b) is a measure of the mean polymer extension throughout the channel. In the CR-flow, the polymer extension is large, above 50% of L^2 over 75% of the channel half-height. A common characteristic of CR and CAR is the inflexion point around $\xi \approx 0.2$. For IAR and SAR, the polymer extension decreases linearly up to $\xi \approx 0.4$, where it experiences a local maximum before decreasing rapidly to very small values in the core.

ENERGY TRANSFERS

The transport equations of the kinetic energy (KE) $e_u := \frac{1}{2}u_i u_i$ and elastic energy (EE) e_p (defined in Eq. 7)




FIG. 7. Streamwise cospectra of the fluctuations of the energy transfer term defined in Eq. (15) as a function of the distance from the wall ξ . The streamwise wavenumber is normalized by the minimum mean Kolmogorov length scale from Fig. 3. (a): CR; (b): CAR; (c): IAR; (d): SAR. Each graph corresponds to simulations introduced in Fig. 1.

read

$$\begin{aligned} \partial_t e_u + u_k \partial_k e_u = & -\partial_i u_i p + \frac{\beta}{Re} \partial_k \partial_k e_u - \frac{\beta}{Re} (\partial_k u_i) (\partial_k u_i) \\ & + \frac{1-\beta}{Re} \partial_k (u_k T_{ik}) - \Pi_e \end{aligned} \quad (9)$$

and

$$\partial_t e_p + u_k \partial_k e_p = -\frac{1-\beta}{2 Re W_i} f T_{ii} + \Pi_e, \quad (10)$$

where

$$\Pi_e := \frac{1-\beta}{Re} T_{ij} S_{ij} \quad (11)$$

is the energy transfer between KE and EE. Similar transport equations can be derived for the turbulent kinetic energy (TKE, $e'_u := \frac{1}{2} u'_i u'_i$) and turbulent elastic energy (TEE, e'_p), yielding

$$\Pi'_e := \frac{1-\beta}{Re} T'_{ij} S'_{ij}. \quad (12)$$

Also of interest to our study, the dissipation rate of TKE,

$$\varepsilon := \frac{\beta}{Re} \partial_j u'_i \partial_j u'_i, \quad (13)$$

defines the Kolmogorov length scale, here written with our adopted normalization,

$$\eta_K := \left(\frac{(\beta/Re)^3}{\varepsilon} \right)^{\frac{1}{4}}, \quad (14)$$

which is the smallest scale, or dissipation scale, in classical turbulence. The length scales in EIT are yet to be defined, since they most likely depend upon flow and polymer parameters at a minimum. For now, the minimum mean Kolmogorov length scale over the height of the channel is adopted as a reference length scale for the flow. The distribution of the Kolmogorov length scale for the four different regimes and simulations of Fig. 1 are shown in Fig. 5. The smallest length scale is at a distance from the wall ξ ranging from 0.3 for the chaotic regimes to 0.6 for SAR. CR, CAR and SAR show a local maximum in the range $0.05 \lesssim \xi \lesssim 0.2$ and another at the centerline. The latter maximum is not surprising since all regimes experience little to no polymer stress with the exception of the junction of the arrowhead.

Figure 6 shows the profiles of the mean and fluctuating energy transfer terms throughout the half-height of the channel. From Eqs. (9) and (10), positive Π_e or Π'_e indicates an energy transfer from the mean kinetic energy of the flow to the mean elastic energy or from TKE to TEE, respectively. The mean energy transfer is positive throughout the channel (Fig. 6a), with a maximum at CR and CAR around $\xi \approx 0.2$, where profiles of C_{ii}/L^2 (Fig. 4b) show an inflection point. For IAR and SAR, the local maximum corresponds to the steep decrease in C_{ii}/L^2 .

The fluctuating energy transfer is negative for CR, CAR and IAR, showing that energy is flowing from TEE to TKE on average (Fig. 6b). For SAR, the energy transfer Π'_e switches sign close to the centerline. The very near wall region is void of fluctuating energy transfer up to $\xi \approx 0.1$. This region extends further for SAR, to $\xi \approx 0.3$. Naturally for SAR, fluctuations are in fact spatial, since the flow is invariant by translation, which explains why the dissipation rate of TKE is null in the very near-wall region, whereas $\bar{\varepsilon}$ for other regimes is finite.

Figure 7 investigates the spectral representation $\widehat{\Pi}'_e$ of the energy transfer

$$\widehat{\Pi}'_e := \frac{1-\beta}{Re} \widehat{T}_{ij} * \widehat{S}_{ij}, \quad (15)$$

which is proportional to the co-spectra of $T'_{ij}S'_{ij}$. In Eq. (15) the \widehat{a} symbol defines the Fourier transform of variable a . This analysis allows for the investigation of the scales and distances from the wall at which polymers gain energy from the flow and *vice versa*. The stream-wise wavenumber is normalized by the minimum of the Kolmogorov length scale.

For CR (Fig. 7a), the energy transfer from TEE to TKE, *i.e.* $\widehat{\Pi}_e$, is mostly from $10\eta_{K,min}$ down to $\sim 5\eta_{K,min}$ at a distance from the wall $0.2 \lesssim \xi \lesssim 0.75$. The energy transfer from TKE to TEE occurs at larger scales $\gtrsim 10\eta_{K,min}$ but closer to the wall, $\xi \sim 0.1 - 0.2$. EIT in its chaotic regime is therefore sustained by an upscale energy transfer from polymers to flow and a downscale energy transfer from flow to polymers. The physical location of the latter corresponds to the location of the inflection point of C_{ii}/L^2 (Fig. 4b) and the maximum mean transfer of energy from KE to EE (Fig. 6a). The upscale energy transfer dominates the fluctuating energy transfer ($\overline{\Pi}'_e$) as shown in Fig. 6b. The flow dynamics of CR-EIT stretches polymers to large mean extension levels. Stretched polymers are organized in thin-sheets, which in turn feed TKE via a mechanism yet to be identified, but occurring at smaller scales than the mechanism of polymer stretching.

Whereas the picture of energy transfer at CAR (Fig. 7b) is similar to CR, IAR and SAR show a much different pattern (Figs. 7c,d). The energy transfer from TKE to TEE shifts upward and is still large scale for IAR but becomes small scale for SAR, albeit of weaker intensity than for all other regimes. The region of energy transfer from TEE to TKE is truncated above $\xi \approx 0.5$ for IAR and again shifted upward and narrower for SAR. A major distinction between chaotic and steady or quasi-steady regimes may be in the location of the energy transfer from TKE to TEE ($\widehat{\Pi}'_e > 0$). One could speculate that the origin of chaos is not only in the spectral locality of the energy transfers but also spatial locality. Injection of TKE into TEE in the region where polymers are the most stretched (near-wall region) could conceivably excite instabilities in the sheets of high polymer stress resulting into the undulations observed in Fig. 1(a) correlated to regions of high- and low-pressure Fig. 1(b).

INFLUENCE OF DOMAIN LENGTH, REYNOLDS NUMBER, AND β

For the chaotic regime, we verified that statistics are not affected by doubling the length of the domain (not shown). SAR flows with $L = 100$ and 200 prove to be




FIG. 8. Snapshots of N_1 fields in a domain twice the length of the domain used in simulations used for Fig. 1. For all simulations, the Reynolds number is 1000.

highly sensitive to the domain length. Doubling the domain size with $L = 100$, $Wi = 100$, $\beta = 0.9$ causes the flow to shift from SAR to CAR as shown in Fig. 8(a). The SAR for $L = 200$ depicted in Fig. 1(g) becomes IAR in the larger domain (Fig. 8b). SAR is recovered for $L = 500$ for $L_x = 4\pi$ (Fig. 8a) and 8π (not shown).

The mechanism driving chaos appears to be a function of both L and L_x . In other words, the undulation of sheets of large N_1 or polymer stress may be created by a large scale instability that is damped when the domain is too short. In spite of the large number of simulations performed for this article, this could not be ascertain. Identifying the exact wavelength of this possible instability as a function of L requires further simulations to probe the range $L_x \in [2\pi, 4\pi]$. The extensibility parameter L drives the length scale of the sheets of large polymer stress, as well as the intensity of the first normal stress difference, which both increases with L for a given Wi .

The arrowhead structure, in its steady form, is found to exist at least between $Re = 100$ and 3000 (Figs. 9a,b, respectively). At $Re = 100$, a depression in the first normal stress difference is observed in the near-wall region at the front of the arrowhead's junction, similar to the one observed in Fig. 1(g) at $Re = 1000$, but extending almost to the wall and with a smaller gradient with the surrounding stress. Note that at $Re = 3000$ reaching SAR requires longer maximum extensibility parameter L than for lower Re for the same Wi and β parameters. There was no attempt to reduce the length of the computational domain to investigate whether IAR and CAR could become stable for lower L at this Reynolds number.

Lastly, Fig. 10 illustrates the effect of the ratio β first




FIG. 9. Snapshots of N_1 fields of steady arrowhead regime at two different Reynolds numbers.

on two different simulations at $Re = 1000$ with $L = 100$ and $Wi = 100$ in a $L_x = 2\pi$ -domain (Figs 10a-b). At $\beta = 0.9$, the flow achieves SAR (see Fig. 3b). The lower $\beta = 0.5$ simulation shows the same regime, confirmed over $4,000 h/U_b$. There are some visible differences in the shape and width of the arrowhead but the main features of the arrowhead structure remain clearly identifiable. Increasing β to 0.97 triggers the chaotic regime CR, as shown in Fig. 10b. Keeping $Wi = 100$ and $\beta = 0.97$, SAR can be recovered at $L = 500$ as shown by Fig. 10c. We have not sought to define precisely the critical L at which the flow is stabilized, nor the critical $\beta \in [0.9, 0.97]$ at which the flow transitions from SAR to intermittence or chaos. A future investigation of the influence of β is however necessary and will be conducted in the near future. The data shown here, suggests two possible co-existing polymer effects. Shear thinning, driven by low β may help stabilize the very near region where the stretch is the highest. At the other end of the spectrum, when $(1 - \beta)$ approaches zero, the recovery of SAR might be indicative of the role of extensional viscosity in the structure of the arrowhead. Tamano *et al.*[27] showed some similarity in the drag reducing properties of flows with comparable $(1 - \beta)L^2$ (See Eq. 8). Noticeably the most significant drag reduction obtained by Tamano *et al.* was for $(1 - \beta)L^2 = 10^3$, the highest value achieved in their simulations. In the limited data for the present study, SAR is also observed for solution with $(1 - \beta)L^2 \geq 10^3$, the simulation of SAR shown in Figs 10a and c have $(1 - \beta)L^2 = 5 \times 10^3$ and 7.5×10^3 , respectively, whereas the CR regime shown in Fig. 10b is at $(1 - \beta)L^2 = 3 \times 10^2$.




FIG. 10. Snapshots of N_1 fields illustrating the effect of the parameter β . (a) and (b) share the same $L = 100$ and $Wi = 100$ as SAR simulations identified for $\beta = 0.9$ (see Fig. 3b). $\beta = 0.5$ sustains SAR (a), whereas $\beta = 0.97$ destabilizes the flow to CR. (c) shows SAR for $\beta = 0.97$ at $L = 500$ and $Wi = 100$.

STEADY ARROWHEAD REGIME

The steady arrowhead regime proves to be a robust feature of EIT. It appears to be triggered by the ratio of polymer extensibility to domain streamwise length L_x for polymer extensibility larger than a threshold. This threshold L_{SAR} is in the range $L_{SAR} \in]50, 100]$ for $\beta = 0.9$ and $Re = 1000$ according to our data. Further numerical experiments are needed to understand the relationship between L and L_x and its influence on chaos. Regarding the latter point, one may speculate that the intense high-pressure region in the wake of the arrowhead's junction stabilizes the flow. When L_x is increased, chaos may arise in regions that are far enough away from the junction, possibly through a linear instability [28, 29]. Under this scenario, the intensity of the pressure gradient between the front and back of the junction may be the determinant factor.

Figure 11 illustrates the complexity of SAR, through streamlines of the fluctuating velocity field superimposed




FIG. 11. (a) Superimposition of streamlines computed from the fluctuating velocity field and contours of N_1 for $Re = 1000$, $L = 200$, $Wi = 100$ and $\beta = 0.9$ (Fig. 1g). (b) Superimposition of the same streamlines and contours of the transfer of energy fluctuations Π'_e

on contours of N_1 (Fig. 11a) and superimposed on contours of the transfer of energy fluctuations Π'_e . Streamlines show the existence of two large scale structures in the near wall regions whose interface is located in a region where energy is transferred from TKE to TEE ($\Pi'_e > 0$). Unsurprisingly, the snapshot of Π'_e in physical space resembles the energy transfer in the spectral-distance from the wall space (Fig. 7d). Figure 11 also establishes the correlation between the depletion of polymer stress in the upper and lower front of the junction and the interface between energy transfers from TKE to TEE and from TEE to TKE ($\Pi'_e < 0$). SAR's energy transfers are localized and appear to drive the dramatic perturbations of velocity fluctuations.

The arrowhead structure most likely owes its symmetry to the presence of walls. A similar structure was observed in a Kolmogorov flow [30, 31] at $Re \lesssim 1$, a regime considered to be the upper bound of elastic turbulence. Figures 7b and 8a of Berti & Boffetta[31] clearly show thin sheets of large T_{11} joining in a pattern similar to the arrowhead. The similarity between elastic turbulence and EIT suggests that the same fundamental mechanisms of polymer/flow interactions may be at play.

The robustness of the arrowhead at low Reynolds number was demonstrated in Page *et al.* [22], for $L = 500$, down to $Re=60$ and for relatively small $Wi = \mathcal{O}(10)$.

Regime	L	Wi	β	ρ_p
CR	50	50	0.9	0.23
CAR	100	50	0.9	0.48
IAR	200	50	0.9	0.9
SAR	200	100	0.9	1.0

TABLE I. Summary of correlation of pressure between the lower and upper walls (Eq. 16) used as a measure of symmetry of the flow for the regimes defined in Fig. 1 at $Re=1000$.

REGIME IDENTIFICATION

The discovery process detailed so far informs the derivation of a possible identification criterion for the four regimes, CR, CAR, IAR and SAR, specific to 2D simulations of periodic channel flows in a relatively short domain. Although the extension of such criterion to longer domains in 2D and 3D periodic or spatially developing flows is not straightforward, the aim is to use primary flow variables, velocity and pressure, that are accessible experimentally. The first component of the criterion is based on wall-pressure fluctuations which have been used to characterize ET [32] and EIT [1, 33]. The correlation of two wall-pressure signals collected at the same stream-wise location but on opposite walls,

$$\rho_p = \frac{\overline{p'_{(x,z=+h,t)} p'_{(x,z=-h,t)}}}{\sqrt{\overline{p'^2_{(z=+h)}} \overline{p'^2_{(z=-h)}}}}, \quad (16)$$

is a measure of the symmetry of the flow about the centerline. For Reynolds number $Re_b = 1000$, the values of this correlation are reported in Table I and can be categorized as low ($\rho_p \sim 0.2$, CR), moderate ($\rho_p \sim 0.5$, CAR), high ($\rho_p \sim 0.9$, IAR) and perfect ($\rho_p = 1$, SAR). The exact bounds delimiting two adjacent regimes require further investigation of the parameter space (Re, Wi, L, β) and will be the focus of future research. The wall-pressure correlation criterion can objectively identify the perfect or near perfect symmetry imposed by the arrowhead structure in IAR and SAR, but remains a necessary condition not a sufficient condition to establish the existence of an arrowhead.

Plots of power spectral density (PSD) of the wall-pressure signal (Fig. 12a) show a distinct peak for IAR and SAR at the frequency corresponding to the flow-through time of the arrowhead based on the mean centerline velocity \bar{U}_c and the length of the domain L_x . The signature of the arrowhead in CAR is however too small and too close to the energetic contributions of surrounding frequencies in the range $0.5 \bar{U}_c/L_x$ to $1.5 \bar{U}_c/L_x$ to be used as an identification criterion. PSD of the streamwise velocity component at the centerline, a quantity that can be measure experimentally, provides an objective identification of the presence of an arrowhead for CAR, with an energy at \bar{U}_c/L_x comparable to that of IAR.

Table II summarizes the identification method of the




FIG. 12. Power spectral density plots of times series sampled at a fixed location: (a) wall pressure; (b) centerline streamwise velocity. Colors correspond to simulations introduced in Fig. 1

Regime	Correlation ρ_p	PSD peak at $f = U_c/L_x$	
		p_w	u_c
CR	Low (~ 0.2)	No	No
CAR	Moderate (~ 0.5)	No	Yes
IAR	High (~ 0.9)	Yes	Yes
SAR	Perfect ($= 1$)	Yes	Yes

TABLE II. Characteristics of the different regimes based on the correlation of wall pressure fluctuations at $z = \pm h$, and the presence or absence of a distinct energetic contribution in the PSD of the wall pressure fluctuations and the centerline velocity fluctuations.

four different regimes, for a periodic channel flow of length 2π , by a combination of correlation and power spectral density analyses of pressure and velocity, two quantities that experiments can measure. The correlation of two wall pressure signals collected at the same streamwise location and on opposite walls measures the symmetry of the flow. Power spectral densities of streamwise centerline velocity fluctuations identify the presence of arrowhead as a peak in energy contribution at a frequency corresponding to the centerline mean velocity and the length of the domain. Another interesting observation is the patch of energetic contribution for the streamwise centerline velocity fluctuations around $fL_x/U_c \sim 0.8$, which is only visible for CR and CAR. Whether this patch is a signature of chaos remains an open question that will be addressed in future research.

The proposed criterion works for a periodic channel of dimensions comparable to the streamwise scale of the arrowhead. Under this condition, the stability of the

IAR and SAR arrowhead produces a dominant frequency. Simulations in longer computational domains presented here suggest that arrowhead structures might be come intermittent, or puff-like. For future experimental or computational studies in large domains, the frequency criterion might be advantageously replaced by POD or DMD.

CONCLUSION

This paper describes the discovery of the first coherent structure found in elasto-inertial turbulence. This takes the particularly simple form of a travelling wave in which polymer stress sheets which originate near the walls bend to meet at the channel centre to form a symmetric arrowhead structure. Alongside a regime where this arrowhead is an attractor (SAR), our simulations have also established the existence of several other regimes in EIT - chaotic (CR), chaotic arrowhead (CAR) and intermittent arrowhead (IAR). These regimes are identified by the structure of the polymer stress field, the fluctuations of the drag increase in time and the energy transfer between polymers and flow. The latter clearly demonstrates that the transfer of energy from fluctuations of elastic energy to fluctuations of turbulent kinetic energy is an upscale mechanism occurring predominantly at small scales away from the walls. Reverse energy transfer occurs at large scales and is a downscale mechanism with the exception of SAR. For the steady arrowhead state, the reverse energy flow is also at small scales but further away from the walls.

The arrowhead coherent structure is a robust state of the flow, which exists over a large range of Reynolds numbers, polymer extensibility, Weissenberg numbers and parameter β . This structure should help uncover the fundamental dynamics underpinning EIT and reveal the mechanism of energy transfer between flow and polymers. We hope to report on further progress in this direction soon.

The authors thank the referees for their constructive comments, which helped improve this manuscript. This research is supported by the National Science Foundation (NSF-CBET-1805636) and the United States- Israel Binational Science Foundation award #2016145. The opinions, findings, and conclusions or recommendations expressed are those of the authors and do not necessarily reflect the views of the National Science Foundation or of the US-Israel Binational Science Foundation.

* ydubief@uvm.edu

[1] D. Samanta, Y. Dubief, M. Holzner, C. Schäfer, A. N. Morozov, C. Wagner, and B. HOF, Elasto-inertial turbulence., Proceedings of the National Academy of Sciences **110**, 10557 (2013).

- [2] Y. Dubief, V. E. Terrapon, and J. Soria, On the mechanism of elasto-inertial turbulence, *Physics of Fluids* **25**, 110817 (2013).
- [3] H. H. Wensink, J. Dunkel, S. Heidenreich, K. Drescher, R. E. Goldstein, H. Löwen, and J. M. Yeomans, Mesoscale turbulence in living fluids, *Proceedings of the National Academy of Sciences* **109**, 14308–14313 (2012).
- [4] R. Alert, J.-F. Joanny, and J. Casademunt, Universal scaling of active nematic turbulence, *Nature Physics*, 1 (2020).
- [5] A. Groisman and V. Steinberg, Elastic turbulence in a polymer solution flow, *Nature* **405**, 53 (2000).
- [6] A. Groisman and V. Steinberg, Efficient mixing at low reynolds numbers using polymer additives, *Nature* **410**, 905 (2001).
- [7] B. Traore, C. Castelain, and T. Burghelea, Efficient heat transfer in a regime of elastic turbulence, *Journal of Non-Newtonian Fluid Mechanics* **223**, 62–76 (2015).
- [8] R. Whalley, W. Abed, D. Dennis, and R. Poole, Enhancing heat transfer at the micro-scale using elastic turbulence, *Theoretical and Applied Mechanics Letters* **5**, 103 (2015).
- [9] R. Poole, B. Budhiraja, A. Cain, and P. Scott, Emulsification using elastic turbulence, *Journal of Non-Newtonian Fluid Mechanics* **177**, 15 (2012).
- [10] S. Sid, V. E. Terrapon, and Y. Dubief, Two-dimensional dynamics of elasto-inertial turbulence and its role in polymer drag reduction, *Phys. Rev. Fluids* **3**, 011301 (2018).
- [11] S. K. Robinson, Coherent motions in the turbulent boundary layer, *Annual Review of Fluid Mechanics* **23**, 601 (1991).
- [12] J. Jiménez and A. Pinelli, The autonomous cycle of near-wall turbulence, *J. Fluid Mech.* **389**, 335 (1999).
- [13] A. Kolmogorov, The local structure of turbulence in incompressible viscous fluid for very large reynolds numbers, in *Dokl. Akad. Nauk SSSR*, Vol. 30 (1941) pp. 9–13.
- [14] Y. Dubief, C. M. White, E. S. G. Shaqfeh, and V. E. Terrapon, Polymer maximum drag reduction: A unique transitional state, in *Annual Research Briefs* (Center for Turbulence Research, Stanford, CA, 2010) pp. 395–404.
- [15] V. E. Terrapon, Y. Dubief, and J. Soria, On the role of pressure in elasto-inertial turbulence, *Journal of Turbulence* **16**, 26 (2014).
- [16] Y. Dubief and F. Delcayre, On coherent-vortex identification in turbulence, *J. of Turbulence* **1** (2000).
- [17] T. Burghelea, E. Segre, and V. Steinberg, Elastic turbulence in von karman swirling flow between two disks, *Phys. Fluids* **19**, 053104 (2007).
- [18] A. Shekar, R. M. McMullen, S.-N. Wang, B. J. McKeon, and M. D. Graham, Critical-layer structures and mechanisms in elastoinertial turbulence, *Phys. Rev. Lett.* **122**, 124503 (2019).
- [19] Y. Dubief, V. Terrapon, C. White, E. Shaqfeh, P. Moin, and S. Lele, New answers on the interaction between polymers and vortices in turbulent flows, *Flow, turbulence and combustion* **74**, 311 (2005).
- [20] Y. Dubief, V. E. Terrapon, and J. Soria, Analysis of transitional polymeric flows and elastic instabilities, in *Proceedings of the Summer Program 2012* (Center for Turbulence Research, Stanford, CA, 2012) pp. 55–63.
- [21] B. Purnode and V. Legat, Hyperbolicity and change of type in flows of FENE-P fluids, *J. Non-Newt. Fluid Mech.* **65**, 111 (1996).
- [22] J. Page, Y. Dubief, and R. R. Kerswell, Exact traveling wave solutions in viscoelastic channel flow, *Phys. Rev. Lett.* **125**, 154501 (2020).
- [23] R. Bird, R. Armstrong, and O. Hassager, *Dynamics of Polymeric Liquids. Vol. 2: Kinetic Theory* (Wiley-Interscience, 1987., 1987).
- [24] See supplemental material at <https://journals.aps.org/> for movies of the evolution in time of N_1 -contours for the four regimes of EIT.
- [25] A. Varshney and V. Steinberg, Drag enhancement and drag reduction in viscoelastic flow, *Physical Review Fluids* **3**, 103302 (2018).
- [26] G. H. Choueiri, J. M. Lopez, and B. Hof, Exceeding the asymptotic limit of polymer drag reduction, *Physical review letters* **120**, 124501 (2018).
- [27] S. Tamano, M. Itoh, S. Hotta, K. Yokota, and Y. Morinishi, Effect of rheological properties on drag reduction in turbulent boundary layer flow, *Phys. Fluids* **21**, 055101 (2009).
- [28] P. Garg, I. Chaudhary, M. Khalid, V. Shankar, and G. Subramanian, Viscoelastic pipe flow is linearly unstable, *Physical review letters* **121**, 024502 (2018).
- [29] I. Chaudhary, P. Garg, G. Subramanian, and V. Shankar, Linear instability of viscoelastic pipe flow, *Journal of Fluid Mechanics* **908** (2021).
- [30] S. Berti, A. Bistagnino, G. Boffetta, A. Celani, and S. Musacchio, Two-dimensional elastic turbulence, *Physical Review E* **77**, 055306 (2008).
- [31] S. Berti and G. Boffetta, Elastic waves and transition to elastic turbulence in a two-dimensional viscoelastic kolmogorov flow, *Physical Review E* **82**, 036314 (2010).
- [32] Y. Jun and V. Steinberg, Power and pressure fluctuations in elastic turbulence over a wide range of polymer concentrations, *Phys. Rev. Lett.* **102**, 124503 (2009).
- [33] G. H. Choueiri, J. M. Lopez, A. Varshney, S. Sankar, and B. Hof, Experimental observation of the origin and structure of elastoinertial turbulence, *Proceedings of the National Academy of Sciences* **118** (2021).

APPENDIX

Grid resolution study

N_x	N_z	$\Delta_{z,min}/h$	$\bar{f}(t)$	RMS(f)	Regime
128	129	10^{-4}	7.1×10^{-3}	9.4×10^{-4}	IAR
256	257	10^{-4}	6.8×10^{-3}	9.3×10^{-4}	IAR
512	513	10^{-3}	8.2×10^{-3}	4.1×10^{-3}	CAR
512	513	5×10^{-4}	7.6×10^{-3}	3.1×10^{-3}	CAR
512	513	10^{-4}	7.6×10^{-3}	3.16×10^{-3}	CAR
512	513	5×10^{-5}	7.6×10^{-3}	3.15×10^{-3}	CAR
1024	1025	10^{-4}	7.6×10^{-3}	3.15×10^{-3}	CAR

TABLE A1. Example of numerical resolution study for regime CAR defined in Fig. 1. All simulations in this case were performed at $Re_b = 1000$ in a domain $L_x \times L_z = 2\pi h \times 2h$. The monitoring metrics are the mean pressure gradient f and its RMS. The resolution used for production is framed by two horizontal lines.

Appropriate grid resolution is critical to the simula-

tion of the different states of EIT. In the course of the present and previous studies, we identified three parameters of crucial importance: Overall resolution $N_x \times N_z$, size of the cell at the wall Δz_{min} and Schmidt number. In this section, the study of these parameters is illustrated by a fully chaotic flow (CR) obtained with $Re_b = 1000$, $L = 50$, $Wi = 50$ and $\beta = 0.9$. The characteristics of the simulations used in this grid convergence studies are compiled in Table A1, which also reports the mean and RMS of the pressure gradient $f(t)$ driving the constant mass flow (see Eq. 3, and the flow regime).

Effects of grid resolution, and Schmidt number of small scales




FIG. A1. Spectral analysis of the resolution study for $Re_b = 1000$, $L = 50$, $Wi = 100$, $\beta = 0.9$. (a) shows the effect of resolution on the fluctuations of wall pressure, (b), the effect of the size of mesh at the wall, and (c) the effect of the Schmidt number.

As discussed in Dubief *et al.*[19], there is no dissipative mechanism in the exact FENE-P equation. The high-order compact scheme used for the advection terms introduces numerical dissipation at high wavenumbers [19] necessary to avoid a buildup of energy at small scales due to the hyperbolic nature of FENE-P. Consequently gradients of C_{ij} and T_{ij} are expected to become sharper with higher resolutions. Through Eq. 1, larger gradients impact the pressure distribution throughout the do-

main. Fig A1(a) shows the power spectral densities in the streamwise direction of wall pressure fluctuations for increasing resolution with fixed $\Delta z_{min}/h = 10^{-4}$ and $Sc = 1000$. The two lowest resolutions, 128^2 and 256^2 underestimate the spectral content of pressure fluctuations across scales, and as reported in Table A1, they yield a flow regime different than the regime simulated for the two highest resolutions.

Another critical parameter is the smallest grid size Δz_{min} at the wall. A parametric study established that $\Delta z_{min} = 10^{-4}$ is necessary to capture the intense gradient of polymer stress at the wall in chaotic regimes. Fig. A1b highlights the spurious increase of energy in the PSD of wall pressure fluctuations across all scales caused by too coarse of a resolution ($\Delta z_{min} = 10^{-3}$), and the convergence of the spectra for ($\Delta z_{min} = 5 \times 10^{-4}, 10^{-4}, 5 \times 10^{-5}$)

The Schmidt number study (Fig. A1c) shows an expected reduction of the energy content at small scale with decreasing Schmidt number. Note that decreasing the Schmidt number is not found to change the flow regime unless $Sc \lesssim 5$, in which case the flow becomes laminar.

The simulation of EIT is therefore a necessary compromise between aiming for the highest resolution for accuracy at the maximum number of wavenumbers and the ability to run long simulations to capture low frequency behavior in statistics (like IAR). It is also important to note that the stiffness of the FENE-P equations requires numerical artifacts, such as global artificial diffusion (GAD, used in Eq. 4), local artificial diffusion (LAD, used in [19]), upwind schemes. The numerical methods bring certain levels of numerical dispersion and dissipation into the solution. The following section demonstrates that SAR is not influenced by numerical dispersion and dissipation. The effects of numerical dissipation on EIT is addressed in the previous and current sections in terms of the resolution study. The higher the resolution, the lower the contribution of numerical dissipation is. The influence of dispersion is also small as shown by the resolution study. Nonetheless any research focused on finding the exact bounds of the CR, CAR, IAR regimes should consider quantifying the uncertainty from numerical dispersion. This is beyond the scope of this paper.

Effects of numerical dissipation and dispersion on SAR

Lastly, the power spectra of N_1 are shown in Fig. A2a for two SAR regimes. Their distribution as a function of the wavenumber is compared to the numerical dissipation and dispersion of the upwind compact scheme used for the advection term [19] in the FENE-P equation (Eq. 4). In the Fourier space, the exact first derivative of a func-




FIG. A2. (a) Imaginary (negative curves) and real (positive curve) components of the modified wavenumbers for the upwind compact scheme [19] (solid lines) and the staggered second order scheme (dashed) for the spatial first derivative. The imaginary and real components quantify the numerical dispersion and dissipation, respectively, of each scheme as a function of the wavenumber. (b) Power spectra of first normal stress difference at the wall of two SAR simulations ($L = 100, 200$, $Wi = 100$, $\beta = 0.9$). (c) Power spectra of turbulent kinetic energy for the same simulations.

tion f defined on $k \in [1, N]$ computational nodes is

$$\widehat{\partial_x f} \Big|_k = \hat{i} w_k \hat{f}_k,$$

where $w_k = 2\pi k/N$ is the wavenumber vector, $\hat{i}^2 = -1$ and \hat{f}_k is the Fourier coefficient vector of f . Any finite difference or finite volume scheme for first derivative can be recast in the Fourier space as

$$\widehat{\partial_x f} \Big|_k = \hat{i} w'_k \hat{f}_k,$$

where w'_k is the modified wavenumber of the numerical scheme, here the upwind compact scheme defined in [19]. The real component $\text{Re}(w'_k)$ of the modified wavenumber represents the numerical dissipation at wavenumber w_k of the scheme. The motivation for an upwind compact scheme is to confine numerical dissipation in the high wavenumbers in order to damp Gibbs oscillations near the grid cutoff. Gibbs oscillations are caused by the presence of large gradients of C_{ij} resulting from the stiffness of the FENE-P model.

Unlike spectral methods, any finite difference (FD) scheme for derivative introduces a certain level of numerical dispersion. The numerical dispersion as a function of the wavenumber is defined as the $\text{Re}(w'_k)$. Central FD schemes are non-dissipative, however the upwind compact scheme is, by design. The numerical dissipation is the real part of the modified wavenumber, $\text{Im}(w'_k - w_k)$. Fig. A2a shows the dispersion of staggered second-order FD scheme used for the advection of momentum and velocity divergence, and the upwind compact scheme used for the advection of C_{ij} , as well as the numerical dissipation of the upwind compact scheme. The departure from zero for the numerical dispersion and dissipation of each scheme is compared to the spectra of the first normal stress difference (N_1) and spectra of turbulent kinetic energy for two simulations of SAR. The relevant dynamic scales for N_1 are confined to wavenumbers smaller than the range of wavenumbers experiencing numerical dissipation ($w_k \gtrsim 1.5$) and much smaller than the range of wavenumbers experiencing dispersion ($w_k \gtrsim 2.5$) for the compact upwind scheme. The numerical dispersion of the staggered central FD scheme affects a range of scales whose energy 10 decades or more smaller than the large scale energy of turbulent kinetic energy. Note that the dispersion of the central compact scheme used in the momentum transport equation (Eq. 3) is not shown in the graph but comparable to that of the upwind compact scheme.

It should be noted that SAR simulations were successfully run with $Sc = 50$, which is not surprising considering the absence of small scales shown in Figs A2b-c.