

Groundwater porosities and effective porosities: definitions, physical relevance, and scale issues

A. Dassargues

Hydrogeology & Environmental Geology, Urban & Environmental Eng., University of Liège, B52 Sart Tilman, 4000 Liège

Porosity describes the ratio between the volume of pores, cracks, and fissures and the total volume of a studied geological medium. This notion implies a volume averaging of the medium characteristics using the concept of Representative Elementary Volume (REV). Small volumes can contain only pores while larger volumes typically contain both pores and fissures. Porosity can be highly scale-dependent, and different porosity values can be measured for the same geological formation. Furthermore, groundwater in the pores and cracks can be partly immobile or mobile. So, the porosity actively involved in groundwater flow can be discussed. A 'mobile water porosity' can be defined, but this remains highly dependent on the existing pressure conditions in the geological medium. In unconfined conditions, the term 'effective porosity' corresponds usually to the drainage porosity corresponding also to the specific yield or the storage coefficient.

When dealing with solute transport and remediation of contaminated sites, another 'effective porosity' is needed to describe the advection velocity of the contaminant. This 'mobile water porosity' acting in solute transport processes takes typically lower values than the 'effective porosity' of drainage (Payne, Quinnan and Potter 2008, Hadley and Newell 2014, Dassargues 2018). There also, scale issues must be expected as shown by field and lab tracer tests.

Different groundwater velocities can be defined in function of the adopted 'effective porosity', and all are averaged over the entire volume of the saturated porous medium considered as the chosen REV. The term 'Darcy velocity' is to be banished herein because it induces much confusion. For the sake of clarity, we propose to distinguish 'drainage effective porosity' and 'transport effective porosity'. Physically, this means that the porosity available to transmit solute concentrations is not automatically the same as that corresponding to mobile water for drainage. The transport effective porosity corresponds probably to the most mobile part of the water occupying the pores, fissures and fractures implying to some extent a channeling effect of the solute transport by advection. This channeling being described at the macroscopic scale of the considered REV with a lower value of the solute transport effective porosity leading (for a constant solute flux) to an increased advection velocity. This distinction to be made between different 'effective porosities' is still surprisingly not mentioned in most of the traditional texts on hydrogeology. However, this is confirmed by well-known and accepted observations by hydrogeologists, especially by those dealing with aquifers affected by multiple porosities (Worthington 2015) but not only by them (Derouane and Dassargues 1998, Brouyère 2001, Hoffmann et al. 2019). Examples of such observations are presented for illustration and discussion.

References (among others)

- Bachmat, Y. & Bear, J. 1986. Macroscopic modelling of transport phenomena in porous media, part 1: The continuum approach, *Transport in Porous media* (1) 213-240.
- Barker, J. A. 2010. Modelling doublets and double porosity. *Q. J. Eng. Geol. and Hydrogeology* 43(3), 259 – 268.
- Bear, J. & Verruijt, A. 1987. *Modeling groundwater flow and pollution*. Dordrecht: Reidel Publishing Company.
- Briers, P., Dollé, F., Orban, P., Piront, L. & Brouyère, S. 2017. Etablissement des valeurs représentatives par type d'aquifère des paramètres hydrogéologiques intervenant dans l'évaluation des risques pour

les eaux souterraines en application du Décret du 5 décembre 2008 relatif à la Gestion des Sols (*in French*). University of Liège - GEOLYS final report. SPW/DGO3, Walloon Region (Belgium).

- Brouyère, S. 2001. *Etude et modélisation du transport et du piégeage des solutés en milieu souterrain variablement saturé* (Study and modelling of transport and retardation of solutes in variably saturated media, *in French*), PhD Thesis, University of Liege.
- Brouyère, S., Dassargues, A., Therrien R. & E. Sudicky. 2000. Modelling of dual porosity media: comparisons of different techniques and evaluation of the impact on plume transport simulations. In: Stauffer F., Kinzelbach W. Kovar, K and Hoehn E. (eds) *Proc. of the ModelCARE'99 Conference*, Zürich, IAHS Publ. 265: 22-27.
- Coats, K.H. & Smith, B.D. 1964. Dead-end pore volume and dispersion in porous media. *Soc. Pet. Eng. J.*: 73-84.
- Carrera, J., Sánchez-Vila, X., Benet, I., Medina, A., Galarza, G. et Guimera J. 1998. On matrix diffusion: formulations, solution methods and qualitative effects. *Hydrogeol J.* 6: 178-190.
- Dassargues A., 2018. *Hydrogeology: groundwater science and engineering*, 472p. Taylor & Francis CRC press, Boca Raton.
- Dassargues A. 2020. *Hydrogéologie appliquée : science et ingénierie des eaux souterraines*, 512p. Dunod. Paris.
- Dassargues A., Radu J.P. & Charlier R. 1988. Finite elements modelling of a large water table aquifer in transient conditions. *Adv. Water Res.* 11(2): 58-66.
- Dassargues A. & Monjoie A. 1993. Chalk as an aquifer in Belgium. In: Downing, R.A., Price, M. Jones, G.P. (eds.) *The hydrogeology of the chalk of north-west Europe*. Clarendon Press, Oxford. 153-169.
- De La Bernardie, J., Bour, O., Guihéneuf, N., Chatton, E., Longuevergne, L. & Le Borgne, T. 2019. Dipole and convergent single-well thermal tracer tests for characterizing the effect of flow configuration on thermal recovery. *Geosciences* 9(10): 440.
- de Marsily, G. 1986. *Quantitative hydrogeology: groundwater hydrology for engineers*. Academic Press.
- Derouane J. and A. Dassargues. 1998. Delineation of groundwater protection zones based on tracer tests and transport modelling in alluvial sediments, *Environmental Geology* 36 (1-2): 27-36.
- Foster, S.S.D. & Milton, V.A. 1974. The permeability and storage of an unconfined chalk aquifer. *Hydrol. Sci. Bull.* 19: 485-500.
- Gerke, H.H. & van Genuchten, M.Th. 1993. A dual-porosity model for simulating the preferential movement of water and solutes in structured porous media. *Water Resources Research* 29(2): 305-319.
- Hadley, P.W. & Newell. C.J. 2014. The new potential for understanding groundwater contaminant transport. *Groundwater* 52(2): 174-186.
- Hakoun V., Orban Ph., Dassargues A. & Brouyère S. 2017. Factors controlling spatial and temporal patterns of multiple pesticide compounds in groundwater (Hesbaye chalk aquifer, Belgium). *Env. Pollution* 223: 185-199.
- Hallet V. & Dassargues A. 1998. Effective porosity values used in calibrated transport simulations in a fissured and slightly karstified chalk aquifer. In: Herbert, M. & Kovar, K. (eds.) *Groundwater Quality 1998*, Tübingen Geowissenschaftliche Arbeiten (TGA), C36: 124-126.
- Hermans, T., Wildemeersch, S., Jamin, P., Orban, P., Brouyère, S., Dassargues, A. and F. Nguyen. 2015. Quantitative temperature monitoring of a heat tracing experiment using cross-borehole ERT, *Geothermics* 53 : 14-26.
- Hoffmann R., Dassargues A., Goderniaux P. and Th. Hermans, 2019. Heterogeneity and prior uncertainty investigation using a joint heat and solute tracer experiment in alluvial sediments. *Frontiers in Earth Science* 7, 10.3389/feart.2019.00108
- Hoffmann R., Goderniaux P., Jamin P., Chatton E., Labasque T., Le Borgne T. & Dassargues, A. 2020. Continuous dissolved gas tracing of fracture-matrix exchanges. *Geophysical Research Letters* 47(17) e2020GL088944.
- Hoffmann R., Maréchal J.C., Selles A. and A. Dassargues. 2022. Heat tracing in a fractured aquifer with injection of hot and cold water. *Groundwater* 60(2): 192-209.

- Hoffmann R., Goderniaux P., Jamin P., Orban Ph., Brouyère S. and A. Dassargues. 2021. Differentiated influence of the double porosity of the chalk on solute and heat transport. In *The Chalk Aquifers of Northern Europe*. Farrell, R. P., Massei, N., Foley, A. E., Howlett, P. R. and West, L. J. (eds), Geological Society, London, Special Publications, 517.
- Huysmans, M. and A. Dassargues. 2005. Review of the use of Peclet numbers to determine the relative importance of advection and diffusion in low permeability environments. *Hydrogeology Journal* 13(5-6) : 895-904.
- Irvine, D.J., Simmons, C.T., Werner, A.D. & Graf, T. 2015. Heat and solute tracers: how do they compare in heterogeneous aquifers? *Groundwater* 53(S1): 10-20.
- Klepikova, M., Wildemeersch, S., Jamin, P., Orban, Ph., Hermans, T., Nguyen, F., Brouyère, S. and A. Dassargues. 2016. Heat tracer test in an alluvial aquifer: field experiment and inverse modelling, *Journal of Hydrology*, 540 :812-823.
- Payne, F.C., Quinnan, A. & Potter. S.T. 2008. *Remediation hydraulics*. Boca Raton: CRC Press/ Taylor & Francis.
- Tamayo-Mas, E., Bianchi, M. & Mansour, M. 2018. Impact of model complexity and multi-scale data integration on the estimation of hydrogeological parameters in a dual-porosity aquifer. *Hydrogeol. J.* 26: 1917-1933.
- Wildemeersch, S., Jamin, P., Orban, P., Hermans, T., Klepikova, M., Nguyen, F., Brouyère, S. and A. Dassargues. 2014. Coupling heat and chemical tracer experiments for estimating heat transfer parameters in shallow alluvial aquifers. *Journal of Contaminant Hydrology* 169(0): 90–99.
- Wood, W.W., Kraemer, T.F. & Hearn, P.P. 1990. Intergranular diffusion: an important mechanism influencing solute transport in classic aquifers? *Science* 247:1569–1572.
- Worthington, S. R., Foley, A. E., & Soley, R. W. 2019. Transient characteristics of effective porosity and specific yield in bedrock aquifers. *Journal of Hydrology* 578: 124129.