




16-11-2023 – 12H15 – 19H – VUB BRUSSELS

CASE STUDY OF A DESICCANT EVAPORATIVE COOLING SYSTEM IN DENMARK

ZEOLI Alanis, JOHRA Hicham, GENDEBIEN Samuel, LEMORT Vincent



Presentation Outline



Introduction to the
IDCS Project



Description of the
Case Study



System Monitoring
and Operation



Performance
Analysis

The IDCS project

Instant District Cooling System (IDCS) project:

- Minimal heating demand in summer : the district heating network (DHN) is almost not used
- De-electrification of the cooling load
- Coupling of the cooling production and the waste heat management
- Connection to DHN to reduce the load on electrical network
- Optimization of the existing DHN
- Enhancement of the heat market



Figure 1 – Principle of a DHN.




Figure 2 – DHN in Denmark.





Figure 3 – Heat sources of the DHN.
source: Danish District Heating Association.

The IDCS project

First prototype of the IDCS project:

- Performance evaluation of an AHU in a large building
- Connection with the district heating network
- University building suffering from overheating in summer



Zone 6
Test zone with new
AHU installed

Zone 1
Reference zone with
conventional
ventilation system



Description of the building test case

Building regulation energy class



- Maximum infiltration rate 1.5 L/s.m²
- Maximum losses through building envelope 7 W/m²
- Maximum total primary energy demand 71.4 kWh/year.m²

Construction



- Year of construction 2014
- Number of floors 5
- Ground surface area of the building 5 036 m²

Building operation

- Maximum occupancy 4 450
- Ventilation requirements ~ 3 m³/h.m²




Desiccant Evaporative Cooling System – DECS



System Monitoring

- Installation with complete instrumentation and constant monitoring
- Data collection for **summer** 2021, 2022 and 2023 (May – September)
- Recording every 30 seconds
- Data for temperature, humidity and system consumption: electricity, heat and water.




Average daily indoor temperature over a warm period

Comparison of the daily indoor temperature in two zones of the same building:

- Zone 1 has a conventional ventilation system
- Zone 6 is equipped with DECS

Analysis of the daily temperature over a warm summer period (20th July – 3rd August 2021):


- High overheating risk in non ventilated zone due to high insulation level and South exposition
- Average temperature reduced by more than 2 K with DECS



Temperature and humidity control during a warm summer week


TEMPERATURE

- Supply temperature almost constant at 17°C
- Outdoor temperature as high as 32°C
- Indoor temperature never exceeds 25°C




RELATIVE HUMIDITY

- Supply RH around 80%
- Outdoor RH between 40 and 90%
- Indoor RH kept in an acceptable range





System limitations with outdoor conditions

- Temperature set point of the system : 16°C
- Set point temperature is not achievable for hot and humid days : outdoor relative humidity of 70-90%
- During hot and humid days, the supply temperature can still be as low as 18-19°C
- Performance limitation when the boundary conditions (outdoor air intake) reach critical heat and moisture content.



System control strategy

- Control of temperature and humidity in the building
- **Sequential** control strategy :
Mode 1 – If T_{out} is too low, heat recovery.





$$\dot{Q}_{cool} = \dot{m}_{vent} \cdot (h_6 - h_5)$$

System control strategy

- Control of temperature and humidity in the building
- **Sequential** control strategy :

Mode 1 – If T_{out} is too low, heat recovery.

Mode 2 – If $T_{in} < T_{setpoint}$, system acts as a ventilation system.



$$\dot{Q}_{cool} = \dot{m}_{vent} \cdot (h_6 - h_5)$$



System control strategy

- Control of temperature and humidity in the building
- **Sequential** control strategy :

Mode 1 – If T_{out} is too low, heat recovery.

Mode 2 – If $T_{in} < T_{setpoint}$, system acts as a ventilation system.

Mode 3 – If $T_{in} > T_{setpoint}$, activation of DEC on process side.



$$\dot{Q}_{cool} = \dot{m}_{vent} \cdot (h_6 - h_5)$$

System control strategy



- Control of temperature and humidity in the building
- Sequential** control strategy :

Mode 1 – If T_{out} is too low, heat recovery.

Mode 2 – If $T_{in} < T_{setpoint}$, system acts as a ventilation system.

Mode 3 – If $T_{in} > T_{setpoint}$, activation of DEC on process side.

Mode 4 – If $RH_{in} > RH_{max}$, activation of DW and HEX.



$$\dot{Q}_{cool} = \dot{m}_{vent} \cdot (h_6 - h_5)$$

System control strategy

- Control of temperature and humidity in the building

- Sequential** control strategy :



Mode 1 – If T_{out} is too low, heat recovery.

Mode 2 – If $T_{in} < T_{setpoint}$, system acts as a ventilation system.

Mode 3 – If $T_{in} > T_{setpoint}$, activation of DEC on process side.

Mode 4 – If $RH_{in} > RH_{max}$, activation of DW and HEX.

Mode 5 – If $T_{in} > T_{setpoint}$, activation of DEC on regeneration side (IEC mode).




$$\dot{Q}_{cool} = \dot{m}_{vent} \cdot (h_6 - h_5)$$

Feasibility Analysis vs System Operation

• Mode 1 • Mode 2 • Mode 3 • Mode 4 • Mode 5


Legend	
DECS	Desiccant Evaporative Cooling System
DEC	Direct Evaporative Cooling
IEC	Indirect Evaporative Cooling



Indoor thermal comfort



- Thermal comfort in zone equipped with DECS has been significantly improved.
- Indoor temperature is above 26°C less than 10% of the time during whole summer.

Yearly overheating hours	Above 26°C	Above 27°C
Regulation limit in Denmark for office buildings	100	25
Without cooling system	281	144
With DECS	88	33



Water consumption analysis

- Water treatment is necessary due to high content in limestone
- Water treatment through reverse osmosis
- Additional water consumption required to clean the filters
- Water treatment could be improved



Performance analysis


- Cooling load produced by the system and provided to the building

$$\dot{Q}_{cool} = \dot{m}_{vent} \cdot (h_6 - h_5)$$

- Calculation of thermal efficiency and electrical COP

$$\eta_{th} = \frac{\dot{Q}_{cool}}{\dot{Q}_{th}} \quad \text{and} \quad COP_{el} = \frac{\dot{Q}_{cool}}{\dot{W}_{el}}$$

- The electrical energy consumption includes the electricity consumption of auxiliaries
- The electrical COP is higher than a standard air-conditioning system
- The consumption of the cooling system is shifted to a thermal energy consumption
- There is an additional water consumption



The IDCS project

Average values during the cooling period

Total cooling load	41 MWh _{th}
Electricity consumption	10 MWh _{el}
Thermal energy consumption	40 MWh _{th}
Water consumption	44 m ³
Average COP	4.12
Average thermal efficiency	31%
Thermal comfort increase	44%

Thank you for your attention

