

Decision Support for Circularity in Office Building Design







Prof. Dr. Shady Attia
Sustainable Building Design Lab, UEE,
Applied Sciences, University of Liège, Belgium
shady.attia@uliege.be



Outline

How to design, build and operate circular buildings?

- 1. Circularity Definition (EN pren17980)
- 2. Circularity Principles (EN pren17980)
- 3. Multi-objective approach with multiple KPI




Figure 1.2. Ranking of EU leading member states that couple carbon neutrality and circularity requirements for new constructions



CEN 350: prenEN 18177 What is Circularity

Circular Economy


Target: The contribution of construction sector to circular economy. However, circular economy deals with macro economic aspects.

Circularity of Buildings

Is an attribute to assess the buildings, building elements and product level.

Circularity of Buildings

- 1) Circularity of materials & products
- 2) Circularity of building components
- 3) Circularity of construction works



CEN 350: prenEN 18177 What is Circularity

Circular Economy

Target: The contribution of construction sector to circular economy. However, circular economy deals with macro economic aspects.

Circularity of Buildings

Is an attribute to assess the buildings, building elements and product level.

Circularity of Buildings

- 1) Circularity of materials & products
- 2) Circularity of building components
- 3) Circularity of construction works



Circularity Definitions

Definitions, Metrics and Key Performance Indicators

According to prenEN 18177:



Circularity in buildings refers to the degree to which a building and its components are aligned with the principles of a circular economy, by being designed, used, maintained, adapted, and deconstructed in ways that:

- 1. Minimize resource extraction and waste,
- 2. Extend the useful life of components and materials, and
- 3. Enable high-value reuse, remanufacturing, or recycling through multiple life cycles.

Circularity Definitions

European Commission, CPR, and CEN

Life Extension (Slowing the loop)

Disassembly & Reversible Assembly (closing the loop)

Material Circularity & Recoverability

Resource Efficiency (Narrowing the loop)

Traceability & Information

Reverse Supply Chains & Business Models

Sustainability

CEN European CEO Standardization

Circularity

• prEN 18177

Carbon Neutrality

• EPBD WLC 2028

1. EU policy & standardization (governance spine) •European Commission (CPR, EPBD recast, Green Deal).

2. Rating systems & applied schemes (market translators)

•Actors: Level(s) (EU JRC), BREEAM, DGNB/BNB, LEED, GRO (BE), klimaaktiv (AT).

The Four Main Streams of Circularity in Construction

3. LCA / Environmental Product Declarations (impact accounting)

Core: EN 15804+A2 (EPDs), EN 15978 (building LCA), ISO 14040/44.

4. MFA & footprint logic (resource efficiency)

•MFA scholars, PEF (Product Environmental Footprint), Circular Footprint Formula (CFF).

EU Taxonomy

Sustainability

• ISO 14040 / ISO 14044

• ISO 21930

Levels Framework

• EN 15978

• EN 15804 + A2

Circularity


Carbon Neutrality

EPBD WLC 2028



EU-27 Regulations

Directives, Certifications and Standards



CEN/TC 350/SC 1 – Circular Economy in Construction prEN 18177

•WG 1 – Framework, Principles & Definitions: Establishes common terminology, KPIs, and a guiding framework for circularity.

•WG 2 - Gap Analysis,

Conclusions & Recommendations Identifies current practice gaps and proposes standardization priorities.

•WG 3 – Chair's Advisory Group Provides strategic coordination and oversight across WGs.

•WG 4 – Circular Information in Construction Works: Focuses on building/material passports, data transparency, BIM integration.

•WG 5 – Circularity Assessment
Develops methodologies and metrics
for evaluating circularity.

•WG 6 – Reuse of Construction Products/Materials: Sets standards and guidance for reusing materials and product take-back.


•WG 7 – Circular Design for the Construction Sector

Promotes design strategies for adaptability, disassembly, and reuse.

•WG 8 – Pre-Demolition/Pre-Redevelopment Audits &


Evaluation: Standardizes procedures for assessing materials before demolition or refurbishment

Lifecycle Stages of Building Products CEN 15978:2018+A2



The Science behind it

Metrics and Key Performance Indicators



Material Flow Analysis
Resource Flow Analysis
Life Cycle Impact Assessment
Building Performance Simulation

You can't manage what you don't measure.























The Science behind it

Materials Environmental Impact








The Science behind it


Life Cycle Assessment



énergies grises embedded energy

· peinture murale Walls paint


consommation en kWh
pour 100 m2 de peinture
murale



Multi-objective approach with multiple KPIs

Building Circularity Framework

Directives, Certifications and Standards



Designers

Circular, Cradle to Cradle, Regenerative and Bio-based buildings

a) Fokker 7+8 Distrib.Centre











d) Iewan Social Housing

e) Circl: ABN Circular Pavillon

f) Circular retrofit lab (VUB)








Photos of the selected projects studies (Attia and Al-Obaidy 2021)

Six demonstration projects were selected based on their carbon footprint and circularity features

Circularity Evaluation Framework

Circular and bio-based buildings

1. GHG emissions




6. Design for **Disassembly** (DfD)

5. Product-service systems (PSS)

4. Design for Adaptability (DfA)

→ Building 01 → Building 02

Circularity criteria	%	Evaluation	
Carbon footprint (According to TOTEM indicators)	%100	10 70 00	
1.1 Global warming	%10		
1.2 Ozone depletion	%10		
1.3 Acidification for soil and water	%10		
1.4 Eutrophication	%10		
1.5 Photochemical ozone creation	%10		
1.6 Depletion of abiotic resources; elements and fossil fuels	%10		
1.7 Human toxicity: cancer and non-cancer effects	%10		
1.8 Particulate matter	%10		
1.9 Ionizing radiation: human health effects	%5		
1.10 Ecotoxicity: freshwater	%5		
1.11 Water resource depletion	%5		
1.12 Land use: occupation and transformation (soil organic matter and biodiversity).	%5		
2. Reuse content	%100	10 10 10	
2.1 History of bearing load			
2,2 Reused content	%80		
2.3 Recycled content (by products)	%20		
2.4 Compliance with construction code			
3. Disassembly potential	%100		
3.1 Connections	%40		
3.2 Material passport	%30		
3.3 Tag & Track	%30		
4. Design for flexible	%100		
4.1 Modularity	%50		
4.2 Standardization of building elements	%50		
5. Land use	%100		
5.1 Land use footprint	%60	16 6 9	
5.2 Person per m²	%40		
6. Circular Economy Services Companies CESCO	%100		
6.1 Construction elements	%30		
6.2 Energy	%30		
6.3 Heating and Cooling system	%20		
6.4 Lighting	%20		






Het Centrum, Westerlo, Belgium

Design and Build Team

On the 7th of February 2021, SBD Lab signed an agreement with Kamp C to be a part of the consortium, doing LCA, and providing consultancy on the design for disassembly

Architect	Design & engineering	Structural engineering	Constructor	Constructing with green & natural elements	Geothermal energy	EPB reporting	Concrete technology	Research
West Architecture	TEN-agency	Streng-th	Beneens	Muurtuin	Tenerga	VESTAD	ResourceFull	VITO








Het Centrum, Westerlo, Belgium

Documentation

On the 7th of February 2021, SBD Lab signed an agreement with Kamp C to be a part of the consortium, doing LCA, and providing consultancy on the design for disassembly











1. GHG Emissions

Low carbon and bio-based buildings



Materials Embodied Energy Content

Amount of energy needed for a material, including mining, production and delivery at construction site per m³ of material








1. GHG Emissions

Embodied and Operational Emissions





- 2023, Operational emissions:
- 4 kgCO2.equiv. per m2 for new residential buildings
- 2023, Embodied emissions (Office)
 1000 kgCO2.equiv per m2



- 2023, Operational emissions:
- 12 kgCO2.equiv. per m2 for new residential buildings
- 2026, Embodied emissions (dwelling)
 750 kgCO2.equiv per m2



Embodied GHG Emissions

Categories of carbon negative materials & potential of negative emissions






Biochar

Captured carbon Biomineralization (Low carbon aggregates)

Potential of negative emissions		
Biobased Materials	10-50%	
Charcoal Concrete	2-10%	
Carbonized Concrete	2-3%	

2. Land Use Impact


LCA based calculation ISO 14040



Set of environmental indicators for land use impact categories [5].

3. Reused Content

LCA based calculation ISO 14040











3. Reused Content

LCA based calculation ISO 14040

Refuse
Reduce
Renew
Re-use
Repair
Refurbish
Remanufacture
Re-purpose
Recycle
Recover





- CO2

Reused material

 Reusing the same material or element repeatedly more than once

Reclaimed materials

 Reclaiming and reusing material in its existing form either for its original purpose or an alternative purpose

Recycled materials

Using materials to make new products

- Circularity Reusable material

 Virgin materials that could be reused for their original purpose, not recycled as new products or materials












3. Reused Content

Tag and Trace + Material Passport + Blockchain



Log- Management Log- Maintanance Record changes to structure Facility manager Name and Code Name and Code Performance Location Specifications Manual-Assembly Manual-disassembly Designer Manufacturer/ Manual-Maintanace Certification supplier Technical Lifespan Composition of Material Material Toxicity Contractor Supplier Manual-Assembly Design As built data Log- Management Build Log- Maintanance

LIÈGE université
SBD Lab

4. Design for Adaptability (DfA)


Flexible Buildings



Adaptable Buildings



Figure 2 Six Levels of Adaptability by Schmidt and Austin 2016




T



5. PSS Product-service systems

Circular Economy Services Companies + Leasing Elements

A CE service company is a company that provides a broad range of circularity solutions, including designs and implementation of materials savings projects, retrofitting, materials reuse, materials infrastructure outsourcing, materials replacement and risk management.





5. PSS Product-service systems

Circular Economy Services Companies + Leasing Elements

A CE service company is a company that provides a broad range of circularity solutions, including designs and implementation of materials savings projects, retrofitting, materials reuse, materials infrastructure outsourcing,

materials replacement and risk management.







5. PSS Product-service systems

Circular Economy Services Companies + Leasing Elements



Building life stages CEN 15978:2018+A2

Description of the stages during the buildings' life, according to E




Figure 1: Lifecycle stages of building carbon. Data source: BS EN 15978:2011 Source: Bowles, Cheslak, and Edelson 2022

LIÈGE université
SBD Lab

ISO 20887 – 2020: Design for disassembly and adaptability




INTERNATIONAL STANDARD ISO 20887

> First edition 2020-01

Sustainability in buildings and civil engineering works — Design for disassembly and adaptability — Principles, requirements and guidance

Développement durable dans les bâtiments et ouvrages de génie civil — Conception pour la démontabilité et l'adaptabilité — Principes, exigences et recommandations



t' Centrum, Westerloo, BE (Benees Architects)








Table 1: Possibilities of reusing timber by connection type (Hradil 2024)

Connections	Suitability	Note
Glued connections	not suitable	Cannot be separated without damaging the elements.
Carpentry joints	sometimes suitable	Notches can cause stress concentration if the elements are used in different configuration.
Nails, staples	sometimes suitable	Fail in bending, and therefore are difficult to remove without damaging the element.
Screws	mostly suitable	The same connector is not so effective in the same hole.
Bolts, dowels	suitable	The hole and the cracks should be checked.

Table 2: advantage & disadvantages regarding different characteristics, grouped by building system

	Assembly recovery	Component recovery	Heavy timber
Number of deconstruction steps	+	-	+
Dealing with damage	-	+	+
Complexity	±	±	+
Unknown/short service life	-	+	+
Verification	±	±	±
	Irrespective of building system		Irrespective of building system
Value of recovered elements	+	-	+

ISSO Standaard Referentiedetails: Meetmethodiek losmaakbaarheid



A	U-waarde [W/m²K]	0,185
16	Gevelbekleding vezelcement	0,01

Source: Circular buildings: disassembly potential measurement method

Source: UGent, To bio or not to bio, https://milieubewustisoleren.be/

LEVENSDUURKENMERKEN VAN DE SAMENSTELLING

De levensduur heeft een indicatie omtrent de levensduur per type materiaallaag. Op de afbeelding wordt de levensduur per materiaal aangeduid in een kleur volgens deze legende:

Site	Structure	Skin	Services	Space plan
oneindig	> 60 jaar	30 - 60	7 - 25 jaar	5 – 20 jaar
		jaar		

Constructieve producten (producten onder de laag 'Structure') blijven meestal de gehele levensduur van een gebouw behouden, terwijl de afwerking meerdere malen wordt vervangen. Producten met kortere levensduur dan die van het gebouw waarin ze toegepast worden, zijn extra interessant om losmaakbaar uit te voeren.

Het is dan ook zinvol dat verbindingen tussen lagen met een verschillende levensduur maximaal toegankelijk zijn en dat de type verbindingen eenvoudig en snel te demonteren zijn. Voornamelijk in functie van renovatie- en/of herstelwerken moet worden vermeden dat lagen met een verschillende levensduur met elkaar worden vermengd (doorkruisingen, zoals technische leidingen in een gespoten isolatie) en dat de zijden van de materiaallaag (randen zoals een tand- en groefverbinding) maximaal ongebonden zijn met aanliggende materiaallagen.




5 DRAAGBALKEN DAK		+
6 ROTSWOLISOLATIE	••••	+
7 GIPSKARTON PLAFOND		+





Designers

Material Choice



Key questio	ns to answer
1.	Does the material fit the purpose?
2.	To what extend is the material available?
3.	Can the raw material be mined locally?
4.	How much energy is needed to produce the material?
5. Clocal	Is the production process happening locally?
6.	How much waste is produced during the production process?
7.	Is there environmental contamination or hindrances during the production process?
8.	What maintenance does the material require?
9.	Is the product ready for disassembly?
10	Can the product be recycled?

Designers

Material Choice

Lessons Learned

Regenerative and Positive Impact Architecture



Design for Reversibility and Modularity

enable easy assembly and disassembly for long building lifespans



Design for Circularity

select components that can be properly reused and expanded their lifespan



Enable Collaborative Consumption and Leasing Services

extend the suppliers and producers responsibility

Certification and Liability

Green Building Rating Systems as Design Rules

Use Level(s) at 3 different levels



Level 1

Concept stage/qualitative

Level 2

Design and construction/ quantitative

Level 3

Reality/monitoring, including the handover to the client



Circular Buildings

Circularity Challenges

Definition and Terminology

•Persistent issue of contradicting or inconsistent language across standards and working groups.

Reference Service Life

•Timing and temporality remain a tension point: assessment now vs. postponing impacts into the future.

Building Taxonomy and Functional Unit

•Functional unit definition remains a key challenge in comparing resource flows, retained value, and environmental impacts.


Retained Value


•The retained value is the engine of the circular economy. The value must be retained from day one and not pushed to a second life.

Circularity Assessment

- •To assess circularity, we first need measurements, then data collection, and finally calculations.
- •Unfortunately, no one is currently doing measurements and data collection because there are no defined KPIs and metrics.

Decision Support for Circularity in Office Building Design







Prof. Dr. Shady Attia
Sustainable Building Design Lab, UEE,
Applied Sciences, University of Liège, Belgium
shady.attia@uliege.be



/in/shady-attia-14352a7 /www.shadyattia.org

