

## TOPICAL REVIEW

# Decarbonization potential of fuel cell technologies in micro-cogeneration applications: spotlight on SOFCs in a Belgian case study

To cite this article: Nicolas Paulus 2025 *Prog. Energy* **7** 022005

View the [article online](#) for updates and enhancements.

## You may also like

- [Do alternative irrigation strategies for rice cultivation decrease water footprints at the cost of long-term soil health?](#)  
John Livsey, Thomas Kätterer, Giulia Vico et al.
- [Limits to forests-based mitigation in integrated assessment modelling: global potentials and impacts under constraining factors](#)  
Théo Rouhette, Neus Escobar, Xin Zhao et al.
- [Investigating afforestation and bioenergy CCS as climate change mitigation strategies](#)  
Florian Humpenöder, Alexander Popp, Jan Philip Dietrich et al.



## TOPICAL REVIEW

# Decarbonization potential of fuel cell technologies in micro-cogeneration applications: spotlight on SOFCs in a Belgian case study

RECEIVED  
30 January 2024REVISED  
2 December 2024ACCEPTED FOR PUBLICATION  
18 December 2024PUBLISHED  
30 January 2025

Nicolas Paulus

Department of Electromechanics, Industrial Engineering Higher Education Institution of the Province of Liège (HEPL), Liège, Belgium

E-mail: [Nicolas.paulus@hepl.be](mailto:Nicolas.paulus@hepl.be)**Keywords:** carbon budget, DCSOFC, fuel cell, negative emissions, CCU, CCS, carbon absorption

## Abstract

There is a plethora of fuel cell technologies, many of which hold great promise in terms of their decarbonisation potential, which this paper aims to explore. In fact, this paper is primarily based on the only two existing technologies on the market, polymer exchange membrane fuel cells and solid oxide fuel cells (SOFCs). Unfortunately, these commercial systems mainly use natural gas as primary fuel due to its cost and practicality (easy transport and storage, existing infrastructures, etc). Using Belgium as a case study, this paper shows that their GHG mitigation potential remains rather insignificant compared to the average individual carbon footprint if their fuel is not decarbonised. Even so, their mitigation potential would still be far from sufficient, and other measures, including behavioural changes, would still need to be implemented. Nevertheless, some emerging fuel cell technologies, such as direct carbon SOFCs (DC-SOFCs) or direct formic acid fuel cells, offer the possibility of facilitating pure CO<sub>2</sub> capture at their anode outlet, thus allowing for potential negative emissions. Using a case study of the electricity demand of an average Belgian home (with two adults) supplied by an efficient biomass-fuelled DC-SOFC, this paper shows that these negative emissions could be up to about 4 tCO<sub>2eq</sub> yr<sup>-1</sup>. By comparison, the IPCC's Sixth Assessment Report estimated the emissions footprint that could never be mitigated, even with future net-zero CO<sub>2</sub> emissions, to be 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita, implying that climate neutrality will require similar levels of carbon sequestration. In populous Western countries, natural carbon sinks are unlikely to be sufficient, and the potential negative emissions of emerging fuel cell technologies will be welcome.

## Nomenclature

AFC	Alkaline fuel cell
AR6	Sixth assessment report (of IPCC)
AwAC	Agence wallonne de l'Air et du Climat (Climate and Air Walloon Agency)
BECCS	Bioenergy carbon capture and storage
CCGT	Combined cycle gas turbine
CCS	Carbon capture and storage
CCU	Carbon capture and utilisation
DAFC	Direct alcohol fuel cell
DCFC	Direct carbon fuel cell (DC-SOFC, also named SO-DCFC is one type of DCFC)
DC-SOFC	Direct carbon solid oxide fuel cell, equivalent to SO-DCFC
DFAFC	Direct formic acid fuel cell
DME	Dimethyl ether
EFC	Enzymatic fuel cell
GHG	Greenhouse gasses

HHV	High heating value
HT	High temperature
IPCC	Intergovernmental Panel on Climate Change
IT	Intermediate temperature
LCA	Life cycle assessment
LHV	Low heating value
LPG	Liquefied petroleum gas
LT	Low temperature
MC-DCFC	Molten-carbonate direct carbon fuel cell
MCFC	Molten-carbonate fuel cell
MEF	Marginal emission factor
MFC	Microbial fuel cell
MH-DCFC	Molten-hydroxide direct carbon fuel cell
(micro-)CHP	(micro) combined heat and power
OEM	Original equipment manufacturer
PAFC	Phosphoric acid fuel cell
PEMFC	Proton exchange membrane fuel cell (or polymer electrolyte membrane fuel cell)
SDG	Sustainable development goal
SMP	System marginal price
SO-DCFC	Solid oxide direct carbon fuel cell
SOFC(-O/-H)	Solid oxide fuel cell (with oxygen-ion/proton conduction)


## 1. Introduction

In its AR6, the IPCC established the remaining carbon budget that humanity can emit from 1 January 2020, with a 67% probability of limiting global warming to +2 °C above pre-industrial levels, at 890 GtCO<sub>2</sub> [1].

One recognised difficulty is the allocation of this carbon budget among countries [2] (and individuals [3]). Two well-known approaches are the ‘grandfathering’ principle (measures of ‘inertia’) and the ‘equity’ principle [4]. The ‘grandfathering’ principle maintains that the carbon budget should be distributed among countries in accordance with their existing emission levels. In contrast, the ‘equity’ principle asserts that the budget should be allocated in proportion to their population levels, i.e. that every human being has the same ‘right to pollute’. The ‘grandfathering’ principle is the subject of considerable criticism, primarily on the grounds that it favours ‘the perpetuation of an unfair allocation of rights on the basis of the previous unfair allocation of the same rights’ [5]. This means that it is already unfair enough that historical per capita emissions were not equal across countries, so they should not be used as a basis for further (inequitable) carbon budget allocations. Consequently, if countries integrate carbon budgets into their climate strategies (as they should [6]), they usually adhere to the principle of ‘equity’ [3]. This is exemplified by France and Wallonia [7], one of the three Belgian regions that serve as the case study in this paper.

As a final individual target, it is often considered that the 2050 carbon footprint should be capped between 1 and 2 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita [8]. For instance, a target of 2 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita is commonly adopted by online carbon footprint calculators [9]. However, it was recently underscored that, in order to achieve GHG neutrality in regions/nations such as France and Wallonia (or, by extension, Belgium), it is preferable to reduce the individual carbon footprint target to approximately 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita [3]. Indeed, that final GHG footprint will have to be absorbed territorially to meet the climate-neutral targets (such as those implied by the European Green Deal [10]). This could either be performed through nature-based, i.e. natural sinks [11], or technological methods [12]. However, the latter are still immature: they can be considered too risky [7] and ethically questionable [13] for climate policies to fully rely on them, although their development is still highly needed in the context of risk mitigation. Therefore, it has been demonstrated that, in densely populated regions/nations such as Belgium and France, reaching such a minimal threshold of 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita with the capacities of natural carbon sinks will be challenging enough (to ensure GHG neutrality) [3]. In fact, the aforementioned study [3] posited that an increase in natural sinks of at least +300% above current levels would be necessary to achieve the desired outcome. This would entail maximising carbon uptake across all territorial areas through deep land use change considerations (implementation of intensive urban vegetation, alternative agricultural techniques, etc).

Moreover, at net-zero CO<sub>2</sub> emissions (assumed in 2050 for the case study selected in this study, based on the European Green Deal [10]), the IPCC has indicated that all GHG could not be completely mitigated as efficiently as CO<sub>2</sub>. A 8 GtCO<sub>2eq</sub> yearly footprint would indeed remain for humanity [1]. In accordance with the ‘equity’ principle and considering a projected 2050 global population of 7.735 billion people [14], this also leads to an individual unmitigated 2050 footprint of approximately 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita.



Consequently; the 2050 final GHG footprint target (of 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita) will thus be represented solely by non-CO<sub>2</sub> GHG pollutants.

It is regrettable that current GHG emissions remain significantly above the target level. For illustrative purposes, consumption-based CO<sub>2</sub>-only emissions (exclusive of the full carbon footprint) have been reported for the year 2021 at respectively 7.2 tCO<sub>2</sub> yr<sup>-1</sup> and 7.0 tCO<sub>2</sub> yr<sup>-1</sup> per capita for the European Union and China (excluding emissions from land use, land-use change, and forestry emissions) [15]. Individual carbon footprint figures (including all GHG) are however more difficult to aggregate. Nevertheless, the average individual carbon footprint for Europe was reported to be 9.0 tCO<sub>2eq</sub> yr<sup>-1</sup> for the year 2015 [16], while for China it was 8.1 tCO<sub>2eq</sub> yr<sup>-1</sup> for the year 2012 [17].

With regard to the selected case study of Belgium, the average individual carbon footprint has remained relatively stable over time and has been established to 16.5 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita for the year 2001 [18], 16 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita for the year 2007 [19], and more recently, to 15.4 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita for the year 2011 [20]. According to an open-access web application available since 2024 [21], which allows for visualizing countries' and regions' carbon footprints using Sankey diagrams and which is documented in detail in several publications [22–24], those order of magnitudes are confirmed. It is noteworthy that the same [21] reports a carbon footprint only slightly lower for the year 2019 (latest available data), i.e. of 15.2 CO<sub>2eq</sub> yr<sup>-1</sup> per capita (considering a consumption-based accounting method).

At the residential scale, micro-cogeneration fuel cell technologies are regarded as a promising area of development, particularly in their three main markets, which are Japan, Europe, and South Korea, due the implementation of ad hoc-aimed subsidies and programs [25–27]. The approximate doubling of the market on an annual basis (at least up to around 2012) [26], is illustrated in figure 1. It is notable that South Korea still has extremely ambitious targets for power generation fuel cells: 2.1 GW<sub>el</sub> to achieve by 2040 for 'fuel cell for domestic buildings' in general and 15 GW<sub>el</sub> for utility fuel cell power plants, including exports. These figures represent a significant increase from the 7.1 and 370 MW<sub>el</sub> reported in 2019, respectively [28–30].

Similarly, Japan has set an ambitious target of installing 5.3 million fuel cell micro-CHP systems by 2030, which it hopes will provide heat and electricity to 10% of Japanese homes [31]. At last, it has been reported that Europe aims to reach a capacity of 10 000 systems per year by 2021 [31, 32], with the objective of achieving (and stabilising), in its 'expected scenario', a capacity of approximately 3 million micro-CHP installations in the residential sector in 2030 [33]. The majority of micro-CHPs would be represented by fuel cells, with the objective of meeting the 'European Union Energy Goals 2030' [34]. This would correspond to a cumulative amount of approximately 15 million installations by 2030 [33].

In fact, the objective of this study is to quantify the current and expected carbon footprint mitigation potential of residential fuel cell micro-CHP systems in comparison to the average individual carbon footprint. Belgium is employed as a case study, utilising its average current dwelling as a representative

example. A key objective of this research is to include in the study some emerging fuel cell technologies, such as DC-SOFCs and DFAFCs, that offer the capability of facilitating pure CO<sub>2</sub> capture at their anode exhaust, thereby potentially enabling negative emissions.

Indeed, technologies exhibiting high CO<sub>2</sub> purity streams represent a significant opportunity for facilitating carbon capture, particularly in light of recent reports indicating that more than 80% of the other technological carbon absorption projects currently fail [35]. This is particularly pertinent to the selected case study of Belgium (and neighbouring countries/regions), where the high individual carbon footprint is coupled with limited natural carbon sink capacities [3].

Consequently, this research makes a direct contribution to four SDGs [36]: sustainable and modern energy for all (SDG7), sustainable cities and communities (SDG11), sustainable production (and consumption) patterns (SDG12), and climate action (SDG13).

## 2. Materials and Methods

### 2.1. Review of fuel cell types

The number of existing fuel cell technologies and fuel cell acronyms is considerable. Such differences may be observed with regard to the electrolyte, the temperature of the stack, the fuel, etc. Even the same fuel cell acronym can be related to different fuel cell types. To illustrate, DCFCs, which utilise solid carbon as fuel, can exist with a variety of electrolytes, including oxide ceramics (DC-SOFC), alkaline solutions, or molten carbonate ceramics [38]. Each one of those DCFCs involves different electrochemical redox reactions, which constitute the core of the fuel cell working principle, thereby defining the reactants and their flows on the electrodes and through the electrolyte [38].

In light of the considerable diversity of emerging technologies, it has been observed that classifying fuel cells primarily according to their charge carrier more accurately represents the electrochemical redox reactions involved than the conventional classifications that rely on the fuel or the electrolyte [38]. In fact, the majority of fuel cell types can indeed be classified according to four categories of charge carriers: H<sup>+</sup> (protons), OH<sup>-</sup>, O<sup>2-</sup> and CO<sub>3</sub><sup>2-</sup> [38].

Firstly, PEMFC [39], PAFC [39], MFC (Microbial Fuel Cell) [40], EFC [41], the main type of DAFC [42], DFAFC [43] and SOFC+ [44], also known as SOFC-H [45] SOFC(H<sup>+</sup>) [46], H-SOFC [47], PCFC (Protonic Ceramic Fuel Cell) [48], PC-SOFC [49], P-SOFC [50] or H<sup>+</sup>-SOFC [51], all utilise hydrogen ions (protons) as charge carriers, despite the differing nature of their fuel and electrolyte.

Secondly, the anion O<sup>2-</sup> is employed primarily in SOFC-O but also in (SO-)DCFC (equivalent to DC-SOFC) [52]. Thirdly, MCFC [43], also referred to as (MC-)DCFCs [52], employ carbonate anions (CO<sub>3</sub><sup>2-</sup>) as charge carriers. Lastly, (MH-)DCFCs [52] and AFCs [39], which encompass several fuel cell subtypes including the other main type of DAFCs [42], utilise hydroxide anions (OH<sup>-</sup>) as charge carriers.

### 2.2. Available fuels for commercial fuel cell micro-CHPs

Regarding the fuel type, hydrocarbons, particularly natural gas, have become the most viable energy source for fuel cell micro-CHP systems, owing to their capability to be converted into hydrogen on-site (if necessary) [53]. For instance, in contrast to SOFCs for which the elevated operating temperatures of the stack may permit internal reforming [54], external reforming is required with PEMFC systems [55], which is generally incorporated into the embodiment of commercialised systems [56].

Natural gas is distinguished from other fuels by its cost-effectiveness and availability [57]. This is further evidenced by its substantial reserves, which, as of 2015, were projected to sustain (2015) extraction rates for 55 years [57]. Furthermore, its distribution network is well established in numerous regions globally [57]. It is the author's understanding that all commercially available fuel cell micro-CHP systems utilise natural gas, with the exception of some in Asia, where LPG and kerosene have been reported to have been employed [57]. It is notable that some commercial systems are also reported as 'hydrogen-ready', particularly for applications where green hydrogen might be available [58].

### 2.3. Commercial micro-cogeneration fuel cell technologies

To date, only five fuel cell technologies have been considered for micro-CHP applications: LT-PEMFC and HT-PEMFC, SOFC-O, PAFCs, and AFC [59, 60]. SOFC-H, which are typically considered as a subset of IT-SOFCs [61], along with IT-SOFCs themselves, are still under study [38] and not regarded in this work as mature CHP technologies. Indeed, their electrolyte, anode, and cathode materials still need to be developed to achieve a sufficient power density and ensure the viability of their commercialisation [61]. Their commercialisation is in fact particularly limited by their cathode, which has traditionally exhibited poor activity or high thermal expansion [62]. Furthermore, SOFCs-H have been reported to have high manufacturing costs and scaling-up difficulties, which also impede their commercialisation [63].

**Table 1.** List of HT-PEMFCs commercialised micro-CHP products and their current availability status.

HT-PEMFC CHP commercial attempts	Current status of the product or its manufacturing company
Enerfuel by Enerfuel [85–89]	Websites not available (even the one of the manufacturing company). It also seems that the Enerfuel company focuses on the transportation sector [86, 89–91].
Elcore by Elcore [87, 92, 93]	The Elcore company declared bankruptcy in 2017 [94]. The Freudenberg company, which has taken over [94], stopped the commercialisation of HT-PEMFC CHP products to focus on fuel cell drive systems for heavy-duty vehicles [95] (probably because many flows have been reported on the Internet about the product [96]).
PureCell by ClearEdge [37, 89, 90]	The ClearEdge company declared bankruptcy in 2013 [97]. The Doosan company, which has taken over [97], seems to have stopped the commercialisation of the HT-PEMFC CHP products. They have mainly taken over the ClearEdge company for their industrial-scale phosphoric acid fuel cell (PAFC) catalogue, such as the “PureCell Model 400” (400 kW <sub>el</sub> ) [98]. It was yet reported that HT-PEMFC micro-CHP systems are still under development at the Doosan company [99].
Gensys Blue by Plug Power [37, 87, 90, 91, 100–104]	Only field trials were operated and the product never made it to the market [91, 100, 103]. Indeed, Plug Power gave a “No-Go” on the project back in 2012 [100].
Serenus by Serenergy [90]	In fact, only fuel cell stack modules were developed. Indeed, they were not commercialised directly as CHP units and had to be integrated with other features, such as a fuel processor, since PEMFC systems require a high-purity hydrogen fuel [71] and since they are simply air cooled (no dedicated heat recovery feature) [91, 105]. Furthermore, those fuel cell modules were mostly used in transportation applications [91]. It seems that the company (now named “Advent Technologies” [106]) no longer commercialises those systems but currently sells methanol-fed fuel cell systems with high temperature stacks. Those methanol fuel cells are DAFCs (direct alcohol fuel cells) [42], not designed for CHP but for transportation or backup power applications [89, 107].

Despite being developed earlier than PEMFCs and SOFCs, PAFCs and AFCs have not attracted substantial commercial interest due to the high manufacturing costs and low lifetimes respectively, inherent to these technologies [25]. Despite the absence of notable products that have been developed for the domestic CHP market utilising these technologies, they exhibit a multitude of desirable characteristics, at times even surpassing the performance of PEMFC CHP systems [64]. Previous studies have demonstrated or modelled these technologies at the 1–10 kW<sub>el</sub> scale as CHP units, employing hydrogen directly as fuel [64, 65]. It is noteworthy that PAFCs have been installed in large commercial and industrial applications for decades [27, 66, 67]. For instance, one commercial example has an electrical power output in the 100–400 kW<sub>el</sub> range [66]. However, this is not the case for AFCs [27, 67], likely due to their CO<sub>2</sub> intolerance and the necessity of a pure oxygen feed [38, 68]. Nevertheless, CO<sub>2</sub> cost-effective removal apparatus could be conceived and has been developed to enable simpler ambient air feeds [67]. In addition, similarly to LT-PEMFCs, there is a need to humidify the electrolyte through the inlet gasses for AFC technologies [69–71].

These limitations have been reported to predominantly confine PAFCs and AFCs to large-scale CHP applications (around 200 kW<sub>el</sub>) and space vehicle uses, respectively [72], which is why these technologies are not further considered in this work for micro-CHP systems.

In addition, to the best of the author’s knowledge, there is currently no HT-PEMFC system available on the market for residential micro-CHP applications. Furthermore, only a limited number of these systems have ever been (or are close to being) commercialised, as it has been reported in table 1. For the sake of clarity, as indicated by their acronyms, it should be noted that HT-PEMFCs differ from LT-PEMFCs mainly through the higher temperature capability of their electrolyte [38].

Indeed, it has been recently reported that micro-CHP HT-PEMFC systems may only become commercially available in the near future, with their relatively short lifetime currently representing a significant obstacle to their widespread adoption [73]. In fact, a number of the remaining challenges that

hinder HT-PEMFC commercialisation have been detailed in another recent publication, including the thermal instability of the catalyst [74].

Therefore, the only fuel cell technologies currently commercialised as micro-CHPs are (LT-)PEMFC and SOFC(-O), which have been compared in table 2, especially in terms of LHV electrical efficiency.

It is noteworthy that SOFC-PEMFC hybrid cogeneration systems have been studied approximately since 2000, initially based on the LT-PEMFC technology [75, 76]. In such SOFC-PEMFC hybrid systems, owing to the internal reforming ability of the SOFC, this latter is used for both electricity generation and fuel reforming. Indeed, it can exhibit a reformat gas at its anode exhaust and subsequently fuel a downstream PEMFC, which allows for eliminating the need for a reformer upstream of the PEMFC [75, 76]. A flowsheet of one example of a SOFC-PEMFC hybrid system is depicted in the following section in figure 5. SOFC-PEMFC hybrid systems may be designed with the intention of combining some of the advantages of the two underlying fuel cell technologies, such as a higher energy efficiency (mainly by having removed the reformer of the PEMFC) while exhibiting a fast startup and a high stability [77]. However, until very recently, with the potential upcoming of the HT-PEMFC technology (if it ever becomes sufficiently mature, as inferred by table 1), those hybrid systems have been reported impractical due to complicated post internal SOFC reforming components that are needed to reduce the CO levels at the fuel inlet conditions required by a LT-PEMFC [75]. Nevertheless, in a modelling study, the hybridisation of a SOFC and a HT-PEMFC at the micro-CHP scale has been recently investigated in 2024, showing promising results compared to standalone systems in terms of efficiency, emissions, and lifecycle cost [75].

#### 2.4. Current and expected performance of micro-CHP systems based on a PEMFC or a SOFC

Back in 2010, the U.S. Department of energy hydrogen and fuel cells program established the expected performance of micro-CHP systems in accordance with fuel cell types [78]. The maximum LHV electrical efficiencies reported attainable for LT-PEMFCs, HT-PEMFCs, and SOFCs(-O) fed by natural gas were, respectively, established at 40%, 45%, and 60% [78].

Actually, numerous studies have reported a maximum LHV electrical efficiency of approximately 45% for HT-PEMFC micro-CHP systems fed by natural gas [37, 73, 78–80], thereby corroborating the aforementioned figure [78].

It is noteworthy that LT-PEMFC and SOFC(-O) commercial micro-CHP systems are already approaching those respective aforementioned efficiency figures [81, 82].

Despite some studies [73, 83, 84] indicating that the LHV electrical efficiency of LT-PEMFC micro-CHPs could reach up to 45% (owing to significant technical improvements in the fuel reforming processor), it is usually assumed that it is probable that electrical LHV efficiency targets of 45% (or more) can be achieved with HT-PEMFCs and SOFCs, but unlikely to be achieved by LT-PEMFCs [37].

Similarly, both Europe and the International Energy Agency have set the 2030 LHV electrical efficiency target for micro-CHP fuel cells (fed by natural gas or biogas) at up to 65% [108, 109]. This target seems to be achievable only with SOFC technologies [27, 110–113]. It is worth mentioning that the ‘Bloom Energy’ company, based in the U.S., has already been marketing a SOFC-based CHP unit, fed by natural gas (or biogas), since 2023 [114]. This unit has a power output of 330 kW<sub>el</sub>, which is higher than the micro-CHP range [59], and a net LHV electrical efficiency (AC) of 65% [114–116], which corresponds to the efficiency targets set by the European Union and the International Energy Agency for 2030 [108, 109].

In fact, the theoretical LHV electrical efficiency of an SOFC is close to 100% for the electrochemical direct oxidation of dry methane without consideration of parasitic losses, thus exhibiting no Carnot limit [117]. Similar efficiency analyses and outcomes have been documented for carbon-fuelled SOFCs (DC-SOFCs) [118]. With hydrogen or carbon monoxide, the theoretical efficiency of SOFCs is still approximately 70% (LHV) [117]. This high 70% figure is, in fact, sometimes already reported as the current upper electrical efficiency limit for SOFCs with internal reforming [119, 120].


In other recent developments within the (SOFC) industry, ‘Ceres Power’ (United Kingdom) has announced a 65% LHV electrical efficiency for a 5 kW<sub>el</sub> stack operating on methane (gross DC efficiency) [117, 125]. Lately, the ‘Robert Bosch’ company (Germany) has announced a 10 kW<sub>el</sub> demonstrator with a gross LHV DC electrical efficiency of 70% [126]. Finally, both those companies have announced that they increased this gross DC efficiency to 72.4%, based on the LHV of methane, for a 150 W<sub>el</sub> stack, developed within the framework of a collaboration [127]. Similarly, the ‘Elcogen’ company (Estonia) is commercializing SOFC stacks for micro-CHP OEMs with an announced gross DC LHV electrical efficiency of 72% [128], which has also been reported at 74% in 2021 [115, 129]. It is notable that it has been reported that a 74% DC LHV efficiency performance was also already achieved back in 2013 by the ‘SolidPower’ company (founded in Italy and recently renamed ‘SolydEra’) [129, 130].

It is noteworthy that this (still significant) discrepancy between gross DC and net AC efficiency may be attributed to the fact that DC gross electrical efficiency does not account for the parasitic power losses (in the

**Table 2.** Comparison between the two sole commercial micro-CHP fuel cell technologies, i.e. the (LT-)PEMFC and the SOFC(-O) systems. Reprinted from [43], Copyright (2014), with permission from Elsevier.

Fuel cell type & Charge carrier	Typical electrolyte	Major contaminants	Stack operating temperature (°C)	Specific advantages	Specific disadvantages	LHV electrical efficiency (%)
PEMFC & H <sup>+</sup>	Solid Nafion <sup>®</sup> , a polymer	Carbon monoxide (CO) <sup>a</sup> Hydrogen sulphide (H <sub>2</sub> S) <sup>a</sup>	60–80 Only low-temperature PEMFC are currently commercialised [121]	Highly modular for most applications High power density Compact structure Rapid startup due to low temperature operation Excellent dynamic response	Complex water and thermal management <sup>a</sup> Low-grade heat High sensitivity to contaminants <sup>a</sup> Expensive catalyst Expensive Nafion <sup>®</sup> membrane [122] Low fuel flexibility	40–60 (with H <sub>2</sub> ) Currently limited to 38.5 with CH <sub>4</sub> as some fuel needs to be burned to provide heat to a methane reformer [123]
SOFC & O <sup>2-</sup>	Solid yttria-stabilised zirconia, i.e. YSZ, a ceramic	Sulphides	800–1000	High electrical efficiencies High-grade heat High tolerance to contaminants Possibility of internal reforming Fuel flexibility Inexpensive catalyst Simpler water management—SOFC can work at a perfect drying state [124]	Slow startup Low power density Strict material requirements High thermal stresses Sealing issues Durability issues High manufacturing costs	55–65 (with H <sub>2</sub> ) Currently limited to 60%-65% with CH <sub>4</sub> [114, 121], i.e. still high thanks to the SOFC fuel flexibility

<sup>a</sup> Contaminants, thermal, and water management of PEMFC stacks have been discussed more deeply in another work [71].



**Figure 2.** Simplified (neutral) 'short' life cycle of CO<sub>2</sub> through an electroreduction unit and a DFAFC. Reprinted with permission from [134]. Copyright (2021) American Chemical Society.

current collection), the DC–AC power conversion losses, and the consumption of auxiliaries, such as the air blower power consumption (oxidizing agent supply at the cathode) [131]. Nevertheless, the aforementioned gross efficiency figures are so promising that it is not implausible to anticipate the advent of SOFC-based commercialised micro-CHP systems with LHV electrical efficiencies of 70%–80% or even higher in the foreseeable future. This is at least the assumption that will be considered in this work.



For information, for natural gas (and biogas) appliances (including fuel cells), HHV efficiencies can be obtained from the LHV efficiency figures thanks to the natural gas HHV to LHV ratio, which has been reported to be about 1.1094 [132], and which is extremely dependent of its chemical composition [133].

## 2.5. Negative emissions fuel cell technologies

It is this author's understanding that only two emerging fuel cell technologies offer the capability of facilitating pure CO<sub>2</sub> capture at their anode exhaust, thereby potentially enabling neutral (or even negative) CO<sub>2</sub> emissions [38].

Firstly, the DFAFC, which is quite similar to an LT-PEMFC (especially in terms of electrolyte, charge carrier, contaminants, efficiency, or operating temperature [38]), can decompose the formic acid fuel into CO<sub>2</sub> and protons at the anode [134]. Its working principle is depicted in the bottom part of figure 2, which presents a simplified (neutral) life cycle of CO<sub>2</sub> through an electro-reduction unit and a DFAFC [134, 135]. This neutral CO<sub>2</sub> cycle, in which formic acid qualifies as an electrofuel, that is to say a liquid hydrocarbon derived from (renewable) electricity as the primary source of energy [136], has the advantage of being 'short' as it does not rely on (slowly growing) biomass. The illustrated capture of CO<sub>2</sub>, its conversion into formic acid, and the subsequent utilisation in the DFAFC constitute a CCU technology [137]. It is noteworthy that formic acid fuel could be produced from biomass [134, 138], which, if associated with CO<sub>2</sub> sequestration (of the off-anode gasses), could enable negative emissions (the electro-reduction would thus not be needed). This would thus constitute a (BE)CCS technology, i.e. (Bioenergy) with Carbon Capture and Storage [137].


Secondly, the DC-SOFC, which is quite similar to a SOFC-O fed with hydrocarbons such as natural gas or biogas (especially in terms of electrolyte, charge carrier, sulphur contamination, efficiency, or operating temperature [38]) also exhibits an almost pure CO<sub>2</sub> stream at the anode exhaust [139]. Its working principle is depicted in the right part of figure 3, which presents a simplified (neutral) life cycle of CO<sub>2</sub> through a methanation unit, a SOFC, and a (SO-)DCFC. The illustrated capture of CO<sub>2</sub>, its conversion into biogas, and the subsequent utilisation in the SOFC constitute a CCU technology [137]. Negative emissions would trivially be obtained with a biomass-fed (SO-)DCFC if the high-purity CO<sub>2</sub> fuel cell exhaust stream was to be directly sequestered instead of being converted into biogas, which would thus constitute a (BE)CCS technology, i.e. (Bioenergy) with Carbon Capture and Storage [137].



This neutral CO<sub>2</sub> cycle has the disadvantage of being 'long' as it relies on the slow growth of biomass. However, it offers the opportunity, for the same amount of biomass fuel, of combining the electrical production of two of the most efficient fuel cell technologies [38], which, as already discussed, exhibit theoretical electrochemical direct oxidation efficiencies that can be considered equal to 100% [117, 118].

Similar other (CO<sub>2</sub>-neutral) cycles involving CCU with (SO-)DCFCs have been reported in the literature, such as the one exhibited in figure 4 [140], which illustrates a way of converting methane fuel into methanol and/or DME while producing (green) electricity. Slightly different cycles have been reported by the same author in another paper [141]. In figure 4, 'Turquoise' hydrogen refers to hydrogen produced via pyrolysis of fossil fuels, where the by-product is solid carbon (that can be stored or utilised, hence exhibiting a lower carbon footprint) [142]. A methanation unit could replace the CO<sub>2</sub> hydrogenation unit to produce methane instead of methanol and/or DME, allowing for completely closing the cycle and preventing the extraction of fossil methane. It is noteworthy that both methanol and DME are well-known as versatile alternative fuels potentially useful in many applications, such as for the transportation and the power sector [143].

Configuration possibilities based on figures 3–4 are endless but leave the scope of this research.



**Figure 5.** Simplified (neutral) cycle of  $\text{CO}_2$  through a methanation unit, a SOFC, and a PEMFC. Reprinted from [144], Copyright (2023), with permission from Elsevier.

It should however be stated that, as mentioned in the paper used as reference and inferred by figure 2 [134], DFAFCs are mainly attractive for small portable applications and promising for automotive applications (rather than for cogeneration). This is attributable to the intrinsic similarities between their characteristics and those of LT-PEMFCs. In fact, this is mainly due to their low electrical efficiency in conjunction with their high power density, their straightforward fuel storage, and convenient fuel delivery [38]. Actually, in light of the aforementioned lower anticipated efficiency figure of the PEMFC technology in comparison to (DC-)SOFCs, it has been reported that historical PEMFC manufacturers have reached the conclusion that the future of fuel cells in domestic built environment applications lies with SOFCs, and have therefore ceased PEMFC development [104]. Therefore, in this paper, lower efficiency fuel cell technologies such as the PEMFC and the DFAFC technologies they derive from will no longer be considered from here onwards to focus solely on SOFC-based systems.

It is noteworthy that a SOFC-PEMFC hybrid system may also present negative emissions without complex sorbent-based carbon capture processes [144]. A typical biogas-fed SOFC can exhibit off-anode exhaust gasses containing several species that can be separated through well-known processes, such as  $\text{CO}_2$ ,  $\text{CO}$ ,  $\text{H}_2\text{O}$  (and, without off-anode recirculation, an excess of  $\text{H}_2$ ) [38, 145].  $\text{CO}$  can be transformed into  $\text{CO}_2$  and  $\text{H}_2$  through a water gas shift reactor and if necessary, for the remaining  $\text{CO}$ , transformed into  $\text{CO}_2$  with oxygen through a preferential oxidation catalyst [71, 144]. The remaining  $\text{H}_2$  is processed through a PEMFC (that contributes to the electrical production), leaving only the  $\text{CO}_2$  with water (in a vapour state) [144]. It can be pointed out that using a HT-PEMFC (if ever commercially mature) instead of a LT-PEMFC would allow for not having to use the selective oxidation catalyst (and the supplied oxygen), as HT-PEMFCs are tolerant to the small quantity of  $\text{CO}$  that could remain in the flue gasses after the water gas shift reactor [38, 71, 75]. At the PEMFC anode exhaust, water can simply be liquefied and separated from the  $\text{CO}_2$  through several cooling and compression stages (through a carbon separation unit) [144]. The resulting  $\text{CO}_2$  of high purity can then be liquefied and sequestered, to enable the negative  $\text{CO}_2$  emissions potential of the whole system [144]. This SOFC-PEMFC hybrid system has been schematised in a  $\text{CO}_2$ -neutral cycle on figure 5. The illustrated capture of  $\text{CO}_2$ , its conversion into biogas, and the subsequent utilisation in the SOFC constitute a CCU technology [137]. Negative emissions would trivially be obtained if the high-purity  $\text{CO}_2$  fuel cell exhaust stream of the carbon separation unit were to be directly sequestered instead of being converted into biogas, which would thus constitute a CCS technology (Carbon Capture and Storage) [137]. It is noteworthy that another way of separating  $\text{H}_2\text{O}$ ,  $\text{H}_2$  and  $\text{CO}_2$  species effectively from a SOFC exhaust is through pressure swing adsorption processes [144].

## 2.6. Carbon footprint calculators

It has been chosen to use simple online carbon footprint calculators to illustrate the decarbonisation potentials of the considered fuel cell micro-CHP technologies. In fact, for the purposes of demonstration, the

selected individual carbon footprint calculator, which was first initiated back in 2014 [146], is that developed by AwAC, i.e. the Climate and Air Walloon Agency [147]. The primary reason for this selection is that it was developed by an official local agency. However, it should be noted that each carbon footprint calculator has its own specific accuracy, advantages, and limitations. Typically, the more complex and lengthy the associated survey is, the more accurate the results will be. However, this could present a significant barrier to accessibility for many individuals.

For example, the calculator in question does not take into account the impact of pet animals or of freshwater consumption. Similarly, the impact of ‘public services’, i.e. the carbon footprint of collective public infrastructure and services (that, are equivalently shared for all citizens of a given country/region), is also not accounted for by the selected calculator. It is noteworthy that this ‘public services’ footprint is the sole category that is not directly related to the individuals and that they are thus unable to directly influence. The responsibility for mitigating this category of emissions is therefore borne solely by the administration and its political choices.

It is therefore recommended that individuals utilise a number of carbon footprint calculators to better evaluate their sensitivity. Thus, for information and potential comparison purposes, a list of other well-known individual carbon footprint calculators has been provided in appendix A.

It is of the utmost importance for users to be aware of the provenance of the calculators they are utilising, as the underlying assumptions may be contingent upon geographical factors (such as the emission factors of grid electricity, for example). Similarly, the tool should preferably have been recently created or updated. Also, even if most calculators express the carbon footprint per capita in terms of all-GHG emissions ( $\text{CO}_{2\text{eq}}$ ), it is important to note that it is not always the case (some calculators may express their results in  $\text{CO}_2$ -only, for example).

It must also be remembered that such calculators only offer indicators and not accurate measured values. Indeed, the absolute value that results from those calculators is not really as important as its order of magnitude and trend over time.

In other words, the primary objective of such calculators is to provide a rough order of magnitude of an individual’s carbon footprint, and more importantly, to direct users towards the most impactful GHG mitigation actions they can implement at their individual levels. In fact, it is well-established that solving the climate crisis relies on changing human behaviour [148] and, to achieve it without redhibitory resistance, it is essential that applied policies and economics meet people where they are, utilising ‘audience-specific messaging and framing’ [149]. Using individual carbon footprint targets, such as the 2050 1  $\text{tCO}_{2\text{eq}} \text{yr}^{-1}$  per capita considered in this paper, along with providing people with simple carbon footprint calculators for self-evaluation and action planning, is therefore highly pertinent in this context.

Even though methods of calculating carbon footprint are far from a global consensus [150], ‘raising awareness’ by regularly monitoring one’s carbon footprint is indeed often considered the first step towards behavioural change and carbon footprint mitigation actions [151]. As a similar example, it has indeed been demonstrated that energy motoring, performed regularly by the occupants of a dwelling, allows for a significant reduction in the energy consumption of that dwelling through behavioural change [152].


## 2.7. Individual carbon footprint example without dwelling energy uses

Individual consumption habits are generally always considered in carbon footprint calculators but they greatly differ from one person to another, and it is not within the scope of this paper to establish ‘average’ habits of a given population. Furthermore, as the decarbonisation potential of fuel cell micro-CHP systems is mainly associated with the dwelling’s energy consumption, the assumptions pertaining to other domains of the individual carbon footprint are deemed inconsequential for the purposes of this study. Consequently, it has been decided to compute a single, realistic exemplar of an individual carbon footprint through the selected carbon footprint calculator. The assumptions implemented in the selected carbon footprint calculator are detailed in appendix B for the purpose of reproduction.

Those assumptions may still be regarded as representative of the typical case, in the sense that they are not describing extremely unrepresentative cases, such as a fully vegan diet coupled with only light-mobility uses or a fully red-meat diet accompanied by extensive travel in a heavy diesel vehicle.

The resulting carbon footprint simulation example (excluding energy use of the dwelling) is shown in figure 6 and is approximately 10  $\text{tCO}_{2\text{eq}} \text{yr}^{-1}$ —significantly above the 2050 target of 1  $\text{tCO}_{2\text{eq}} \text{yr}^{-1}$  per capita required for climate neutrality (based upon the unmitigable GHG emissions reported by the IPCC [1] and the projected global population [14] considered in this study). This difference already illustrates that even if dwellings achieve zero emissions from energy use, changes in behaviour and consumption choices remain essential.

Although it has been mentioned that the related assumptions (detailed in appendix B) were not intended to represent the case of the average Belgian or European citizen, the resulting carbon footprint reported in



**Table 3.** Chosen emission factors (from a previous study [154]) for the energy uses of the average Belgian residential dwelling, which is represented by its current average energy demands (reported in 2023) [153]. The subsequent carbon footprints of the average Belgian dwelling's energy uses are also established accordingly.

Dataset	Gas consumption emission factor (gCO <sub>2eq</sub> kWh <sup>-1</sup> )	Electricity consumption emission factor (gCO <sub>2eq</sub> kWh <sub>el</sub> <sup>-1</sup> )	Average gas consumption of the dwelling (kWh yr <sup>-1</sup> )	Average electricity consumption of the dwelling (kWh <sub>el</sub> yr <sup>-1</sup> )	Carbon footprint (tCO <sub>2eq</sub> yr <sup>-1</sup> )
Dataset 'A'	251	456	17 000	3500	5,86
Dataset 'E1'	254	167	17 000	3500	4,90

figure 6 (10 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita without dwelling energy uses) is consistent with the 15.2 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita (complete footprint) established for Belgium for the year 2019 [21–24].

It is worth mentioning that the remaining CO<sub>2eq</sub> emissions still reported for the dwelling in figure 6 are mostly related to the GHG emissions embodied in its construction (and that are vented onto the building's operational lifespan).

Up to this point, no consideration has been given to the energy uses of the dwelling (gas/electricity consumption). Consequently, the resulting individual carbon footprint (of 10 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita for the example given in figure 6), is not related to the choice of the space heating appliance or the utilisation of any cogeneration system, whether fuel cell-based or otherwise.

In other words, as previously stated, it can already be established with certainty that implementing fuel cell micro-CHPs, even when operating at 100% efficiency and fed by 100% biogas (or other climate-neutral fuels) represents an insufficient solution. Further action is required, including behavioural and consumption choice changes. It can already be acknowledged at this point that negative emissions technologies, such as DC-SOFC micro-CHP systems, which are the subject of this investigation, can also provide significant benefits in this regard (as it will be demonstrated in the following section).

## 2.8. Individual carbon footprint example with energy uses

Additionally, this paper employs the average Belgian dwelling as a case study to illustrate the decarbonisation potentials of fuel cell micro-CHP technologies. According to the Belgian regulator [153], it corresponds in 2023 to 17 000 kWh of natural gas consumption and 3500 kWh<sub>el</sub> of electrical consumption per year. Those figures have been reported in table 3.

Emission factors for gas and electricity consumption (mainly applicable to Belgium) have been extensively documented in a prior study [154]. Two LCA emission factor datasets, namely the dataset 'A' and the dataset 'D1' from the aforementioned research [154] have been replicated in table 3 and employed in this study.

Dataset 'A' was initially provided for the purpose of establishing CO<sub>2eq</sub> savings from CHP units when compared to 'reference systems', which consist of a gas condensing boiler of 90% of average LHV efficiency for heat production and of a CCGT of 55% of average LHV efficiency for electrical consumption [155]. This is not only relevant to Belgium but also to all regions/nations that regularly utilise CCGTs on their grids. It basically assumes that the decentralised CHP electrical production (e.g. of fuel cells) is replacing the electrical production of CCGTs not equipped with heat recuperation, which would generally require a district heating connection due to the size of the CCGT plants [156]. While this is a promising approach in the context of the energy transition, current CCGTs are not generally connected to district heating networks [157].

Dataset 'D1' considers the Belgian statistical average electrical consumption emission factor between the population of unweighed hourly emission factors provided by Electricity Maps [158] for the whole year 2021. It therefore better corresponds to the average (Belgian) electrical mix than dataset 'A'.

However, none of the considered emission factors (neither dataset 'A' nor dataset 'D1') take into account the electrical transportation and distribution losses (which can reach about 6%–7% in the European Union [159]) that are avoided with decentralised electrical production systems, such as (micro-)CHPs.

Actually, the electrical market and electrical prices (at least in the European Union) rely on the SMP principle [160], which signifies that they are defined by the latest power plants that must be activated to meet the demand. These have typically been and, in Belgium, continue to be, CCGT plants, either for reasons of flexibility and/or economic benefit. In fact, according to the hourly data provided by Electricity Maps [158] for the year 2021 (that have been used to compute the dataset 'D1'), there was always some electrical production originating from natural gas power plants. As again evidenced by the data provided by Electricity Maps [158], this was also the case for the year 2020. Therefore, through the SMP principle, the MEF, which 'reflects the emissions intensities of the marginal generators in the system, i.e. the last generators needed to meet demand at a given time' [161], can be regarded as consistently equivalent to the emission factor for electricity production from natural gas power plants, as reported by the dataset 'A' in table 3. Furthermore, this is anticipated to remain the case in Belgium for the foreseeable future, considering the fact that the government is currently supporting the construction of new CCGTs, which are intended to (at least partially) phase out old nuclear power plants [162, 163].

For this study, and at least for Belgium, both dataset 'A' (marginal emissions) and dataset 'D1' (average emissions) from table 3 can thus indeed be regarded as relevant, with dataset 'D1' possibly considered to hold an even greater significance than dataset 'A' in reflecting the overall characteristics of the electrical grid.

The average Belgian dwelling energy consumptions related to datasets 'A' and 'D1' respectively correspond to carbon footprints (of energy usage) of 5.86 tCO<sub>2eq</sub> yr<sup>-1</sup> and 4.90 tCO<sub>2eq</sub> yr<sup>-1</sup>, which must be added, in proportion to the number of occupants in the dwelling, to the individual carbon footprint established in figure 6 (which was close to 10 tCO<sub>2eq</sub> yr<sup>-1</sup>). When divided by the number of adult occupants considered (i.e. two, as reported in appendix B), those energy uses carbon footprint figures account for only approximately 25% of the total individual carbon footprint chosen example. This example once again emphasises the necessity for carbon footprint mitigation to extend beyond dwelling energy uses.

These constitute from here onwards the 'base scenario' of this research, which will be used as a reference to illustrate the decarbonisation potential of fuel cell micro-CHP technologies. To sum up, regardless of the emission factor dataset from table 3 (either 'A' or 'D1'), the reference 'base scenario' does not include any (micro-)CHP system and consistently assumes that the dwelling's heat demands are supplied with a gas condensing boiler (of 90% of LHV efficiency). Additionally, it assumes that the electrical demand is supplied by the grid, with its specific inherent assumption regarding the electrical emission factor.

### 3. Results

As it has been demonstrated that other fuel cell technologies are either not mature enough and/or not as efficient, this study has been focusing on SOFC technologies, which specific advantages have been presented in table 2, and on DC-SOFCs they derive from. Consequently, table 4 evaluates the carbon footprint of several 'ideal' (DC-)SOFC micro-CHP systems that would correspond to an electrical production that would match the electrical consumption of the average Belgian dwelling given in table 3 (3500 kWh<sub>el</sub>). It also establishes the carbon footprint savings permitted by those fuel cells in comparison to the 'base scenario' established in the preceding section. As previously discussed, the thermal demand is assumed to always be equal to the 2023 average Belgian dwelling given in table 3 (corresponding to a 17 000 kWh of gas consumption with a gas

condensing boiler averaging 90% of LHV efficiency). In all cases, it is assumed that the implementation of the fuel cell micro-CHP will reduce the thermal demand for the gas-condensing boiler.

As the energy transition progresses, it is likely that the renovation of buildings will result in a decrease in the thermal demand of the average dwelling. Conversely, the electrification of mobility is likely to result in an increase in the electrical demand of the average dwelling (in comparison to the demand considered in this study) [164]. This is however not taken into account at this point.

For the sake of simplicity, all the 'ideal' cases considered in table 4 assume that the (DC-)SOFC is fully flexible in terms of electrical production, matching the dwelling's electrical load profile exactly. However, it is not yet realistic to expect that current SOFC systems will be able to be shut down (or modulated down to 0%) due to their long startup times [54]. Nevertheless, the modulation range of SOFC systems currently on the market is already quite large (in the 33%–100% range [166]) and it is reasonable to hope that it will even be extended in the future.

The efficiencies of the fuel cell systems reported in table 4 are based on the already discussed current and expected performance of the technology, as indicated here below:

- First case (1): 60% and 25% LHV electrical and thermal efficiency (respectively) for the current performance of commercialised micro-CHP SOFC systems. It is noteworthy that these performances have been stated by the OEM [166] but have been verified in laboratory investigations [54, 167] and, at least for the electrical efficiency, in field-test monitoring studies [166].
- Second case (2): 75% of expected LHV electrical efficiency for the SOFC technology seems realistic, as inferred in the previous section. It has however been assumed that this increased electrical efficiency would result in a five-percentage-point reduction in the thermal efficiency, thus maintaining the total LHV efficiency at a realistic level as well of 95%.
- Third case (3): same SOFC as in the second case but entirely fed by biogas (with an assumed emission factor of zero). The remaining heat demand of the dwelling is also assumed to be provided with 'green energy' (with an assumed emission factor of zero).
- Fourth case (4): similar assumptions as in the third case, with a SOFC exhibiting slightly increased performance. In this instance, the SOFC is however fed with solid biomass, i.e. dry biochar such as pinewood biochar (also with an assumed emission factor of zero). It would therefore be a DC-SOFC which, as previously discussed, produces a highly pure CO<sub>2</sub> stream at the anode exhaust, thereby enabling the capability of CO<sub>2</sub> capture (and negative emissions). It should however be mentioned that the maturity of DC-SOFC is currently insufficient [43] to expect the introduction of such systems within the short time-frame required for the energy transition [3]. Nevertheless, its potential for negative emissions may still prove beneficial in the future, regardless of the timing of the emergence of the technology, as it will be demonstrated subsequently in this section. Although the theoretical DC LHV efficiency of the electrochemical oxidation of solid carbon is close to 100% [118], 80% LHV electrical efficiency for real DC-SOFC micro-CHP systems seems to be a more realistic efficiency figure, which is also often considered in the reviewed literature [168]. It has again been assumed that this increased electrical efficiency (in comparison to the third case) would result in a further reduction of the thermal efficiency by five percentage points, in order to maintain the total LHV efficiency at a realistic level of 95%.

Thus, compared to average grid electricity, table 4 demonstrates that the impact of fuel cells fed by natural gas (or other fossil fuels) is detrimental when compared to the 'base scenario', as evidenced by the negative savings reported in table 4. Even when a comparison is made with the electrical production of CCGTs with a high emission factor of 456 gCO<sub>2eq</sub> kWh<sub>el</sub><sup>-1</sup> (marginal emissions), and when highly efficient future natural gas flexible SOFCs are taken into account (second case), table 4 only indicates small carbon footprint savings in comparison with the 'base scenario' (positive savings reported in table 4). In view of the desirable reduction in the use of CCGTs, this once again emphasises the importance of flexible electrical production for future fuel cell micro-CHP systems (at least if they are not fed with CO<sub>2</sub> neutral fuels). Fortunately, this is already being achieved to a certain extent with some micro-CHP SOFC systems that are currently available on the market [166].

It is in fact only the introduction of 100% biogas (or other CO<sub>2</sub> neutral fuels), as considered in the third case, that exhibits a substantial decarbonisation potential. Indeed, as previously stated, the implementation of any (SOFC) micro-CHP systems, regardless of their efficiency (as in the first and second cases), results in a relatively insignificant or even negative CO<sub>2</sub> impact.


It is noteworthy that the carbon footprint savings reported in table 4 are established in comparison to the reference 'base scenario', considering current values of natural gas and electricity emissions factors. They have not been established in comparison to future potential reference scenarios involving greener grid gas and greener grid electricity. The objective is to evaluate the potential carbon footprint savings in comparison

**Table 4.** Yearly carbon footprint calculations of several SOFC micro-CHP systems energy use corresponding to an average Belgian dwelling of 17 000 kWh and 3500 kWh<sub>el</sub> of gas and electricity consumption.

Data	Best 'current SOFC', 60% LHV electrical efficiency, 25% LHV thermal efficiency (1) <sup>a</sup>	Best 'future SOFC', 75% LHV electrical efficiency, 20% LHV thermal efficiency (2) <sup>a</sup>	Best 'future SOFC', 75% LHV electrical efficiency, 20% LHV thermal efficiency, 100% biogas (3) <sup>a</sup>	Best 'future DC- SOFC', 80% LHV electrical efficiency, 15% LHV thermal efficiency, 100% biochar with CO <sub>2</sub> capture (4) <sup>a</sup>
Fuel cell electrical production (kWh <sub>el</sub> yr <sup>-1</sup> )	3500	3500	3500	3500
Gas consumption related to the fuel cell electrical production (kWh yr <sup>-1</sup> )	5833	4667	4667	0
Fuel cell heat production (kWh <sub>th</sub> yr <sup>-1</sup> )	1458	933	933	656
Remaining heat demand, supposedly provided by a 90% LHV efficient gas boiler (kWh <sub>th</sub> yr <sup>-1</sup> )	13 842	14 367	14 367	14 644
Total (fossil fuel) gas consumption, fuel cell, and gas boiler (kWh yr <sup>-1</sup> )	21 213	20 630	0	0
Carbon footprint related to the (fossil fuel) gas consumption— Dataset 'A' (tCO <sub>2eq</sub> yr <sup>-1</sup> )— marginal emissions	5.32	5.18	0.00	0.00
Carbon footprint related to the (fossil fuel) gas consumption— Dataset 'E1' (tCO <sub>2eq</sub> yr <sup>-1</sup> )	5.39	5.24	0.00	0.00
Negative carbon footprint from CO <sub>2</sub> capture at the anode exhaust <sup>b</sup>	N/A	N/A	N/A	1.76
Carbon footprint savings—Dataset 'A' (tCO <sub>2eq</sub> yr <sup>-1</sup> )— marginal emissions	0.54	0.68	5.86	7.63
Carbon footprint savings—Dataset 'E1' (tCO <sub>2eq</sub> yr <sup>-1</sup> )	-0.49	-0.34	4.90	6.67

<sup>a</sup> The different cases are based on the current and expected/hoped performance of fuel cell micro-CHPs. Those calculations are related to an average dwelling and are not expressed as 'per capita'. All fuel cells are assumed to be fully flexible to meet the dwelling's electrical demand.

<sup>b</sup> With the carbon content intensity assumption equivalent to 403 gCO<sub>2</sub> kWh<sub>fuel</sub><sup>-1</sup> (resulting figures are expressed in the table in tCO<sub>2</sub> yr<sup>-1</sup> or tCO<sub>2eq</sub> yr<sup>-1</sup> in this case, as CO<sub>2</sub> can be assumed to be the only GHG released fuel cells [165]). This carbon content intensity has been calculated for dry pinewood biochar (HHV = LHV = 24.49 MJ kg<sup>-1</sup>, 59.86% of carbon content, DC-SOFC with 80% of electrical efficiency [168]). It is crucial to consider that detrimental positive GHG emissions related to biochar production (and transport) have been neglected for the sake of simplicity and to be consistent with a low-carbon economic future (where, for example, the GHG emissions of the transportation and energy sectors can be neglected and where biochar can grow without GHG-emitting fertiliser). If those detrimental emissions were to be considered, this would straightforwardly tend to reduce the negative emissions potential of the considered DC-SOFC reported in this table. Life cycle emissions of the fuel cell itself have also been neglected because of a lack of available data (construction, transport, disposal, etc).



to the existing situation, i.e. to the reference 'base scenario'. It should however be noted that if CO<sub>2</sub> neutral fuels were to be available in the future for SOFCs, it is likely that they will also be used in other space heating and/or electrical production appliances. For example, biogas can currently be readily employed in a gas condensing boiler (or even in a CCGT power plant). Consequently, the genuine decarbonisation potential of micro-CHP systems can in fact solely be attributed to negative emissions technologies, such as DC-SOFCs (as evidenced in the fourth case of table 4).

The carbon footprint savings due to the implementation of the ideal fuel cell micro-CHP systems in the average Belgian dwelling outlined in table 4 have been reproduced graphically in figure 7. This has been performed on the assumption that the dwelling in question is occupied by two adult individuals, as detailed in appendix B. Actually, in an average Belgian dwelling such as the one represented by the energy consumptions considered in this section, there might also be some children. However, it has been decided to report the established carbon footprint of the dwelling solely on its (two) adult occupants. The average Belgian individual carbon footprint being close to one of Wallonia, i.e. about 15.4 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita [20], as it is one of the three Belgian regions, those decarbonisation potentials have been represented over two Walloon individual carbon footprint pathways compatible with IPCC's +2 °C 'equity' carbon budget established in a previous study [3]. Indeed, it can be seen in both scenarios that the blue bars, corresponding to IPCC's remaining +2 °C 'equity' carbon budget, represent positive values in the year 2050. The GHG mitigation scenario illustrated on the left even never allows for the carbon budget to be exceeded (and reach negative values), as opposed to the right one. Only the decarbonisation potentials established from marginal emissions (and reported in table 4) have been considered (i.e. using dataset 'A' from table 3). Indeed, dataset 'D1' (in table 3) has not been used because there are no carbon footprint savings for natural gas-fed fuel cells when average grid electricity is considered (as exhibited in table 4). The 'O' dots correspond to the reference 'base scenario', i.e. the Belgian average dwelling energy uses carbon footprint given in table 3 (using the marginal emissions provided by dataset 'A'). All of the dots have been established by dividing the Belgian average dwelling energy uses carbon footprints (directly reported in or deduced from tables 3 and table 4) by the number of adult occupants in the dwelling (i.e. two in this case, as stated in appendix B), and added to the chosen example of carbon footprint without energy uses reported in figure 6. It can again be deduced that significant decarbonisation can only occur using CO<sub>2</sub> neutral energy vectors (dots '3'), irrespective of the employed heating and power generation systems (hence not exclusively in fuel cell CHPs). However, a significant decarbonisation potential of fuel cell systems still lies in technologies that exhibit a highly pure CO<sub>2</sub> stream at their exhaust and thereby facilitate CO<sub>2</sub> capture, such as DC-SOFCs (dots '4').

The initial carbon footprint of the reference 'base scenario' (dot 'O' in figure 7, i.e. about 13 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita) is actually lower than the current average individual carbon footprint in Belgium. As observable in figure 7, the individual carbon footprint of Wallonia (or by extension, that of Belgium) shall actually reach this value at least between 2025 and 2028, depending on the mitigation scenario, i.e. Figure 7(a) or figure 7(b). In other words, the assumptions set out in appendix B and implemented to the selected carbon footprint calculator (which produced figure 6), along with the energy use assumptions (per capita) related to the average Belgian dwelling (reported in the previous section) could actually be regarded as a few years ahead of the current average Belgian individual carbon footprint, in light of the proposed GHG mitigation pathways illustrated in figure 7.

## 4. Discussion

As evidenced in table 4, the DC-SOFC exhibits a negative CO<sub>2</sub> emissions potential of 1.76 tCO<sub>2eq</sub> yr<sup>-1</sup> for the considered current average Belgian dwelling. Although not insignificant, it may appear relatively modest in comparison to the current individual Belgian carbon footprint, which is estimated to be 15.2 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita for the year 2019 [21–24]. This is particularly the case, as illustrated in figure 7, when the savings are divided by the number of (adult) occupants in the dwelling, which is in this instance two. Furthermore, it would even be reduced if this study were to consider the detrimental positive GHG emissions related to the fuel production (and transport), i.e. biochar in the case of the considered DC-SOFC, in addition to the negative emissions potential enabled by the pure CO<sub>2</sub> stream at the fuel cell exhaust. Indeed, these emissions were excluded in order to align with the assumption of a low-carbon economic future, as documented in table 4. It is noteworthy that, as previously stated, the life cycle emissions of the fuel cell itself have also been excluded due to a lack of available data (construction, transportation, disposal, *etc*), which would further reduce this negative emissions potential.

Nevertheless, it has already been mentioned that the electrification of mobility (and of other areas of usage) is likely to result in an increase in the average electricity demand of the average dwelling. Therefore, the electrical demand (to the DC-SOFC reported by the fourth case of table 4) will likely greatly exceed the 3500 kWh<sub>el</sub> considered here, thus increasing the potential for negative emissions. To illustrate, a 20 kWh<sub>el</sub>/100 km electric vehicle with 20 000 km annual mileage would necessitate an additional fuel cell demand of 4000 kWh<sub>el</sub>. In addition to the initial domestic demand of 3500 kWh<sub>el</sub>, this would result in an annual electric demand of 7500 kWh<sub>el</sub> to the fuel cell. Considering the DC-SOFC of the fourth case of table 4 (with 80% of LHV electrical efficiency), negative emissions could reach values slightly lower than 4 tCO<sub>2</sub> yr<sup>-1</sup> for the dwelling (i.e. about 3.8 tCO<sub>2</sub> yr<sup>-1</sup>). This equates to approximately 2 tCO<sub>2</sub> yr<sup>-1</sup> per capita when considering the number of adult occupants in the household. Alternatively, when the current average fertility rate in Europe of 1.6 [169] is also considered (which increases the considered number of occupants of the dwelling to 3.6), the figure rises slightly above than 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita. Actually, in recent studies for developed countries [170], the annual distance travelled with a passenger car is commonly assumed to be 16 000 km (in contrast to the 20 000 km considered here). However, this has a negligible impact on the results as, when the 1.6 current average fertility rate in Europe [169] is considered (i.e. 3.6 occupants in the dwelling), the negative CO<sub>2</sub> emissions potential of the DC-SOFC micro-CHP is only reduced to a value slightly below 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita.

This approach can be intensively criticised on the grounds that it suggests that the greater electrical consumption of the dwelling, the greater the negative emission potential of the DC-SOFC associated with it. While this has indeed been demonstrated mathematically, it runs dangerously counter to the ‘energy sobriety principle’, sometimes known as ‘enoughness’ or ‘frugality’, but better known as ‘sufficiency’ [171], as introduced in the IPCC’s AR6 in 2022 [172]. Whatever the semantics, sufficiency<sup>1</sup> should always be the primary and necessary consideration in the energy transition [172–174]. In addition, it seems highly unlikely that a significant deployment of DC-SOFCs without sufficient measures to promote sufficiency/sobriety would be without considerable risks. For instance, critical concerns could indeed be linked to tensions around material or biomass availability or to various environmental issues (such as unexpected pollution levels and/or harmful impacts on biodiversity), which could exert pressure on the defined limits of planetary boundaries [175].

Nevertheless, the potential negative emissions allowed by the electricity production from biomass-fed DC-SOFCs is substantial and can still easily be higher than the recommended 2050 individual carbon footprint (reduced from current levels considering the sufficiency/sobriety principle as the first mitigation step). As previously discussed, this 2050 target is estimated around 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita, based on the already discussed unmitigable GHG emissions reported by the IPCC [1] and the projected global population [14]. In fact, the achievement of full climate neutrality implies that (natural or technological) carbon absorption will also reach this 1 tCO<sub>2eq</sub> yr<sup>-1</sup> per capita target by 2050. Fortunately, it has just been shown in this work that the potential for CO<sub>2</sub> (technical) sequestration at the anode exhaust of biomass-fuelled DC-SOFC micro-CHPs in residential applications could readily lie in this order of magnitude.

<sup>1</sup> The French advocacy group *négaWatt*, which specialises in modelling energy transition scenarios, has identified four types of sufficiency [179]: structural, dimensional, usage and collaborative. Structural sufficiency focuses on organizing spaces and activities to reduce consumption, such as minimizing travel distances. Dimensional sufficiency ensures that equipment and facilities are scaled to their actual use, like using appropriately sized vehicles. Usage sufficiency emphasizes efficient use of resources, such as lowering space heating temperature setpoints or extending equipment lifespans, while collaborative sufficiency promotes sharing resources, like carpooling or shared workspaces [180, 181].

Actually, technical negative emissions technologies, exemplified by DC-SOFCs, will assume a pivotal role in the future if the natural territorial absorption levels are unable to be sufficiently increased. Indeed, as previously discussed, attaining such a level of carbon absorption with natural sinks alone will prove to be a significant challenge [176], especially for densely populated regions. According to a recent study [3], a minimum increase of +300% in carbon sinks would be necessary for regions/nations like Belgium and France compared to their current levels.

It is important to note that these potential negative emissions would be additive to the trivial benefits obtained from the avoided fossil fuels permitted by electrification of societal uses. For instance, in the aforementioned case of an annual mileage of 20 000 km (with a petrol car with a fuel consumption 6.0 l/100 km and an emissions rate of 144 gCO<sub>2</sub> km<sup>-1</sup> [177]), the avoided fossil fuel use represents a significant step towards GHG mitigation, amounting to approximately 2.88 tCO<sub>2</sub> yr<sup>-1</sup>.

It is noteworthy that the negative CO<sub>2</sub> emissions potential reported in table 4 for the DC-SOFC will remain unaffected by any reduction in space heating demand of the average dwelling. Indeed, this negative emissions potential (associated with the fourth case of table 4) represents an additional contribution to the carbon footprint savings that have already been included with the utilisation of 100% of 'green' energy vectors (included in the third case of table 4). In fact, a transition of the reference space heating system from gas condensing boilers (as in the 'base scenario') to heat pumps (for the thermal demand not covered by the fuel cell micro-CHP) would even result in an increase in the electrical demand to the DC-SOFC, thereby also increasing its negative CO<sub>2</sub> emissions potential. It thus follows that the results of this study are not only confined to the current average (Belgian) dwelling, with an annual gas consumption of 17 000 kWh, as depicted in this work.

Regarding the limitations of this study, it is pertinent to reiterate that the electrical transportation and distribution losses (which can reach approximately 6%–7% in the European Union [159]) that are avoided through decentralised electrical production from micro-CHP systems have not been considered in this work. It can thus be surmised that this will serve to enhance the decarbonisation potential outlined in table 4 or discussed in this section. However, this effect can be assumed to be compensated by the fact that the negative emission potentials estimated in this work have been calculated without consideration of the entire life cycle of the fuel cells themselves. Indeed, only the negative emissions associated with the utilisation phase of the system have been taken into account (in contrast to, for example, the emissions generated during its construction, transportation, disposal, *etc.*). In addition, this work has not considered the detrimental positive GHG emissions associated with the production and transportation of the fuel, in this case biochar (supposedly grown without GHG-emitting fertiliser). Ultimately, these deliberate omissions, which may slightly overestimate the reported negative emissions potential of the fuel cell, are likely to be consistent with the goals of a future low carbon economy in which these very negative emissions fuel cells could play a fundamental role, as demonstrated in this work.

In fact, the main limitations of this study lie in the uninvestigated barriers to the commercialisation of DC-SOFC systems that enable carbon capture at their anode outlet (such as cost or technological readiness) and in the fact that the DC-SOFC considered in this work was assumed to be fully flexible, which has yet to be demonstrated for CHP applications (although this is already partially the case for commercialised SOFCs [166]).

Although decarbonisation potentials have not been established for systems other than (DC-)SOFCs (because they have been reported in this study as the most promising micro-CHP fuel cell technologies), the methodology used in table 4 is simple enough to be very easily reproduced for PEMFCs or DFAFCs systems (or for any flexible CHP technology, as long as its LHV electrical and thermal efficiencies are known).

## 5. Conclusions

From table 2 it can be concluded that the main advantages of SOFC-based technologies for the decarbonisation of the residential heat and power sector lie in their high electrical efficiencies, high quality heat and simple water management. In addition, their high tolerance to impurities, their high fuel flexibility, the possibility of internal reforming that they offer, and their relatively simple composition of the off-anodes gasses, allow the use of carbon-neutral energy vectors, such as biogas, syngas, ammonia, alcohols, which can be considered as promising alternatives because they could be convenient to produce, store and/or transport. Furthermore, this paper has presented in figure 7 and analysed in table 4 the decarbonisation potential of biomass-fuelled DC-SOFCs, which even allow negative CO<sub>2</sub> emissions thanks to the CO<sub>2</sub> purity of the off-anode gasses. Conversely, the slow start-up and low power densities shown in table 2 are disadvantages of SOFC technologies, which are more specific to mobile applications than to stationary applications (such as CHP). Nevertheless, their cost and durability are still ongoing challenges (as mentioned again in table 2).

This study has shown that the GHG mitigation benefits of natural gas-fed fuel cell micro-CHPs compared to the overall average individual carbon footprint for an average Belgian dwelling are at best rather limited, even for 'ideal' future flexible systems with high efficiencies. In fact, this work has identified carbon footprint savings of only about  $0.5 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$  for an average dwelling with such a fuel cell system. This should be compared to the current Belgian average individual carbon footprint, which is much higher, i.e. about  $15.4 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$ . These savings only occur when compared to current marginal electricity emissions (with a rather high emission factor of  $456 \text{ tCO}_{2\text{eq}} \text{ kWh}_{\text{el}}^{-1}$ , corresponding to CCGT power plant production). Although this marginal emission factor assumption was valid for the whole of 2020 and 2021 in Belgium, as shown by data from Electricity Maps, it is likely to be reduced at some point in the future as the use of natural gas-fired CCGT on the grid is reduced (for the sake of the energy transition). This would further reduce the already small carbon footprint savings potential of natural gas-fed residential fuel cells (or, by extension, of other natural gas-fed CHPs).

In addition, this work has shown that even 'ideal' fuel cell micro-CHPs (when powered by natural gas or other fossil fuels) cannot compete environmentally with current grid electricity. Furthermore, it should be considered that this average grid electricity should become even greener every day with the energy transition.

It is therefore essential to implement other GHG mitigation measures. For example, 100% biogas (and/or other climate neutral energy vectors), with the potential help of increased insulation levels, would increase the carbon footprint savings to about  $5 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$  for the average Belgian dwelling, i.e. 10 times higher than those allowed by the implementation of the natural gas fed 'ideal' SOFC micro-CHPs reported in this work.

The electrification of personal vehicles also has significant potential, estimated at  $2.88 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$  for the selected case study, which is represented by a 20 000 km annual mileage driven by a 6.0 l/100 km petrol car (savings permitted by the reduction of fossil fuel use). Nevertheless, this will still not be sufficient, and (non-technological) behavioural changes are imperative. For instance, as illustrated in the carbon footprint example of figure 6, dietary habits and savings accounts also have a considerable impact that must be mitigated (representing a total of approximately  $2.7 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$  per capita GHG emissions).

However, certain fuel cell CHP technologies are capable of facilitating the capture of  $\text{CO}_2$  at their anode exhaust. Indeed, pure  $\text{CO}_2$  is the sole fuel cell reaction product at the anode of DFAFCs (fed by formic acid, preferably  $\text{CO}_2$ -neutral and sustainable, i.e. as electrofuel and/or derived from biomass). Pure  $\text{CO}_2$  is also the sole fuel cell reaction product at the anode of the more efficient DC-SOFCs (fed by solid carbon, preferably biomass). Consequently, negative emissions potentials have been investigated in this work with the example of an efficient future (flexible) DC-SOFC micro-CHP sized based upon the electric demand of the average Belgian dwelling.

Actually, when the DC-SOFC is oversized to also accommodate expected electrification future needs, such as personal vehicle mobility (which will necessitate increased electrical production), it has been demonstrated that its associated negative emissions can easily reach approximately  $4 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$  for the average Belgian dwelling (including a single electric vehicle with an annual mileage of 20 000 km). This corresponds to slightly more than  $1 \text{ tCO}_{2\text{eq}} \text{ yr}^{-1}$  per capita for the considered dwelling (assuming two adult occupants and the current European average fertility rate of 1.6). This exact level of negative emissions per capita in fact represents the minimum required to achieve climate neutrality, as deduced from the unavoidable GHG emissions reported by the IPCC and the projected global population.

Even if the preferred option is to rely on natural sinks rather than unproven technological solutions, exceeding the carbon budget recommended by the IPCC is an unacceptable risk. Consequently, in light of the significant negative emissions potential highlighted in this study, it is strategically imperative for climate policies to consider investments in DC-SOFC technologies, recognising their potentially substantial role in achieving climate neutrality through the facilitated pure (technical)  $\text{CO}_2$  capture at their anode exhaust.

## Data availability statement

All data that support the findings of this study are included within the article.

## Acknowledgment

The author would first like to thank Valéry Broun, Director of the Industrial Engineering Higher Education Institution of the Province of Liège (HEPL), for accommodating the class schedules to allow room for such research activities. The author also extends their gratitude to the entire HEPL institution for its continuous support.

## Funding

This study did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

## Appendix A

A non-exhaustive list of well-known individual carbon footprint calculators has been reported for information and potential comparison purposes here below. All referenced links were last accessed on 12 November 2024, at 16:00 CET.

1. <https://calculeurs.awac.be/>—Used in this study.
2. <https://nosgestesclimat.fr/>
3. [www.goodplanet.org/fr/calculeurs-carbone/particulier/](http://www.goodplanet.org/fr/calculeurs-carbone/particulier/)
4. [www.rtf.be/article/mobilite-energie-conso-a-combien-selevent-vos-emissions-de-co2-faites-le-test-avec-notre-calculateur-11074811](http://www.rtf.be/article/mobilite-energie-conso-a-combien-selevent-vos-emissions-de-co2-faites-le-test-avec-notre-calculateur-11074811)
5. <https://footprint.wwf.org.uk/> (for UK) or [www.wwf.ch/fr/vie-durable/calculateur-d-empreinte-ecologique](http://www.wwf.ch/fr/vie-durable/calculateur-d-empreinte-ecologique) (for Switzerland)
6. [www.footprintcalculator.org/home/en](http://www.footprintcalculator.org/home/en)
7. <https://coolclimate.berkeley.edu/calculator>
8. <https://climate.selectra.com/fr/empreinte-carbone/calculer>
9. <https://neoenea.be/calculateur-simplifie/>
10. <https://etat.emfro.lu/s3/myimpact>
11. [www.mijnverborgenimpact.nl/en/](http://www.mijnverborgenimpact.nl/en/)
12. <https://knowsdgs.jrc.ec.europa.eu/cfc> (also evaluates impacts against the planetary boundaries and SDGs 3, 6 12, 13, 14 and 15 [178])

## Appendix B

The main assumptions reported to the chosen carbon calculator footprint [147] here below. Those case-dependent assumptions have been reported for the reproducibility of the study and to provide examples of the level of detail involved in the chosen carbon footprint calculator.

- Detached house of 200 m<sup>2</sup>, 2 adults (children not considered)
- About 2.5 average garbage bags a week, including papers and cardboard, not including organic trash
- Organic trash thrown in an individual compost
- One small petrol car, bought second handed in 2020 and supposedly used until 2030
  - 8000 km yr<sup>-1</sup> for professional activities
  - 6000 km yr<sup>-1</sup> for personal activities
- Distance travelled by plane:
  - 7000 km for professional activities
  - 7000 km for personal vacation
- 14 meals week<sup>-1</sup> (breakfasts not included): 2 red meat-based meals, 3 white meat-based meals, 1 fish-based meal, 5 vegetarian meals, 3 bread-based meat (with cheese)
- 10 drinks week<sup>-1</sup> (that are not tap water)
- Groceries not specifically local but exhibiting bio labels, not frozen, packed (not bulk food), not specifically aligned with the seasons
- The dwelling possesses 2 computers, 2 smartphones (second-handed, changed every 24 months), 2 TVs, 1 fridge, 1 freezer, 1 dishwasher, 1 dryer, 1 washing machine
- 20 h of High-Definition streaming/week
- 5 pieces of new clothes/year
- 1000 € on a generic savings account

All those assumptions and the carbon footprint calculations are related to the year 2023.

## ORCID iD

Nicolas Paulus  <https://orcid.org/0000-0003-2081-3810>

## References

- [1] IPCC WGIII 2022 Summary for Policymakers *Climate Change 2022 - Mitigation of Climate Change* (Cambridge University Press) (<https://doi.org/10.1017/9781009157926.001>)
- [2] Gignac R and Matthews H D 2015 Allocating a 2 °C cumulative carbon budget to countries *Environ. Res. Lett.* **10** 075004
- [3] Paulus N 2024 Developing individual carbon footprint reduction pathways from carbon budgets: examples with Wallonia and France *Renew. Sustain. Energy Rev.* **198** 114428
- [4] Raupach M R, Davis S J, Peters G P, Andrew R M, Canadell J G, Ciais P, Friedlingstein P, Jotzo F, van Vuuren D P and le Quéré C 2014 Sharing a quota on cumulative carbon emissions *Nat. Clim. Change* **4** 873–9
- [5] Dooley K *et al* 2021 Ethical choices behind quantifications of fair contributions under the Paris Agreement *Nat. Clim. Change* **11** 300–5
- [6] van der Ploeg F 2018 The safe carbon budget *Clim. Change* **147** 47–59
- [7] Paulus N 2023 Confronting nationally determined contributions (NDCs) to IPCC's +2 °C carbon budgets through the analyses of France and Wallonia climate policies *J. Ecol. Eng.* **24** 214–25
- [8] Fawcett T, Hvelplund F and Meyer N I 2010 Making it personal: per capita carbon allowances *Generating Electricity in a Carbon-Constrained World* (Elsevier) pp 87–107
- [9] Auger C, Hilloulin B, Boisserie B, Thomas M, Guignard Q and Rozière E 2021 Open-source carbon footprint estimator: development and University declination *Sustainability* **13** 4315
- [10] Maris G and Flouros F 2021 The green deal, national energy and climate plans in Europe: Member States' compliance and strategies *Adm. Sci.* **11** 75
- [11] Matthews H D, Zickfeld K, Dickau M, MacIsaac A J, Mathesius S, Nzotungicimpaye C-M and Luers A 2022 Temporary nature-based carbon removal can lower peak warming in a well-below 2 °C scenario *Commun. Earth Environ.* **3** 1–8
- [12] Batres M, Wang F M, Buck H, Kapila R, Kosar U, Licker R, Nagabhushan D, Rekhelman E and Suarez V 2021 Environmental and climate justice and technological carbon removal *Electr. J.* **34** 107002
- [13] Lenzi D 2018 The ethics of negative emissions *Glob. Sustain.* **1** 1–8
- [14] Turbat V, Gribble R and Zeng W 2022 Population, burden of disease, and health services *International Handbook of Population Policies* (Springer) pp 59–77
- [15] Zhang S, Kaikun W, Yastrubskiy M and Huang C 2023 Carbon emissions from international trade and consumption: assessing the role of cumulative risk for EU and Chinese economic development *Energy Strat. Rev.* **50** 101219
- [16] Lee J, Shigetomi Y and Kanemoto K 2023 Drivers of household carbon footprints across EU regions, from 2010 to 2015 *Environ. Res. Lett.* **18** 044043
- [17] Xing Z, Jiao Z and Wang H 2022 Carbon footprint and embodied carbon transfer at city level: a nested MRIO analysis of Central Plain urban agglomeration in China *Sustain. Cities Soc.* **83** 103977
- [18] Hertwich E G and Peters G P 2009 Carbon footprint of nations: a global, trade-linked analysis *Environ. Sci. Technol.* **43** 6414–20
- [19] Hambÿe C, Hertveldt B and Michel B 2018 Does consistency with detailed national data matter for calculating carbon footprints with global multi-regional input–output tables? A comparative analysis for Belgium based on a structural decomposition *J. Econ. Struct.* **7** 11
- [20] Towa E, Zeller V, Merciai S, Schmidt J and Achten W M J 2022 Toward the development of subnational hybrid input–output tables in a multiregional framework *J. Ind. Ecol.* **26** 88–106
- [21] The Shift Project 2024 *Emissions Per Capita* (available at: <https://sankey.theshiftproject.org/>) (Accessed 2 December 2024)
- [22] Södersten C-J H, Wood R and Hertwich E G 2018 Endogenizing capital in MRIO models: the implications for consumption-based accounting *Environ. Sci. Technol.* **52** 13250–9
- [23] Stadler K *et al* 2018 EXIOBASE 3: developing a time series of detailed environmentally extended multi-regional input-output tables *J. Ind. Ecol.* **22** 502–15
- [24] Andrieu B, Le Boulzec H, Delannoy L, Verzier F, Winter G, Vidal O and Stadler K 2024 An open-access web application to visualise countries' and regions' carbon footprints using Sankey diagrams *Commun. Earth Environ.* **5** 236
- [25] Brett D J L, Brandon N P, Hawkes A D and Staffell I 2011 Fuel cell systems for small and micro combined heat and power (CHP) applications *Small and Micro Combined Heat and Power (CHP) Systems* (Elsevier) pp 233–61
- [26] Dodds P E, Staffell I, Hawkes A D, Li F, Grünewald P, McDowall W and Ekins P 2015 Hydrogen and fuel cell technologies for heating: a review *Int. J. Hydrog. Energy* **40** 2065–83
- [27] Cigolotti V, Genovese M and Fragiaco P 2021 Comprehensive review on fuel cell technology for stationary applications as sustainable and efficient poly-generation energy systems *Energies* **14** 4963
- [28] Stangarone T 2021 South Korean efforts to transition to a hydrogen economy *Clean. Technol. Environ. Policy* **23** 509–16
- [29] Intralink 2021 *The Hydrogen Economy South Korea Market Intelligence Report* (available at: <https://www.intralinkgroup.com/Syndication/media/Syndication/Reports/Korean-hydrogen-economy-market-intelligence-report-January-2021.pdf>)
- [30] Park C 2020 Green hydrogen economy roadmap: a Korean perspective *Proc. 37th European Photovoltaic Solar Energy Conf. and Exhibition (EU PVSEC 2020)* (available at: [https://iea-pvps.org/wp-content/uploads/2020/09/5.Green-Hydrogen-Economy-Roadmap\\_CPark\\_Final.pdf](https://iea-pvps.org/wp-content/uploads/2020/09/5.Green-Hydrogen-Economy-Roadmap_CPark_Final.pdf))
- [31] Nazir H *et al* 2020 Is the H2 economy realizable in the foreseeable future? Part III: H2 usage technologies, applications, and challenges and opportunities *Int. J. Hydrog. Energy* **45** 28217–39
- [32] Bozorgmehri S, Heidary H and Salimi M 2023 Market diffusion strategies for the PEM fuel cell-based micro-CHP systems in the residential sector: scenario analysis *Int. J. Hydrog. Energy* **48** 3287–98
- [33] Code 2 - Cogeneration Observatory and Dissemination Europe 2014 *Micro-CHP Potential Analysis European Level Report* (available at: <https://www.pace-energy.eu/wp-content/uploads/2017/06/The-European-micro-CHP-Roadmap-from-CODE2-project.pdf>)
- [34] Aguilo-Rullan A 2017 EU policy & micro-CHP *Journée Micro-Mini Cogénérations* (available at: <https://atee.fr/system/files/2020-01/7.%20Antonio%20Aguilo%20Rullan%20Commission%20europ%C3%A9enne.pdf>)
- [35] Abdulla A, Hanna R, Schell K R, Babacan O and Victor D G 2021 Explaining successful and failed investments in U.S. carbon capture and storage using empirical and expert assessments *Environ. Res. Lett.* **16** 014036
- [36] Waage J *et al* 2015 Governing the UN sustainable development goals: interactions, infrastructures, and institutions *Lancet Glob. Health* **3** e251–2
- [37] Ellamla H R, Staffell I, Bujlo P, Pollet B G and Pasupathi S 2015 Current status of fuel cell based combined heat and power systems for residential sector *J. Power Sources* **293** 312–28

- [38] Paulus N 2024 Comprehensive assessment of fuel cell types: a novel fuel cell classification system *Renewable Energy (Under Review)*
- [39] Mahapatra M K and Singh P 2014 Fuel cells: energy conversion technology *Future Energy: Improved, Sustainable and Clean Options for Our Planet* (Elsevier) pp 511–47
- [40] Hamouda R A and El-Naggar N E A 2021 Cyanobacteria-based microbial cell factories for production of industrial products *Microbial Cell Factories Engineering for Production of Biomolecules* (Academic) ch 14, pp 277–302
- [41] Leech D, Kavanagh P and Schuhmann W 2012 Enzymatic fuel cells: recent progress *Electrochim. Acta* **84** 223–34
- [42] Karim N A and Kamarudin S K 2021 Introduction to direct alcohol fuel cells (DAFCs) *Direct Liquid Fuel Cells* (Elsevier) pp 49–70
- [43] Sharaf O Z and Orhan M F 2014 An overview of fuel cell technology: fundamentals and applications *Renew. Sustain. Energy Rev.* **32** 810–53
- [44] Dincer I and Zamfirescu C 2014 Hydrogen and fuel cell systems *Advanced Power Generation Systems* (Elsevier) pp 143–98
- [45] Tawalbeh M, Murtaza S Z M, Al-Othman A, Alami A H, Singh K and Olabi A G 2022 Ammonia: a versatile candidate for the use in energy storage systems *Renew. Energy* **194** 955–77
- [46] Demin A 2002 Thermodynamic analysis of a methane fed SOFC system based on a protonic conductor *Solid State Ion.* **152–153** 555–60
- [47] Liu F and Duan C 2021 Direct-hydrocarbon proton-conducting solid oxide fuel cells *Sustainability* **13** 4736
- [48] Sumi H, Shimada H, Yamaguchi Y, Mizutani Y, Okuyama Y and Amezawa K 2021 Comparison of electrochemical impedance spectra for electrolyte-supported solid oxide fuel cells (SOFCs) and protonic ceramic fuel cells (PCFCs) *Sci. Rep.* **11** 10622
- [49] Basbus J, Arce M, Troiani H, Su Q, Wang H, Caneiro A and Mogni L 2020 Study of  $\text{BaCe}_{0.4}\text{Zr}_{0.4}\text{Y}_{0.2}\text{O}_{3-\delta}/\text{BaCe}_{0.8}\text{Pr}_{0.2}\text{O}_{3-\delta}$  (BCZY/BCP) bilayer membrane for protonic conductor solid oxide fuel cells (PC-SOFC) *Int. J. Hydrog. Energy* **45** 5481–90
- [50] Shi H, Su C, Ran R, Cao J and Shao Z 2020 Electrolyte materials for intermediate-temperature solid oxide fuel cells *Prog. Nat. Sci., Mater. Int.* **30** 764–74
- [51] Rashid N L R M, Samat A A, Jais A A, Somalu M R, Muchtar A, Baharuddin N A and Wan Isahak W N R 2019 Review on zirconate-cerate-based electrolytes for proton-conducting solid oxide fuel cell *Ceram. Int.* **45** 6605–15
- [52] Dong Y, Xing L, Li X, Gao Y, Cao Z and Liu J 2022 A membrane-less molten hydroxide direct carbon fuel cell with fuel continuously supplied at low temperatures: a modeling and experimental study *Appl. Energy* **324** 119585
- [53] Hawkes A, Staffell I, Brett D and Brandon N 2009 Fuel cells for micro-combined heat and power generation *Energy Environ. Sci.* **2** 729
- [54] Paulus N and Lemort V 2023 Experimental investigation of a solid oxide fuel cell (SOFC) used in residential cogeneration applications *Proc. 36th Int. Conf. on Efficiency, Cost, Optimization, Simulation and Environmental Impact of Energy Systems (ECOS2023)* (<https://doi.org/10.52202/069564-0056>)
- [55] Paulus N and Lemort V 2023 Field-test performance models of a residential micro-cogeneration system based on the hybridization of a proton exchange membrane fuel cell and a gas condensing boiler *Energy Convers. Manage.* **295** 117634
- [56] Paulus N and Lemort V 2022 Grid-impact factors of field-tested residential proton exchange membrane fuel cell systems *Proc. 14th REHVA HVAC World Congress (CLIMA2022)* (<https://doi.org/10.34641/CLIMA.2022.176>)
- [57] Staffell I, Brett D J L, Brandon N P and Hawkes A D 2015 Fuel cell micro-CHP *Domestic Microgeneration* (Routledge) pp 219–51
- [58] Schuh S, Dragosits S, Seidl C and Grimm S 2021 Brennstoffzellen für den Endkundenbereich *Int. Energiewirtschaftstagung an der TU-Wien (IEWT 2021)* (available at: [https://iewt2021.eeg.tuwien.ac.at/download/contribution/presentation/150/150\\_presentation\\_20210916\\_101356.pdf](https://iewt2021.eeg.tuwien.ac.at/download/contribution/presentation/150/150_presentation_20210916_101356.pdf))
- [59] Martinez S, Michaux G, Salagnac P and Bouvier J-L 2017 Micro-combined heat and power systems (micro-CHP) based on renewable energy sources *Energy Convers. Manage.* **154** 262–85
- [60] Jannelli E, Minutillo M and Perna A 2013 Analyzing microcogeneration systems based on LT-PEMFC and HT-PEMFC by energy balances *Appl. Energy* **108** 82–91
- [61] Hossain S, Abdalla A M, Jamain S N B, Zaini J H and Azad A K 2017 A review on proton conducting electrolytes for clean energy and intermediate temperature-solid oxide fuel cells *Renew. Sustain. Energy Rev.* **79** 750–64
- [62] Liu J, Jin Z, Miao L, Ding J, Tang H, Gong Z, Peng R and Liu W 2019 A novel anions and cations co-doped strategy for developing high-performance cobalt-free cathode for intermediate-temperature proton-conducting solid oxide fuel cells *Int. J. Hydrog. Energy* **44** 11079–87
- [63] Chen X, Zhang H, Li Y, Xing J, Zhang Z, Ding X, Zhang B, Zhou J and Wang S 2021 Fabrication and performance of anode-supported proton conducting solid oxide fuel cells based on  $\text{BaZr}_{0.1}\text{Ce}_{0.7}\text{Y}_{0.1}\text{Yb}_{0.1}\text{O}_{3-\delta}$  electrolyte by multi-layer aqueous-based co-tape casting *J. Power Sources* **506** 229922
- [64] Verhaert I, Mulder G and De Paepe M 2016 Evaluation of an alkaline fuel cell system as a micro-CHP *Energy Convers. Manage.* **126** 434–45
- [65] Ghouse M, Abaoud H and Al-Boeiz A 2000 Operational experience of a 1 kW PAFC stack *Appl. Energy* **65** 303–14
- [66] Staffell I and Green R 2013 The cost of domestic fuel cell micro-CHP systems *Int. J. Hydrog. Energy* **38** 1088–2
- [67] Staffell I and Ingram A 2010 Life cycle assessment of an alkaline fuel cell CHP system *Int. J. Hydrog. Energy* **35** 2491–505
- [68] Kazeroonian F K and Rahimpour M R 2023 Application of syngas in fuel cell *Advances in Synthesis Gas: Methods, Technologies and Applications* (Elsevier) pp 337–67
- [69] Huo S, Deng H, Chang Y and Jiao K 2012 Water management in alkaline anion exchange membrane fuel cell anode *Int. J. Hydrog. Energy* **37** 18389–402
- [70] Ferriday T B and Middleton P H 2021 Alkaline fuel cell technology—a review *Int. J. Hydrog. Energy* **46** 18489–510
- [71] Paulus N, Job N and Lemort V 2025 Investigation of degradation mechanisms and corresponding recovery procedures of a field-tested residential cogeneration Polymer Electrolyte Membrane fuel cell submitted
- [72] Sundén B 2019 Fuel Cell Types - overview *Hydrogen, Batteries and Fuel Cells* (Elsevier) pp 123–44
- [73] Arsalis A 2019 A comprehensive review of fuel cell-based micro-combined-heat-and-power systems *Renew. Sustain. Energy Rev.* **105** 391–414
- [74] Meyer Q, Yang C, Cheng Y and Zhao C 2023 Overcoming the electrode challenges of high-temperature proton exchange membrane fuel cells *Electrochem. Energy Rev.* **6** 16
- [75] Arsalis A 2024 Design, modeling, and optimization of a novel 6 kWe hybrid solid oxide fuel cell high temperature-proton exchange membrane fuel cell system *Clean. Energy Syst.* **8** 100113
- [76] Dicks A L, Fellows R G, Martin Mescal C and Seymour C 2000 A study of SOFC–PEM hybrid systems *J. Power Sources* **86** 501–6

- [77] Guo X, Guo Y, Wang J, Meng X, Deng B, Wu W and Zhao P 2023 Thermodynamic analysis of a novel combined heating and power system based on low temperature solid oxide fuel cell (LT-SOFC) and high temperature proton exchange membrane fuel cell (HT-PEMFC) *Energy* **284** 129227
- [78] Ruth M 2012 *1–10 kW Stationary Combined Heat and Power Systems Status and Technical Potential: Independent Review* NREL/BK-6A10-48265 U.S. Department of Energy Hydrogen and Fuel Cells Program (available at: <https://www.nrel.gov/docs/fy10osti/48265.pdf>)
- [79] Korsgaard A, Nielsen M and Kaer S 2008 Part one: a novel model of HTPeM-based micro-combined heat and power fuel cell system *Int. J. Hydrog. Energy* **33** 1909–20
- [80] Haider R, Wen Y, Ma Z-F, Wilkinson D P, Zhang L, Yuan X, Song S and Zhang J 2021 High temperature proton exchange membrane fuel cells: progress in advanced materials and key technologies *Chem. Soc. Rev.* **50** 1138–87
- [81] Paulus N and Lemort V 2024 Experimental investigation and modelling of a Solid Oxide Fuel Cell (SOFC) used in residential cogeneration applications *Entropy: Thermodynamics – Energy – Environment – Economy* vol 5
- [82] Dávila C, Paulus N and Lemort V 2022 Experimental investigation of a micro-CHP unit driven by natural gas for residential buildings *Proc. 19th Int. Refrigeration and Air Conditioning Conf. at Purdue (Herrick 2022)* (available at: <https://docs.lib.purdue.edu/cgi/viewcontent.cgi?article=3417&context=iracc>)
- [83] Pasdag O, Kvasnicka A, Steffen M and Heinzel A 2012 Highly integrated steam reforming fuel processor with condensing burner technology for maximised electrical efficiency of CHP-PEMFC systems *Energy Proc.* **28** 57–65
- [84] Di Marcobertardino G and Manzolini G 2017 Investigation of a 5 kW micro-CHP PEM fuel cell based system integrated with membrane reactor under diverse EU natural gas quality *Int. J. Hydrog. Energy* **42** 13988–4002
- [85] Syah R, Isola L A, Guerrero J W G, Suksatan W, Sunarsi D, Elveny M, Alkaim A F, Thangavelu L and Aravindhan S 2021 Optimal parameters estimation of the PEMFC using a balanced version of Water Strider Algorithm *Energy Rep.* **7** 6876–86
- [86] Ramakrishnan S, Ramya K and Rajalakshmi N 2022 High-temperature Proton Exchange Membrane—an insight *PEM Fuel Cells* (Elsevier) pp 223–42
- [87] Gallucci F, van Sint Annaland M, Roses L and Manzolini G 2015 Using palladium membrane-based fuel reformers for combined heat and power (CHP) plants *Palladium Membrane Technology for Hydrogen Production, Carbon Capture and Other Applications* (Elsevier) pp 319–44
- [88] Herdem M S, Sinaki M Y, Farhad S and Hamdullahpur F 2019 An overview of the methanol reforming process: comparison of fuels, catalysts, reformers, and systems *Int. J. Energy Res.* **43** 5076–105
- [89] Lehnert W, Lüke L and Samsun R C 2016 High temperature polymer electrolyte fuel cells *Fuel Cells: Data, Facts and Figures* (Wiley) pp 235–47
- [90] Molle M, Schmidt T J and Benicewicz B C 2013 Polybenzimidazole Fuel Cell Technology *Fuel Cells* (Springer) pp 391–431
- [91] McConnell V P 2009 High-temperature PEM fuel cells: hotter, simpler, cheaper *Fuel Cells Bull.* **2009** 12–16
- [92] Anon 2017 E.ON partners with efficiency to bring Elcore fuel cell systems to German residential market *Fuel Cells Bull.* **2017** 1
- [93] Schenk A, Gamper S, Grimmer C, Pichler B E, Bodner M, Weinberger S and Hacker V 2016 Development of low cost high-temperature polymer electrolyte fuel cell membrane-electrode-assemblies for combined heat and power plants in single family homes *ECS Trans.* **75** 435–41
- [94] Bednarek T, Davies J, Malkow T and Weidner E 2021 *Historical Analysis of FCH 2 JU Stationary Fuel Cell Projects* JRC125018 (<https://doi.org/10.2760/527879>)
- [95] Freudenberg Group 2020 *2019 Annual Report* (available at: [https://www.freudenberg.com/fileadmin/downloads/english/FreudenbergGroup\\_AnnualReport\\_2019.pdf](https://www.freudenberg.com/fileadmin/downloads/english/FreudenbergGroup_AnnualReport_2019.pdf))
- [96] HausEnergieForum 2019 *Etlische Elcore 2400 komplett ab 450€ aus Insolvenzmasse* (available at: <https://www.hausenergieforum.de/diskussion/thread/8843-etliche-elcore-2400-komplett-ab-450-aus-insolvenzmasse?pageNo=1>) (Accessed 2 January 2025)
- [97] Wei M, Smith S J and Sohn M D 2017 Experience curve development and cost reduction disaggregation for fuel cell markets in Japan and the US *Appl. Energy* **191** 346–57
- [98] Doosan 2018 *PureCell® Model 400* (available at: [https://www.doosanfuelcellpower.com/download/pdf/catalog/pafc-400kw\\_en.pdf](https://www.doosanfuelcellpower.com/download/pdf/catalog/pafc-400kw_en.pdf))
- [99] Jo A *et al* 2017 Modeling and analysis of a 5 kW HT-PEMFC system for residential heat and power generation *Int. J. Hydrog. Energy* **42** 1698–714
- [100] Petrecky J and Ashley C J 2014 *CHP Fuel Cell Durability Demonstration - Final Report* DE-EE0000480 Plug Power (<https://doi.org/10.2172/1160148>)
- [101] Pasupathi S, Calderon Gomez J C, Su H, Reddy H, Bujlo P and Sita C 2016 Stationary HT-PEMFC-based systems—combined heat and power generation *Recent Advances in High-Temperature PEM Fuel Cells* (Elsevier) pp 55–77
- [102] Cumalioglu I (Plug Power) 2009 GenSys blue: fuel cell heating appliance *Fuel Cell Seminar* (available at: <https://www.energy.gov/eere/fuelcells/articles/gensys-blue-fuel-cell-heating-appliance>)
- [103] Vogel J and Marcinkoski J (DOE Hydrogen Program) 2010 *Highly Efficient, 5 kW CHP Fuel Cells Demonstrating Durability and Economic Value in Residential and Light Commercial Applications* FY 2010 Annual Progress Report (available at: [https://www.hydrogen.energy.gov/docs/hydrogenprogramlibraries/pdfs/progress10/xi\\_3\\_vogel.pdf?sfvrsn=af8a665c\\_1](https://www.hydrogen.energy.gov/docs/hydrogenprogramlibraries/pdfs/progress10/xi_3_vogel.pdf?sfvrsn=af8a665c_1))
- [104] Elmer T, Worall M, Wu S and Riffat S B 2015 Fuel cell technology for domestic built environment applications: state-of-the-art review *Renew. Sustain. Energy Rev.* **42** 913–31
- [105] Serenergy 2010 *Fuel Cell Stack Module—Serenus 166/390 Air C* Datasheet v2.5–0210 (available at: <https://doi.org/10.5281/zenodo.14734145>)
- [106] De Castro E S, Kaye I, Chen R and Pavlik T 2022 Compact design of HT pefmc stacks with advanced cooling *ECS Meeting Abstracts* MA2022-02 p 1466
- [107] Araya S S, Zhou F, Liso V, Sahlin S L, Vang J R, Thomas S, Gao X, Jeppesen C and Kær S K 2016 A comprehensive review of PBI-based high temperature PEM fuel cells *Int. J. Hydrog. Energy* **41** 21310–44
- [108] Fuel Cells and Hydrogen 2 Joint Undertaking (FCH 2 JU) 2018 *Addendum to the Multi - Annual Work Plan 2014 - 2020* (available at: [https://www.clean-hydrogen.europa.eu/system/files/2018-06/MAWP%2520final%2520version\\_endorsed%2520GB%252015062018%2520%2528ID%25203712421%2529.pdf](https://www.clean-hydrogen.europa.eu/system/files/2018-06/MAWP%2520final%2520version_endorsed%2520GB%252015062018%2520%2528ID%25203712421%2529.pdf))
- [109] Cigolotti V and Genovese M Technology Collaboration Programme 2021 Stationary fuel cell applications—current and future technologies—cost, performances, and potential *Stationary fuel cell applications—current and future technologies - cost, performances, and potential* International Energy Agency (available at: [https://ieafuelcell.com/fileadmin/publications/2021/2021\\_AFCTCP\\_Stationary\\_Application\\_Performance.pdf](https://ieafuelcell.com/fileadmin/publications/2021/2021_AFCTCP_Stationary_Application_Performance.pdf))

- [110] International Energy Agency 2015 *Technology Roadmap Hydrogen and Fuel Cells* (available at: <https://iea.blob.core.windows.net/assets/e669e0b6-148c-4d5c-816b-a7661301fa96/TechnologyRoadmapHydrogenandFuelCells.pdf>)
- [111] Fan L, Tu Z and Chan S H 2021 Recent development of hydrogen and fuel cell technologies: a review *Energy Rep.* **7** 8421–46
- [112] Andersson M and Froitzheim J (Energiforsk) 2019 *Technology review - Solid Oxide Cells 2019* Swedish Electromobility Centre (available at: <https://energiforsk.se/media/26740/technology-review-solid-oxide-cells-2019-energiforskrapport-2019-601.pdf>)
- [113] Wachsmann E D, Marlowe C A and Lee K T 2012 Role of solid oxide fuel cells in a balanced energy strategy *Energy Environ. Sci.* **5** 5498–09
- [114] Bloom Energy 2023 *The Bloom Energy Server 5.5* (available at: <https://ncwpdr.org/wp-content/uploads/2023/03/bloom-energy-server-2023.pdf>)
- [115] Mendonça C, Ferreira A and Santos D M F 2021 Towards the commercialization of solid oxide fuel cells: recent advances in materials and integration strategies *Fuels* **2** 393–419
- [116] Liu J, Tang Q, Su Y, Li T, Wang Y and Zhu M 2021 Economic analysis of solid oxide fuel cell and its role in carbon peak, carbon neutralization process Proc. *4th Int. Conf. on Energy, Electrical and Power Engineering (CEEPE 2021)* pp 115–9
- [117] Boldrin P and Brandon N P 2019 Progress and outlook for solid oxide fuel cells for transportation applications *Nat. Catal.* **2** 571–7
- [118] Li X, Zhu Z, De Marco R, Bradley J and Dicks A 2010 Modification of coal as a fuel for the direct carbon fuel cell *J. Phys. Chem. A* **114** 3855–62
- [119] Stambouli A B and Traversa E 2002 Solid oxide fuel cells (SOFCs): a review of an environmentally clean and efficient source of energy *Renew. Sustain. Energy Rev.* **6** 433–55
- [120] Zeng Z, Qian Y, Zhang Y, Hao C, Dan D and Zhuge W 2020 A review of heat transfer and thermal management methods for temperature gradient reduction in solid oxide fuel cell (SOFC) stacks *Appl. Energy* **280** 115899
- [121] PACE—Pathway to a Competitive European Fuel Cell micro-CHP Market 2021 *D1.7—summary report on specifications for newest model deployment in PACE* Element Energy (available at: <https://pace-energy.eu/wp-content/uploads/2021/05/PACE-D1.7-2021-update-FV.pdf>)
- [122] Park J O and Hong S-G 2016 Design and optimization of HT-PEMFC MEAs *High Temperature Polymer Electrolyte Membrane Fuel Cells* (Springer International Publishing) pp 331–52
- [123] Perna A and Minutillo M 2020 Residential cogeneration and trigeneration with fuel cells *Current Trends and Future Developments on (Bio-) Membranes* (Elsevier) pp 197–239
- [124] Wen T 2002 Material research for planar SOFC stack *Solid State Ion.* **148** 513–9
- [125] Leah R T *et al* 2017 Development of high efficiency steel cell technology for multiple applications *ECS Trans.* **78** 2005–14
- [126] Weeber K, Horstmann P and Miersch J 2018 Changes in power generation and distribution and the role of SOFC Proc. *13th European SOFC & SOE Forum (EFCF 2018)*
- [127] Leah R T, Bone A, Selcuk A, Rahman M, Clare A, Lankin M, Felix F, Mukerjee S and Selby M 2019 Latest results and commercialization of the ceres power steelcell® technology platform *ECS Trans.* **91** 51–61
- [128] Noponen M, Göös J, Torri P, Chade D, Vähä-Piikkiö H and Hallanoro P 2016 Performance characteristics of elcogen solid oxide fuel cell stacks Proc. *12th European SOFC & SOE Forum (EFCF 2016)*
- [129] Beale S B, Andersson M, Boigues-Muñoz C, Frandsen H L, Lin Z, McPhail S J, Ni M, Sundén B, Weber A and Weber A Z 2021 Continuum scale modelling and complementary experimentation of solid oxide cells *Prog. Energy Combust. Sci.* **85** 100902
- [130] Bertoldi M, Bucheli O and Ravagni A V 2014 Development and manufacturing of SOFC-based products at SOFCpower SpA Proc. *11th European SOFC & SOE Forum (EFCF 2014)*
- [131] Halinen M, Rautanen M, Saarinen J, Pennanen J, Pohjoranta A, Kiviahio J, Pastula M, Nuttall B, Rankin C and Borglum B 2011 Performance of a 10 kW SOFC demonstration unit *ECS Trans.* **35** 113–20
- [132] Paulus N and Lemort V 2024 Experimental assessment of pollutant emissions from residential fuel cells and comparative benchmark analysis *J. Environ. Manage.* **359** 121017
- [133] Paulus N and Lemort V 2023 Establishing the energy content of natural gas residential consumption : example with Belgian field-test applications *IOP Conf. Ser.: Earth Environ. Sci.* **1185** 012013
- [134] Ma Z, Legrand U, Pahija E, Tavares J R and Boffito D C 2021 From CO<sub>2</sub> to Formic Acid Fuel Cells *Ind. Eng. Chem. Res.* **60** 803–15
- [135] Fernández-Caso K, Díaz-Sainz G, Alvarez-Guerra M and Irabien A 2023 Electroreduction of CO<sub>2</sub> : advances in the continuous production of formic acid and formate *ACS Energy Lett.* **8** 1992–2024
- [136] Sundén B 2019 *Hydrogen, Batteries and Fuel Cells* (Elsevier) pp 37–55
- [137] Dziejarski B, Krzyżyńska R and Andersson K 2023 Current status of carbon capture, utilization, and storage technologies in the global economy: a survey of technical assessment *Fuel* **342** 127776
- [138] Chen X, Liu Y and Wu J 2020 Sustainable production of formic acid from biomass and carbon dioxide *Mol. Catal.* **483** 110716
- [139] Ju H, Eom J, Lee J K, Choi H, Lee S, Song R-H and Lee J 2013 The activity of ash-free coal in direct carbon fuel cells *ECS Trans.* **50** 71–79
- [140] Banu A and Bicer Y 2022 Integration of methane cracking and direct carbon fuel cell with CO<sub>2</sub> capture for hydrogen carrier production *Int. J. Hydrog. Energy* **47** 19502–16
- [141] Banu A, Midilli A and Bicer Y 2023 Exergetic sustainability comparison of turquoise hydrogen conversion to low-carbon fuels *J. Clean. Prod.* **384** 135473
- [142] Ajanovic A, Sayer M and Haas R 2022 The economics and the environmental benignity of different colors of hydrogen *Int. J. Hydrog. Energy* **47** 24136–54
- [143] Semelsberger T A, Borup R L and Greene H L 2006 Dimethyl ether (DME) as an alternative fuel *J. Power Sources* **156** 497–511
- [144] Kim H R, Seo M H, Ahn J H and Kim T S 2023 Thermodynamic design and analysis of SOFC/PEMFC hybrid systems with cascade effects: a perspective on complete carbon dioxide capture and high efficiency *Energy Rep.* **9** 2335–47
- [145] Chen K K, Han Y, Tong Z, Gasda M and Ho W S W 2021 Membrane processes for CO<sub>2</sub> removal and fuel utilization enhancement for solid oxide fuel cells *J. Memb. Sci.* **620** 118846
- [146] AwAC 2014 *Guide pour réaliser un bilan des émissions de Gaz à Effet de Serre en Wallonie et pour utiliser le calculateur de l'AWAC* (available at: [https://awac.be/wp-content/uploads/2021/08/pdf\\_GuideBilanGES\\_V1.0.pdf](https://awac.be/wp-content/uploads/2021/08/pdf_GuideBilanGES_V1.0.pdf))
- [147] AwAC (Agence Wallonne de l'air & du climat) 2014 *Calculateur Carbone* (available at: <https://calculateurs.awac.be>) (Accessed 12 December 2024)
- [148] Semenza J C, Hall D E, Wilson D J, Bontempo B D, Sailor D J and George L A 2008 Public perception of climate change: voluntary mitigation and barriers to behavior change *Am. J. Prev. Med.* **35** 479–87
- [149] Moser S C 2010 Communicating climate change: history, challenges, process and future directions *Wiley Interdiscip. Rev. Clim. Change* **1** 31–53

- [150] Pandey D, Agrawal M and Pandey J S 2010 Carbon footprint: current methods of estimation *Environ. Monit. Assess.* **178** 135–60
- [151] Björn-Hansen A, Katzeff C and Eriksson E 2022 Exploring the use of a carbon footprint calculator challenging everyday habits *Nordic Human-Computer Interaction Conf. (ACM)* pp 1–10
- [152] van Dam S S, Bakker C A and van Hal J D M 2010 Home energy monitors: impact over the medium-term *Build. Res. Inf.* **38** 458–69
- [153] CREG 2023 *Analyse semestrielle de l'évolution des prix de l'énergie—2e semestre 2023* (available at: <https://www.creg.be/sites/default/files/assets/Prices/EvolPrFR.pdf>)
- [154] Paulus N, Davila C and Lemort V 2022 Field-test economic and ecological performance of Proton Exchange Membrane Fuel Cells (PEMFC) used in micro-combined heat and power residential applications (micro-CHP) *Proc. 35th Int. Conf. on Efficiency, Cost, Optimization, Simulation and Environmental Impact of Energy Systems (ECOS2022)* (<https://doi.org/10.11581/dtu.00000267>)
- [155] CWaPE 2005 *Décision CD-5j18-CWaPE relative à "la définition des rendements annuels d'exploitation des installations modernes de référence"* (available at: <https://www.cwape.be/sites/default/files/cwape-documents/50.pdf>)
- [156] Noussan M, Jarre M, Roberto R and Russolillo D 2018 Combined vs separate heat and power production—primary energy comparison in high renewable share contexts *Appl. Energy* **213** 1–10
- [157] Jimenez-Navarro J-P, Kavvadias K, Filippidou F, Pavičević M and Quoilin S 2020 Coupling the heating and power sectors: the role of centralised combined heat and power plants and district heat in a European decarbonised power system *Appl. Energy* **270** 115134
- [158] Electricity Maps 2016 *The Leading Electricity Grid API* (available at: [www.electricitymaps.com](http://www.electricitymaps.com)) (Accessed 19 November 2024)
- [159] Psofopoulos C S, Skoula I, Karras C, Chatzimpiros A and Chionidis M 2010 Electricity savings and CO2 emissions reduction in buildings sector: how important the network losses are in the calculation? *Energy* **35** 485–90
- [160] Chae Y, Kim M and Yoo S H 2012 Does natural gas fuel price cause system marginal price, vice-versa, or neither? A causality analysis *Energy* **47** 199–204
- [161] Siler-Evans K, Azevedo I L and Morgan M G 2012 Marginal emissions factors for the U.S. electricity system *Environ. Sci. Technol.* **46** 4742–8
- [162] ELIA 2023 *Grid Constraints Backbone Antwerp & Liège Region* (available at: <https://economie.fgov.be/sites/default/files/Files/Energy/Annexe-3-Grid-constraints.pdf>)
- [163] Larsen E and van Ackere A 2023 Importing from? Capacity adequacy in a European context *Electr. J.* **36** 107236
- [164] Li X, Lepour D, Heymann F and Maréchal F 2023 Electrification and digitalization effects on sectoral energy demand and consumption: a prospective study towards 2050 *Energy* **279** 127992
- [165] Paulus N and Lemort V 2023 Pollutant testing (NOx, SO2 and CO) of commercialized micro-combined heat and power (mCHP) fuel cells *Proc. 36th Int. Conf. on Efficiency, Cost, Optimization, Simulation and Environmental Impact of Energy Systems (ECOS2023)* (<https://doi.org/10.52202/069564-0104>)
- [166] Paulus N and Lemort V 2022 Field-test performance of solid oxide fuel cells (SOFC) for residential cogeneration applications *Proc. 7th Int. High Performance Buildings Conf. at Purdue (Herrick 2022)* (available at: <https://docs.lib.purdue.edu/cgi/viewcontent.cgi?article=1404&context=ihpbc>)
- [167] Paulus N and Lemort V 2023 Simplified test bench for experimental investigations of space heating appliances *IOP Conf. Ser.: Earth Environ. Sci.* **1185** 012014
- [168] Jafri N, Wong W Y, Doshi V, Yoon L W and Cheah K H 2018 A review on production and characterization of biochars for application in direct carbon fuel cells *Process Saf. Environ. Prot.* **118** 152–66
- [169] Leridon H 2020 Population mondiale: vers une explosion ou une implosion ? *Popul. Soc.* **573** 1–4
- [170] Amatuni L, Ottelin J, Steubing B and Mogollón J M 2020 Does car sharing reduce greenhouse gas emissions? Assessing the modal shift and lifetime shift rebound effects from a life cycle perspective *J. Clean. Prod.* **266** 121869
- [171] Oliveira Panão M J N 2024 Energy ratings as drivers of energy sufficiency in residential buildings: a comprehensive review and future directions *Energy Build* **320** 114583
- [172] Ness D A 2023 Technological efficiency limitations to climate mitigation: why sufficiency is necessary *Build. Cities* **4** 139–57
- [173] Campos I and Marin-González E 2020 People in transitions: energy citizenship, prosumerism and social movements in Europe *Energy Res. Soc. Sci.* **69** 101718
- [174] Wiese F *et al* 2024 The key role of sufficiency for low demand-based carbon neutrality and energy security across Europe *Nat. Commun.* **15** 9043
- [175] Rockström J *et al* 2009 Planetary boundaries: exploring the safe operating space for humanity *Ecol. Soc.* **14** 32
- [176] Dooley K, Christiansen K L, Lund J F, Carton W and Self A 2024 Over-reliance on land for carbon dioxide removal in net-zero climate pledges *Nat. Commun.* **15** 9118
- [177] Pinto G and Oliver-Hoyo M T 2008 Using the relationship between vehicle fuel consumption and CO2 emissions to illustrate chemical principles *J. Chem. Educ.* **85** 218
- [178] Sala S, De Laurentiis V, Barbero Vignola G, Marelli L and Sanye Mengual E 2022 *The Consumer Footprint Calculator, EUR 31089 EN JRC129382* Publications Office of the European Union (<https://doi.org/10.2760/597000>)
- [179] Chatelin S 2016 *Qu'est-ce que la sobriété ?* Fil d'argent (available at: [https://negawatt.org/telechargement/Presse/1601\\_Fil-dargent\\_Qu'est-ce-que-la-sobriete.pdf](https://negawatt.org/telechargement/Presse/1601_Fil-dargent_Qu'est-ce-que-la-sobriete.pdf))
- [180] Falque-Masset M-L, Charles A and Bauquet N 2023 *La sobriété énergétique, élément clé des stratégies bas carbone* 978-2-7371-2239-2 AREC (Institut Paris Region) (available at: [https://www.arec-idf.fr/fileadmin/DataStorage/user\\_upload/sobriete\\_bat.pdf](https://www.arec-idf.fr/fileadmin/DataStorage/user_upload/sobriete_bat.pdf))
- [181] Ménascé D and Levy I (Institut Veolia) 2024 The social and economic challenges of sufficiency *Field Actions Sci. Rep.* (available at: <https://journals.openedition.org/factsreports/7368>)